



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sun Microsystems
Sun Fire 3800**

SPECfp®2006 =

--

SPECfp_base2006 =

2.86

CPU2006 license: 6


Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Mar-2006

Hardware Availability: Nov-2001

Software Availability: May-2006



Hardware

CPU Name: UltraSPARC III Cu
CPU Characteristics:
CPU MHz: 900
FPU: Integrated
CPU(s) enabled: 1 core, 1 chip, 1 core/chip
CPU(s) orderable: 2,4,6,8 chips
Primary Cache: 32 KB I + 64 KB D on chip per chip
Secondary Cache: 8 MB I+D off chip per chip

Software

Operating System: Solaris 10 1/06
Compiler: Sun Studio 11 with patch 120760-03
Auto Parallel: No
File System: ufs
System State: Default
Base Pointers: 32-bit
Peak Pointers: Not Applicable
Other Software: None

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

**Sun Microsystems
Sun Fire 3800**

SPECfp2006 =

--

SPECfp_base2006 =

2.86

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Mar-2006

Hardware Availability: Nov-2001

Software Availability: May-2006

L3 Cache: None
Other Cache: None
Memory: 4 GB (8 x 512 MB DIMM, 4-way interleaved)
Disk Subsystem: 2x36GB 10,000RPM SCSI (RAID 1)
Other Hardware: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	3371	4.03	<u>3371</u>	<u>4.03</u>	3371	4.03						
416.gamess	6638	2.95	<u>6639</u>	<u>2.95</u>	6639	2.95						
433.milc	5598	1.64	5598	1.64	<u>5598</u>	<u>1.64</u>						
434.zeusmp	3260	2.79	<u>3260</u>	<u>2.79</u>	3260	2.79						
435.gromacs	2674	2.67	2669	2.68	<u>2669</u>	<u>2.67</u>						
436.cactusADM	6396	1.87	<u>6396</u>	<u>1.87</u>	6396	1.87						
437.leslie3d	<u>2897</u>	<u>3.25</u>	2896	3.25	2897	3.24						
444.namd	2723	2.95	<u>2721</u>	<u>2.95</u>	2721	2.95						
447.dealII	3489	3.28	<u>3486</u>	<u>3.28</u>	3486	3.28						
450.soplex	<u>4590</u>	<u>1.82</u>	4606	1.81	4585	1.82						
453.povray	1604	3.32	<u>1604</u>	<u>3.32</u>	1604	3.32						
454.calculix	2885	2.86	2885	2.86	<u>2885</u>	<u>2.86</u>						
459.GemsFDTD	3607	2.94	<u>3606</u>	<u>2.94</u>	3601	2.95						
465.tonto	3308	2.97	<u>3309</u>	<u>2.97</u>	3314	2.97						
470.lbm	<u>5970</u>	<u>2.30</u>	5970	2.30	5971	2.30						
481.wrf	3228	3.46	<u>3228</u>	<u>3.46</u>	3227	3.46						
482.sphinx3	3473	5.61	3489	5.59	<u>3481</u>	<u>5.60</u>						

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

Stack limit set to 131072

Platform Notes

Only 1 CPU enabled by the system controller
(prior to boot)

Base Compiler Invocation

C benchmarks:

cc

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire 3800

SPECfp2006 = --

SPECfp_base2006 = 2.86

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Mar-2006

Hardware Availability: Nov-2001

Software Availability: May-2006

Base Compiler Invocation (Continued)

C++ benchmarks:

CC

Fortran benchmarks:

f90

Benchmarks using both Fortran and C:

cc f90

Base Optimization Flags

C benchmarks:

-g -fast -xpagesize=4M

C++ benchmarks:

-g0 -library=stlport4 -fast -xpagesize=4M

Fortran benchmarks:

-g -fast -xpagesize=4M

Benchmarks using both Fortran and C:

-g -fast(cc) -fast(f90) -xpagesize=4M

Base Other Flags

C benchmarks:

-V

C++ benchmarks:

-verbose=version

Fortran benchmarks:

-V

Benchmarks using both Fortran and C:

-V

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/sun-studio.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/sun-studio.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire 3800

SPECfp2006 = --

SPECfp_base2006 = 2.86

CPU2006 license: 6

Test sponsor: Sun Microsystems

Tested by: Sun Microsystems

Test date: Mar-2006

Hardware Availability: Nov-2001

Software Availability: May-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v90.

Report generated on Tue Jul 22 10:01:58 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 24 August 2006.