SPEC® CINT2006 Result

Hewlett-Packard Company

HP Integrity rx8640 (1.6GHz/24MB Dual-Core Intel Itanium 2)

SPECint®_rate2006 = 209

SPECint_rate_base2006 = 193

CPU2006 license: 03		**Test date:**	Sep-2006
Test sponsor:	Hewlett-Packard Company	**Hardware Availability:**	Sep-2006
Tested by:	Hewlett-Packard Company	**Software Availability:**	Sep-2006



Hardware

CPU Name:	Dual-Core Intel Itanium 2 9050
CPU Characteristics:	1.6GHz/24MB, 533MHz FSB
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	16 cores, 8 chips, 2 cores/chip
CPU(s) orderable:	1-16 chips
Primary Cache:	16 KB I + 16 KB D on chip per core
Secondary Cache:	1 MB I + 256 KB D on chip per core
L3 Cache:	12 MB I+D on chip per core
Other Cache:	None
Memory:	64 GB (32x2GB DIMMs)
Disk Subsystem:	73GB 15K RPM SCSI
Other Hardware:	None

Software

Operating System:	HPUX11i-TCOE B.11.23.0609
Compiler:	HP C/aC++ Developer’s Bundle C.11.23.12
Auto Parallel:	No
File System:	vxfs
System State:	Multi-user
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill Smartheap 8.0

Hewlett-Packard Company

HP Integrity rx8640 (1.6GHz/24MB Dual-Core Intel Itanium 2)

SPECint_rate2006 = 209

SPECint_rate_base2006 = 193

CPU2006 license: 03
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company
Test date: Sep-2006
Hardware Availability: Sep-2006
Software Availability: Sep-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	1047	149	**1044**	**150**	1032	151	16	**868**	**180**	869	180	861	181
401.bzip2	16	**1016**	**152**	1026	150	1013	152	16	**988**	**156**	992	156	986	157
403.gcc	16	**916**	**141**	915	141	920	140	16	884	146	881	146	**883**	**146**
429.mcf	16	617	237	609	239	**610**	**239**	16	596	245	580	252	**586**	**249**
445.gobmk	16	927	181	**925**	**181**	922	182	16	737	228	736	228	**736**	**228**
456.hmmer	16	359	416	356	420	**356**	**420**	16	343	435	343	436	**343**	**436**
458.sjeng	16	1289	150	**1302**	**149**	1306	148	16	1114	174	1112	174	**1113**	**174**
462.libquantum	16	1533	216	**1532**	**216**	1528	217	16	1533	216	**1532**	**216**	1532	216
464.h264ref	16	1048	338	**1047**	**338**	1045	339	16	1048	338	**1047**	**338**	1045	339
471.omnetpp	16	1052	95.1	1051	95.1	**1052**	**95.1**	16	984	102	**982**	**102**	982	102
473.astar	16	507	221	**505**	**223**	504	223	16	492	228	**490**	**229**	489	229
483.xalancbmk	16	549	201	**540**	**204**	539	205	16	475	232	473	233	**474**	**233**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
The system had the September 2006 HP-UX 11i v2 Technical Computing
Operating Environment (TCOE) and compilers installed, along with
the following patches:

PHSS_34858  linker + fdp cumulative patch
PHSS_34853  Math Library Cumulative Patch
PHSS_34854  Integrity Unwind Library
PHSS_34855  HP C Compiler (A.06.12)
PHSS_34856  aC++ Compiler (A.06.12)
PHSS_34857  u2comp/be/plugin library patch
PHSS_34395  FORTRAN I/O Library [libIO77]
PHSS_34397  FORTRAN Intrinsics [libF90 B.11.23.17]
PHSS_34399  Fortran Product Patch, v3.1 to v3.1.1
PHKL_34020  Perfmon enhancements and Itanium Dual-Core

The following kernel tunables were set, in addition to the defaults
set by the Technical Computing OE:

dbc_max_pct=20
dbc_min_pct=20
maxdsiz=3221225472
maxssiz=401604608
```

Platform Notes

```
The system was configured as a single partition with 2 cells and
4 processors (8 cores) per cell.  Memory was configured as 50% local
and 50% interleaved.

The following config file entry was used to bind
processes to cells using the HP-UX "mpsched" utility:
submit = let "MYNUM=$SPECCOPYNUM" ; let "LDOM=\$MYNUM/8" ; mpsched -l \$LDOM $command
```

Base Compiler Invocation

C benchmarks:
`/opt/ansic/bin/cc -Ae`

C++ benchmarks:
`/opt/aCC/bin/aCC -Aa`

Base Portability Flags

400.perlbench: -DSPEC_CPU_HPUX_IA64
403.gcc: -DSPEC_CPU_HPUX
462.libquantum: -DSPEC_CPU_HPUX
483.xalancbmk: -DSPEC_CPU_HPUX_IA64

Base Optimization Flags

C benchmarks:
```
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M
-Wl,+pi,64M -Wl,-N
```

C++ benchmarks:
```
+Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M
-Wl,+pi,64M -Wl,-N
/usr/lib/hpux32/libCsup.a /opt/smartheap/SmartHeap_8/lib/libsmartheap.a
```

Peak Compiler Invocation

C benchmarks:
`/opt/ansic/bin/cc -Ae`

C++ benchmarks:
`/opt/aCC/bin/aCC -Aa`

Hewlett-Packard Company

HP Integrity rx8640 (1.6GHz/24MB Dual-Core Intel Itanium 2)

SPECint_rate2006 = 209

SPECint_rate_base2006 = 193

CPU2006 license: 03
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company
Test date: Sep-2006
Hardware Availability: Sep-2006
Software Availability: Sep-2006

Peak Portability Flags

400.perlbench: -DSPEC_CPU_HPUX_IA64
403.gcc: -DSPEC_CPU_HPUX
462.libquantum: -DSPEC_CPU_HPUX
483.xalancbmk: -DSPEC_CPU_HPUX_IA64

Peak Optimization Flags

C benchmarks:

400.perlbench: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M -Wl,-N

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: Same as 400.perlbench

445.gobmk: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Odataprefetch=direct

456.hmmer: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M

458.sjeng: Same as 445.gobmk

462.libquantum: Same as 456.hmmer

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M /usr/lib/hpux32/libCsup.a /opt/smartheap/SmartHeap_8/lib/libsmartheap.a

473.astar: +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Onoparmsoverlap /usr/lib/hpux32/libCsup.a /opt/smartheap/SmartHeap_8/lib/libsmartheap.a

483.xalancbmk: +Oprofile=collect:all(pass 1) +Oprofile=use(pass 2) +Ofaster +Otype_safety=ansi -Wl,-a,archive_shared -Wl,+pd,64M -Wl,+pi,64M +Onoparmsoverlap /usr/lib/hpux32/libCsup.a /opt/smartheap/SmartHeap_8/lib/libsmartheap.a

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090715.06.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090715.06.xml

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:05:54 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 October 2006.