SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3500 (Intel Xeon E5335)

SPECint®_rate2006 = Not Run

SPECint_rate_base2006 = 67.2

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jan-2007
Hardware Availability: Feb-2007
Software Availability: Aug-2006



Hardware

CPU Name:	Intel Xeon E5335
CPU Characteristics:	1066MHz system bus
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	8 GB (8 x 1GB DDR2-5300F ECC)
Disk Subsystem:	1 x 80 GB SATA, 7200 RPM
Other Hardware:	None

Software

Operating System:	Microsoft Windows Server 2003 Enterprise x64 Edition + SP1 (64-bit)
Compiler:	Intel C++ Compiler for IA32 version 9.1 Build no 20060816 Microsoft Visual Studio .Net 2003 (for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	Not Applicable
Other Software:	Smart Heap Library, Version 8

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

IBM Corporation

IBM System x3500 (Intel Xeon E5335)

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 67.2

CPU2006 license: 11
Test sponsor: IBM Corporation
Tested by: IBM Corporation

Test date: Jan-2007
Hardware Availability: Feb-2007
Software Availability: Aug-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	691	113	708	110	**707**	**111**							
401.bzip2	8	1232	62.7	1227	62.9	**1229**	**62.8**							
403.gcc	8	1961	32.8	**2066**	**31.2**	2076	31.0							
429.mcf	8	**1203**	**60.6**	1201	60.7	1204	60.6							
445.gobmk	8	821	102	819	102	**819**	**102**							
456.hmmer	8	1110	67.2	**1110**	**67.2**	1111	67.2							
458.sjeng	8	994	97.4	994	97.4	**994**	**97.4**							
462.libquantum	8	5642	29.4	**5642**	**29.4**	5642	29.4							
464.h264ref	8	1086	163	**1086**	**163**	1085	163							
471.omnetpp	8	**1150**	**43.5**	1150	43.5	1150	43.5							
473.astar	8	1018	55.2	**1019**	**55.1**	1021	55.0							
483.xalancbmk	8	653	84.5	654	84.4	**654**	**84.4**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
This result was measured on an IBM System X 3400.   IBM System X 3400 and IBM System
X 3500 are electronically equivalent.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic91-flags.20090714.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:14:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 February 2007.