SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML370 G5
(2.66 GHz, Intel Xeon processor X5355)

SPECint®_rate2006 = 45.8

SPECint_rate_base2006 = 44.4

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon X5355
CPU Characteristics:	2.66GHz, 4x2 MB L2 shared, 1333 MHz bus
CPU MHz:	2666
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8x2 GB PC2-5300F CL5)
Disk Subsystem:	2x72 GB 10 K SAS
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise X64 Edition
Compiler:	Intel C++ Compiler 9.1 for 32-bit apps, Build 20060323Z Package ID: W_CC_P_9.1.020 Microsoft Visual Studio .NET 2003 (v7.1.3088, for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant ML370 G5
(2.66 GHz, Intel Xeon processor X5355)

SPECint_rate2006 = 45.8

SPECint_rate_base2006 = 44.4

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Nov-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	530	73.8	**531**	**73.6**	532	73.4	4	**487**	**80.3**	489	80.0	486	80.4
401.bzip2	4	950	40.6	950	40.6	**950**	**40.6**	4	933	41.4	**933**	**41.4**	931	41.4
403.gcc	4	1423	22.6	1442	22.3	**1430**	**22.5**	4	1451	22.2	**1448**	**22.2**	1448	22.2
429.mcf	4	**916**	**39.8**	916	39.8	917	39.8	4	**916**	**39.8**	916	39.8	917	39.8
445.gobmk	4	**635**	**66.1**	633	66.2	636	66.0	4	563	74.5	**564**	**74.4**	568	73.9
456.hmmer	4	**840**	**44.4**	840	44.4	840	44.4	4	819	45.6	**818**	**45.6**	818	45.6
458.sjeng	4	**763**	**63.5**	763	63.5	763	63.5	4	702	68.9	702	69.0	**702**	**69.0**
462.libquantum	4	4326	19.2	4326	19.2	**4326**	**19.2**	4	**4323**	**19.2**	4323	19.2	4324	19.2
464.h264ref	4	821	108	**822**	**108**	822	108	4	805	110	**805**	**110**	805	110
471.omnetpp	4	881	28.4	883	28.3	**883**	**28.3**	4	858	29.1	**858**	**29.1**	859	29.1
473.astar	4	790	35.5	**791**	**35.5**	791	35.5	4	793	35.4	793	35.4	**793**	**35.4**
483.xalancbmk	4	**492**	**56.1**	493	56.0	492	56.1	4	481	57.4	482	57.3	**482**	**57.3**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Power Regulator set to Static High Performance Mode in BIOS.
Adjacent Sector Prefetch disabled in BIOS.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib           -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99

C++ benchmarks:
icl -Qvc7.1

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
shlw32m.lib -link /FORCE:MULTIPLE

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: Same as 400.perlbench

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 400.perlbench

Continued on next page

Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:24:58 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 February 2007.