SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c
(2.66 GHz, Intel Xeon processor X5355)

SPECint®_rate2006 = 82.2

SPECint_rate_base2006 = 79.6

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon X5355
CPU Characteristics:	2.66 GHz, 2x4 MB L2 shared, 1333 MHz bus
CPU MHz:	2666
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8x2 GB PC2-5300F CL5)
Disk Subsystem:	2x72 GB 10 K SAS
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise X64 Edition
Compiler:	Intel C++ Compiler 9.1 for 32-bit apps, Build 20060323Z Package ID: W_CC_P_9.1.020 Microsoft Visual Studio .NET 2003 (v7.1.3088, for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL460c
(2.66 GHz, Intel Xeon processor X5355)

SPECint_rate2006 = 82.2

SPECint_rate_base2006 = 79.6

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Feb-2007
Hardware Availability: Jan-2007
Software Availability: Nov-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	**535**	**146**	535	146	535	146	8	490	159	491	159	**490**	**159**
401.bzip2	8	996	77.5	994	77.6	**996**	**77.5**	8	**981**	**78.7**	983	78.5	980	78.8
403.gcc	8	2006	32.1	**1982**	**32.5**	1938	33.2	8	**1987**	**32.4**	1966	32.8	1992	32.3
429.mcf	8	1141	63.9	**1140**	**64.0**	1139	64.0	8	1141	63.9	**1140**	**64.0**	1139	64.0
445.gobmk	8	632	133	634	132	**634**	**132**	8	566	148	**566**	**148**	566	148
456.hmmer	8	842	88.6	**842**	**88.6**	842	88.6	8	820	91.0	820	91.0	**820**	**91.0**
458.sjeng	8	766	126	765	126	**766**	**126**	8	705	137	705	137	**705**	**137**
462.libquantum	8	**5407**	**30.7**	5407	30.7	5407	30.7	8	**5407**	**30.7**	5407	30.7	5406	30.7
464.h264ref	8	**822**	**215**	822	216	823	215	8	806	220	805	220	**805**	**220**
471.omnetpp	8	1100	45.5	**1101**	**45.4**	1102	45.4	8	**1080**	**46.3**	1080	46.3	1080	46.3
473.astar	8	**871**	**64.5**	871	64.5	870	64.5	8	874	64.3	872	64.4	**874**	**64.3**
483.xalancbmk	8	571	96.7	**572**	**96.5**	573	96.4	8	564	97.9	**565**	**97.6**	566	97.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
Power Regulator set to Static High Performance Mode in BIOS.
Adjacent Sector Prefetch disabled in BIOS.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99

C++ benchmarks:
icl -Qvc7.1

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
shlw32m.lib -link /FORCE:MULTIPLE

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: Same as 400.perlbench

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 400.perlbench

Continued on next page

Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/hp-ic91-flags.20090715.02.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:22:15 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 20 February 2007.