SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX201 (Intel Xeon E5345)

SPECint®_rate2006 = 71.7

SPECint_rate_base2006 = 71.7

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Feb-2007
Hardware Availability: Feb-2007
Software Availability: May-2006



Hardware

CPU Name:	Intel Xeon E5345
CPU Characteristics:	1333MHz system bus
CPU MHz:	2330
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1-2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8x2GB DDR2-RAM PC2-5300F CAS 5-5-5)
Disk Subsystem:	73 GB SCSI, 10000RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition + SP1 (32-bit)
Compiler:	Intel C++ Compiler for IA32 version 9.1 Package ID W_CC_C_9.1.025 Build no 20060519Z Microsoft Visual Studio .NET 2003 7.1.3088 (for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	Microquill SmartHeap Library v.8.0 for SMP

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Itautec

Servidor Itautec MX201 (Intel Xeon E5345)

SPECint_rate2006 = 71.7

SPECint_rate_base2006 = 71.7

CPU2006 license: 9001
Test sponsor: Itautec
Tested by: Itautec

Test date: Feb-2007
Hardware Availability: Feb-2007
Software Availability: May-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	629	124	630	124	**629**	**124**	8	629	124	630	124	**629**	**124**
401.bzip2	8	1081	71.4	1080	71.5	**1080**	**71.5**	8	1081	71.4	1080	71.5	**1080**	**71.5**
403.gcc	8	**2205**	**29.2**	2207	29.2	2197	29.3	8	**2205**	**29.2**	2207	29.2	2197	29.3
429.mcf	8	**1283**	**56.9**	1283	56.9	1284	56.8	8	**1283**	**56.9**	1283	56.9	1284	56.8
445.gobmk	8	713	118	710	118	**713**	**118**	8	713	118	710	118	**713**	**118**
456.hmmer	8	**958**	**77.9**	958	77.9	957	78.0	8	**958**	**77.9**	958	77.9	957	78.0
458.sjeng	8	**874**	**111**	874	111	874	111	8	**874**	**111**	874	111	874	111
462.libquantum	8	5458	30.4	5460	30.4	**5459**	**30.4**	8	5458	30.4	5460	30.4	**5459**	**30.4**
464.h264ref	8	**935**	**189**	935	189	934	189	8	**935**	**189**	935	189	934	189
471.omnetpp	8	**1242**	**40.3**	1244	40.2	1241	40.3	8	**1242**	**40.3**	1244	40.2	1241	40.3
473.astar	8	948	59.2	949	59.2	**948**	**59.2**	8	948	59.2	949	59.2	**948**	**59.2**
483.xalancbmk	8	611	90.4	610	90.5	**610**	**90.5**	8	611	90.4	610	90.5	**610**	**90.5**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
This result was measured on the Servidor Itautec MX221.
The Servidor Itautec MX221 and the Servidor Itautec MX201
are electronically equivalent.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlSMPMt.lib            -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
-fast -Qcxx_features /F512000000 shlSMPMt.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Optimization Flags

C benchmarks:

400.perlbench: basepeak = yes

401.bzip2: basepeak = yes

403.gcc: basepeak = yes

429.mcf: basepeak = yes

445.gobmk: basepeak = yes

456.hmmer: basepeak = yes

458.sjeng: basepeak = yes

462.libquantum: basepeak = yes

464.h264ref: basepeak = yes

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: basepeak = yes

483.xalancbmk: basepeak = yes

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Itautec-ic91-flags.20090714.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Itautec-ic91-flags.20090714.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:31:00 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 7 March 2007.