# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

## Acer Altos R720 (Intel Xeon X5355, 2.66GHz)

SPECfp®_rate2006 = 57.2

SPECfp_rate_base2006 = 56.3

**CPU2006 license:** 97
**Test sponsor:** Acer Incorporated
**Tested by:** Acer Incorporated

**Test date:** Feb-2007
**Hardware Availability:** Nov-2006
**Software Availability:** Nov-2006




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon X5355 |
| CPU Characteristics: | 1333MHz system bus |
| CPU MHz: | 2666 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 8 MB I+D on chip per chip, 4 MB shared / 2 cores |

Continued on next page

### Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 10 EM64T (Kernel 2.6.16.21-0.8-smp) |
| Compiler: | Intel C++ Compiler 9.1 for Intel EM64T-based Package ID l_cc_c_9.1.042 Build no 20060707<br>Intel Fortran Compiler for Intel EM64T-based applications, Version 9.1<br>Package ID l_fc_c_9.1.040 Build no 20061101 |
| Auto Parallel: | No |
| File System: | ext2 |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

## Acer Altos R720 (Intel Xeon X5355, 2.66GHz)

SPECfp_rate2006 = 57.2

SPECfp_rate_base2006 = 56.3

**CPU2006 license:** 97
**Test sponsor:** Acer Incorporated
**Tested by:** Acer Incorporated

**Test date:** Feb-2007
**Hardware Availability:** Nov-2006
**Software Availability:** Nov-2006

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD
Other Hardware: None

System State: Default
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: --

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 8 | 3411 | 31.9 | **3407** | **31.9** | 3403 | 31.9 | 8 | 3408 | 31.9 | **3408** | **31.9** | 3408 | 31.9 |
| 416.gamess | 8 | 1071 | 146 | **1072** | **146** | 1073 | 146 | 8 | **1158** | **135** | 1158 | 135 | 1160 | 135 |
| 433.milc | 8 | 3482 | 21.1 | 3477 | 21.1 | **3478** | **21.1** | 8 | 3505 | 21.0 | **3500** | **21.0** | 3499 | 21.0 |
| 434.zeusmp | 8 | 1164 | 62.5 | **1161** | **62.7** | 1161 | 62.7 | 8 | 1158 | 62.9 | **1159** | **62.8** | 1160 | 62.8 |
| 435.gromacs | 8 | **460** | **124** | 458 | 125 | 463 | 123 | 8 | 444 | 129 | 445 | 128 | **444** | **129** |
| 436.cactusADM | 8 | **1378** | **69.4** | 1381 | 69.2 | 1373 | 69.6 | 8 | 1380 | 69.3 | **1389** | **68.8** | 1396 | 68.5 |
| 437.leslie3d | 8 | 3235 | 23.2 | 3251 | 23.1 | **3249** | **23.1** | 8 | 3261 | 23.1 | **3254** | **23.1** | 3240 | 23.2 |
| 444.namd | 8 | 576 | 111 | **574** | **112** | 574 | 112 | 8 | 581 | 110 | 584 | 110 | **582** | **110** |
| 447.dealII | 8 | 728 | 126 | **721** | **127** | 716 | 128 | 8 | 725 | 126 | **698** | **131** | 695 | 132 |
| 450.soplex | 8 | **2338** | **28.5** | 2334 | 28.6 | 2340 | 28.5 | 8 | 2339 | 28.5 | 2341 | 28.5 | **2340** | **28.5** |
| 453.povray | 8 | 290 | 147 | **291** | **146** | 293 | 145 | 8 | **223** | **191** | 223 | 191 | 223 | 191 |
| 454.calculix | 8 | **642** | **103** | 644 | 103 | 634 | 104 | 8 | 625 | 106 | **632** | **105** | 633 | 104 |
| 459.GemsFDTD | 8 | 4048 | 21.0 | 4037 | 21.0 | **4038** | **21.0** | 8 | 4064 | 20.9 | 4049 | 21.0 | **4050** | **21.0** |
| 465.tonto | 8 | 1003 | 78.5 | 1024 | 76.8 | **1004** | **78.4** | 8 | 989 | 79.6 | 977 | 80.5 | **982** | **80.2** |
| 470.lbm | 8 | **4559** | **24.1** | 4562 | 24.1 | 4558 | 24.1 | 8 | **4558** | **24.1** | 4558 | 24.1 | 4559 | 24.1 |
| 481.wrf | 8 | 1950 | 45.8 | 1947 | 45.9 | **1950** | **45.8** | 8 | **1957** | **45.7** | 1960 | 45.6 | 1951 | 45.8 |
| 482.sphinx3 | 8 | 3684 | 42.3 | **3678** | **42.4** | 3676 | 42.4 | 8 | 3631 | 42.9 | **3635** | **42.9** | 3635 | 42.9 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run

## General Notes

This result was measured on the Acer Altos R520.
The Altos R720 and Altos R520 are electronically equivalent.

## Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

## Peak Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

C++ benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

Fortran benchmarks:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

Benchmarks using both Fortran and C:
-prof_gen(pass 1) -prof_use(pass 2) -fast -auto_ilp32

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Acer-CPU2006-ic91-flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Acer-CPU2006-ic91-flags.xml

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

Acer Altos R720 (Intel Xeon X5355, 2.66GHz)

SPECfp_rate2006 = 57.2

SPECfp_rate_base2006 = 56.3

**CPU2006 license:** 97
**Test sponsor:** Acer Incorporated
**Tested by:** Acer Incorporated

**Test date:** Feb-2007
**Hardware Availability:** Nov-2006
**Software Availability:** Nov-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 10:54:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 March 2007.