SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T880 (3.20 GHz, Intel Xeon 7130M)

SPECfp®2006 = 10.6

SPECfp_base2006 = 10.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Mar-2007
Hardware Availability: Sep-2006
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon 7130M
CPU Characteristics:	3.2GHz, 800MHz bus
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 2 cores/chip
CPU(s) orderable:	1,2,4 chips
Primary Cache:	12 K micro-ops I + 16 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core

Continued on next page

Software

Operating System:	Windows Server 2003 Enterprise X64 Edition
Compiler:	Intel C++ Compiler 9.1 for 32-bit Build 20061103Z Package ID: W_CC_C_9.1.033 Intel Fortran Compiler 9.1 for 32-bit Build 20061103Z Package ID: W_FC_C_9.1.033 Microsoft Visual Studio .NET 2003 (libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T880 (3.20 GHz, Intel Xeon 7130M)

SPECfp2006 = 10.6

SPECfp_base2006 = 10.4

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Mar-2007
Hardware Availability: Sep-2006
Software Availability: Nov-2006

L3 Cache: 8 MB I+D on chip per chip
Other Cache: None
Memory: 32 GB (667 MHz ECC CL5 DDR2 FB-DIMM)
Disk Subsystem: 2x36GB SAS 15000 rpm
Other Hardware: None

Base Pointers: 32-bit
Peak Pointers: 32-bit
Other Software: MicroQuill SmartHeap Library 8.0 (shlW32M.lib)

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	944	14.4	944	14.4	**944**	**14.4**	949	14.3	949	14.3	**949**	**14.3**
416.gamess	**2090**	**9.37**	2090	9.37	2090	9.37	**2090**	**9.37**	2090	9.37	2090	9.37
433.milc	1389	6.61	1390	6.61	**1390**	**6.61**	**1378**	**6.66**	1378	6.66	1379	6.66
434.zeusmp	1145	7.95	1145	7.95	**1145**	**7.95**	1154	7.88	1154	7.88	**1154**	**7.88**
435.gromacs	795	8.98	795	8.98	**795**	**8.98**	795	8.98	795	8.98	**795**	**8.98**
436.cactusADM	**852**	**14.0**	852	14.0	852	14.0	813	14.7	813	14.7	**813**	**14.7**
437.leslie3d	1119	8.40	1119	8.40	**1119**	**8.40**	**1116**	**8.42**	1116	8.42	1116	8.42
444.namd	872	9.20	872	9.20	**872**	**9.20**	**874**	**9.18**	874	9.18	874	9.18
447.dealII	891	12.8	**891**	**12.8**	891	12.8	800	14.3	800	14.3	**800**	**14.3**
450.soplex	**810**	**10.3**	810	10.3	810	10.3	795	10.5	795	10.5	**795**	**10.5**
453.povray	**474**	**11.2**	474	11.2	474	11.2	**427**	**12.4**	427	12.4	427	12.4
454.calculix	1005	8.21	**1005**	**8.21**	1005	8.21	1004	8.21	1004	8.21	**1004**	**8.21**
459.GemsFDTD	**1263**	**8.40**	1263	8.40	1263	8.40	1276	8.31	1276	8.31	**1276**	**8.31**
465.tonto	1299	7.57	**1299**	**7.57**	1299	7.57	1275	7.72	**1275**	**7.72**	1274	7.72
470.lbm	**821**	**16.7**	821	16.7	821	16.7	823	16.7	823	16.7	**823**	**16.7**
481.wrf	**1000**	**11.2**	1000	11.2	1000	11.2	**1000**	**11.2**	1000	11.2	1000	11.2
482.sphinx3	**1048**	**18.6**	1048	18.6	1048	18.6	968	20.1	**969**	**20.1**	969	20.1

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Other Configuration Notes
/NUMPROC=1 flag was added to boot.ini to invoke
uniprocessor environment

The NovaScale T880 and the NovaScale R480 models are
electronically equivalent.
The results have been measured on a NovaScale R480 model.
```

Base Compiler Invocation

C benchmarks:
```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:
```
icl -Qvc7.1
```

Fortran benchmarks:
```
ifort
```

Benchmarks using both Fortran and C:
```
icl -Qvc7.1 -Qc99 ifort
```

Base Portability Flags

436.cactusADM: `-Qlowercase /assume:underscore`
444.namd: `-TP`
447.dealII: `-DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG -DBOOST_NO_INTRINSIC_WCHAR_T`
453.povray: `-DSPEC_CPU_WINDOWS_ICL`
454.calculix: `-DSPEC_CPU_NOZMODIFIER -Qlowercase`
481.wrf: `-DSPEC_CPU_WINDOWS_ICL`

Base Optimization Flags

C benchmarks:
```
-fast /F950000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

C++ benchmarks:
```
-fast -Qcxx_features /F950000000 shlw32m.lib
           -link /FORCE:MULTIPLE
```

Fortran benchmarks:
```
-fast /F950000000           -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:
```
-fast /F950000000           -link /FORCE:MULTIPLE
```

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:
```
icl -Qvc7.1
```

Continued on next page

Peak Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc7.1 -Qc99 ifort

Peak Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG -DBOOST_NO_INTRINSIC_WCHAR_T
453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Peak Optimization Flags

C benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F950000000 -link /FORCE:MULTIPLE

416.gamess: basepeak = yes

434.zeusmp: Same as 410.bwaves

437.leslie3d: Same as 410.bwaves

459.GemsFDTD: Same as 410.bwaves

465.tonto: Same as 410.bwaves

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

Continued on next page

Peak Optimization Flags (Continued)

436.cactusADM: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast /F950000000 -link /FORCE:MULTIPLE`

454.calculix: `Same as 436.cactusADM`

481.wrf: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/flags.20090714.00.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/flags.20090714.00.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:27:33 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 1 May 2007.