SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T880 (3.20 GHz, Intel Xeon 7130M)

SPECfp®_rate2006 = 49.6

SPECfp_rate_base2006 = 48.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Mar-2007
Hardware Availability: Sep-2006
Software Availability: Nov-2006



Hardware

CPU Name:	Intel Xeon 7130M
CPU Characteristics:	3.2GHz, 800MHz bus
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chip
CPU(s) orderable:	1,2,4 chips
Primary Cache:	12 K micro-ops I + 16 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core

Continued on next page

Software

Operating System:	Windows Server 2003 Enterprise X64 Edition
Compiler:	Intel C++ Compiler 9.1 for 32-bit Build 20061103Z Package ID: W_CC_C_9.1.033 Intel Fortran Compiler 9.1 for 32-bit Build 20061103Z Package ID: W_FC_C_9.1.033 Microsoft Visual Studio .NET 2003 (libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale T880 (3.20 GHz, Intel Xeon 7130M)

SPECfp_rate2006 = 49.6

SPECfp_rate_base2006 = 48.7

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Mar-2007
Hardware Availability: Sep-2006
Software Availability: Nov-2006

L3 Cache: 8 MB I+D on chip per chip
Other Cache: None
Memory: 32 GB (667 MHz ECC CL5 DDR2 FB-DIMM)
Disk Subsystem: 2x36GB SAS 15000 rpm
Other Hardware: None

Base Pointers: 32-bit
Peak Pointers: 32-bit
Other Software: MicroQuill SmartHeap Library 8.0 (shlW32M.lib)

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3268	33.3	3275	33.2	**3269**	**33.3**	8	3274	33.2	3272	33.2	**3273**	**33.2**
416.gamess	8	2087	75.0	**2087**	**75.0**	2087	75.1	8	2087	75.0	**2087**	**75.0**	2087	75.1
433.milc	8	3745	19.6	3756	19.6	**3754**	**19.6**	8	3753	19.6	3754	19.6	**3754**	**19.6**
434.zeusmp	8	1316	55.3	1329	54.8	**1329**	**54.8**	8	1328	54.8	**1333**	**54.6**	1345	54.1
435.gromacs	8	798	71.6	797	71.6	**798**	**71.6**	8	798	71.6	797	71.6	**798**	**71.6**
436.cactusADM	8	1265	75.6	**1265**	**75.6**	1266	75.5	8	**1247**	**76.6**	1248	76.6	1247	76.7
437.leslie3d	8	2970	25.3	2964	25.4	**2969**	**25.3**	8	2975	25.3	2967	25.3	**2974**	**25.3**
444.namd	8	872	73.6	**872**	**73.6**	872	73.6	8	874	73.4	**874**	**73.4**	874	73.4
447.dealII	8	**1016**	**90.1**	1004	91.2	1017	90.0	8	912	100	**920**	**99.5**	945	96.8
450.soplex	8	1966	33.9	1968	33.9	**1967**	**33.9**	8	1942	34.4	**1940**	**34.4**	1938	34.4
453.povray	8	473	89.9	**473**	**89.9**	474	89.8	8	427	99.6	428	99.4	**427**	**99.6**
454.calculix	8	**1030**	**64.1**	1031	64.0	1025	64.4	8	**1024**	**64.5**	1024	64.4	1023	64.5
459.GemsFDTD	8	3687	23.0	3690	23.0	**3689**	**23.0**	8	3619	23.5	3622	23.4	**3622**	**23.4**
465.tonto	8	1517	51.9	1527	51.5	**1526**	**51.6**	8	**1494**	**52.7**	1495	52.6	1490	52.8
470.lbm	8	4542	24.2	**4542**	**24.2**	4545	24.2	8	**4541**	**24.2**	4540	24.2	4544	24.2
481.wrf	8	1884	47.4	1889	47.3	**1885**	**47.4**	8	1884	47.4	1889	47.3	**1885**	**47.4**
482.sphinx3	8	**2048**	**76.1**	2048	76.1	2050	76.1	8	1998	78.0	**1999**	**78.0**	2005	77.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Other Configuration Notes

The NovaScale T880 and the NovaScale R480 models are
electronically equivalent.
The results have been measured on a NovaScale R480 model.
```

Base Compiler Invocation

C benchmarks:
```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:
```
icl -Qvc7.1
```

Fortran benchmarks:
```
ifort
```

Benchmarks using both Fortran and C:
```
icl -Qvc7.1 -Qc99 ifort
```

Base Portability Flags

436.cactusADM: `-Qlowercase /assume:underscore`
444.namd: `-TP`
447.dealII: `-DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG -DBOOST_NO_INTRINSIC_WCHAR_T`
453.povray: `-DSPEC_CPU_WINDOWS_ICL`
454.calculix: `-DSPEC_CPU_NOZMODIFIER -Qlowercase`
481.wrf: `-DSPEC_CPU_WINDOWS_ICL`

Base Optimization Flags

C benchmarks:
```
-fast /F950000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

C++ benchmarks:
```
-fast -Qcxx_features /F950000000 shlw32m.lib
            -link /FORCE:MULTIPLE
```

Fortran benchmarks:
```
-fast /F950000000            -link /FORCE:MULTIPLE
```

Benchmarks using both Fortran and C:
```
-fast /F950000000            -link /FORCE:MULTIPLE
```

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:
```
icl -Qvc7.1
```

Continued on next page

Peak Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc7.1 -Qc99 ifort

Peak Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG -DBOOST_NO_INTRINSIC_WCHAR_T
453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Peak Optimization Flags

C benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features /F950000000 shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F950000000 -link /FORCE:MULTIPLE

416.gamess: basepeak = yes

434.zeusmp: Same as 410.bwaves

437.leslie3d: Same as 410.bwaves

459.GemsFDTD: Same as 410.bwaves

465.tonto: Same as 410.bwaves

Benchmarks using both Fortran and C:

435.gromacs: basepeak = yes

Continued on next page

Peak Optimization Flags (Continued)

436.cactusADM: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast /F950000000 -link /FORCE:MULTIPLE`

454.calculix: `Same as 436.cactusADM`

481.wrf: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/flags.20090714.00.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/flags.20090714.00.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:35:18 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 1 May 2007.