SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor 5110, 1.60 GHz

SPECfp®_rate2006 = 30.0

SPECfp_rate_base2006 = 29.1

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: May-2007
Hardware Availability: Jul-2006
Software Availability: Feb-2007



Hardware

CPU Name:	Intel Xeon 5110
CPU Characteristics:	1067 MHz system bus
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip

Continued on next page

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86_64
Compiler:	Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package-ID: l_cc_p_9.1.047 Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070215, Package ID: l_fc_p_9.1.043
Auto Parallel:	No
File System:	ext2

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

PRIMERGY RX300 S3, Intel Xeon processor 5110, 1.60 GHz

SPECfp_rate2006 = 30.0

SPECfp_rate_base2006 = 29.1

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: May-2007
Hardware Availability: Jul-2006
Software Availability: Feb-2007

L3 Cache: None
Other Cache: None
Memory: 8 GB (8x1 GB DDR2 PC2-5300F, 2 rank, CAS 5-5-5, with ECC)
Disk Subsystem: SAS (73GB 15400 rpm)
Other Hardware: None

System State: Multiuser, Runlevel 3
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	4	2088	26.0	2088	26.0	**2088**	**26.0**	4	2088	26.0	2088	26.0	**2088**	**26.0**
416.gamess	4	1793	43.7	**1794**	**43.7**	1797	43.6	4	1793	43.7	**1794**	**43.7**	1797	43.6
433.milc	4	**2117**	**17.3**	2117	17.3	2118	17.3	4	2236	16.4	**2236**	**16.4**	2235	16.4
434.zeusmp	4	1144	31.8	**1141**	**31.9**	1138	32.0	4	1147	31.7	**1152**	**31.6**	1153	31.6
435.gromacs	4	744	38.4	**739**	**38.6**	739	38.7	4	714	40.0	714	40.0	**714**	**40.0**
436.cactusADM	4	1257	38.0	**1258**	**38.0**	1271	37.6	4	1257	38.0	**1258**	**38.0**	1271	37.6
437.leslie3d	4	2043	18.4	**2038**	**18.5**	2031	18.5	4	2043	18.4	**2038**	**18.5**	2031	18.5
444.namd	4	958	33.5	**956**	**33.6**	955	33.6	4	958	33.5	**956**	**33.6**	955	33.6
447.dealII	4	**872**	**52.5**	871	52.5	876	52.2	4	846	54.1	880	52.0	**854**	**53.6**
450.soplex	4	1541	21.7	**1541**	**21.6**	1546	21.6	4	**1429**	**23.3**	1421	23.5	1430	23.3
453.povray	4	486	43.8	**486**	**43.8**	487	43.7	4	**369**	**57.7**	378	56.3	368	57.8
454.calculix	4	982	33.6	**987**	**33.4**	988	33.4	4	964	34.2	**961**	**34.3**	959	34.4
459.GemsFDTD	4	2493	17.0	2512	16.9	**2511**	**16.9**	4	2493	17.0	2512	16.9	**2511**	**16.9**
465.tonto	4	1231	32.0	1229	32.0	**1229**	**32.0**	4	**1196**	**32.9**	1203	32.7	1194	33.0
470.lbm	4	**3485**	**15.8**	3483	15.8	3485	15.8	4	**3291**	**16.7**	3292	16.7	3291	16.7
481.wrf	4	1413	31.6	1410	31.7	**1413**	**31.6**	4	1413	31.6	1410	31.7	**1413**	**31.6**
482.sphinx3	4	2549	30.6	2565	30.4	**2558**	**30.5**	4	2401	32.5	2383	32.7	**2384**	**32.7**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
```

General Notes

```
The system bus runs at 1067 MHz

All binaries were built with 64-bit Intel compiler except:
433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with
32-bit Intel compiler by changing the path for include and library files.

The PRIMERGY RX300 S3 and the PRIMERGY TX300 S3 are electronically equivalent.
```

Continued on next page

General Notes (Continued)

```
For information about Fujitsu Siemens Computers in your country please see:
http://www.fujitsu-siemens.com/countries
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Continued on next page

Base Optimization Flags (Continued)

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

Peak Compiler Invocation

C benchmarks:
/opt/intel/cc/9.1.047/bin/icc -I/opt/intel/cc/9.1.047/include
-L/opt/intel/cc/9.1.047/lib

C++ benchmarks (except as noted below):
icpc

450.soplex: /opt/intel/cc/9.1.047/bin/icpc
-I/opt/intel/cc/9.1.047/include -L/opt/intel/cc/9.1.047/lib

Fortran benchmarks (except as noted below):
ifort

434.zeusmp: /opt/intel/fc/9.1.043/bin/ifort
-I/opt/intel/fc/9.1.043/include -L/opt/intel/fc/9.1.043/lib

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

433.milc: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

470.lbm: `Same as 433.milc`

482.sphinx3: `-fast`

C++ benchmarks:

444.namd: `basepeak = yes`

447.dealII: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

450.soplex: `Same as 447.dealII`

453.povray: `Same as 447.dealII`

Fortran benchmarks:

410.bwaves: `basepeak = yes`

416.gamess: `basepeak = yes`

434.zeusmp: `-fast`

437.leslie3d: `basepeak = yes`

459.GemsFDTD: `basepeak = yes`

465.tonto: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

Benchmarks using both Fortran and C:

435.gromacs: `-prof_gen`(pass 1) `-prof_use`(pass 2) `-fast`

436.cactusADM: `basepeak = yes`

454.calculix: `Same as 435.gromacs`

481.wrf: `basepeak = yes`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.09.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:47:42 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 May 2007.