SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5160,3.00GHz)

SPECint®_rate2006 = 54.4

SPECint_rate_base2006 = 52.6

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006



Hardware

CPU Name:	Intel Xeon 5160
CPU Characteristics:	3.00 GHz, 4 MB L2, 1333 MHz system bus
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem:	1x73 GB SAS, 15000 RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition X64 Edition Service Pack1
Compiler:	Intel C++ Compiler for IA32 version 9.1 Package ID W_CC_C_9.1.033 Build no 20061103Z Microsoft Visual Studio .NET 2003 (lib & linker)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library 8.0 (shlW32M.lib)

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor 5160,3.00GHz)

SPECint_rate2006 = 54.4

SPECint_rate_base2006 = 52.6

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: May-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	472	82.8	472	82.8	**472**	**82.8**	4	433	90.2	434	90.1	**434**	**90.1**
401.bzip2	4	858	45.0	**856**	**45.1**	853	45.3	4	839	46.0	839	46.0	**839**	**46.0**
403.gcc	4	**1203**	**26.8**	1200	26.8	1213	26.6	4	1209	26.6	**1202**	**26.8**	1194	27.0
429.mcf	4	770	47.4	769	47.4	**769**	**47.4**	4	795	45.9	**796**	**45.8**	796	45.8
445.gobmk	4	555	75.7	557	75.3	**555**	**75.6**	4	**495**	**84.9**	494	84.9	495	84.7
456.hmmer	4	746	50.0	746	50.0	**746**	**50.0**	4	**726**	**51.4**	726	51.4	726	51.4
458.sjeng	4	690	70.2	**690**	**70.2**	690	70.1	4	**636**	**76.1**	636	76.1	637	76.0
462.libquantum	4	2749	30.1	2749	30.2	**2749**	**30.2**	4	2738	30.3	**2738**	**30.3**	2738	30.3
464.h264ref	4	**736**	**120**	736	120	736	120	4	**720**	**123**	721	123	719	123
471.omnetpp	4	736	34.0	**735**	**34.0**	735	34.0	4	692	36.1	**692**	**36.1**	692	36.1
473.astar	4	640	43.9	641	43.8	**641**	**43.8**	4	**640**	**43.9**	639	43.9	640	43.9
483.xalancbmk	4	416	66.3	416	66.4	**416**	**66.4**	4	407	67.8	**407**	**67.8**	407	67.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
The NovaScale R440 and the NovaScale R460 models are
electronically equivalent.
The results have been measured on a NovaScale R460 model.
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99

C++ benchmarks:
icl -Qvc7.1

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Peak Optimization Flags

C benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/flags.20090714.00.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/flags.20090714.00.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 11:05:41 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 12 June 2007.