SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard X7DA8

SPECint®_rate2006 = 80.2

SPECint_rate_base2006 = 77.6

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Apr-2007
Hardware Availability: May-2007
Software Availability: Apr-2007



Hardware

CPU Name:	Intel Xeon X5355
CPU Characteristics:	2.66GHz, 1333 MHz Bus
CPU MHz:	2660
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1, 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 X 2GB ECC PC2-5300, CL5, FBDIMM)
Disk Subsystem:	750GB IDE, 7200RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition W/ SP1
Compiler:	Intel C++ Compiler for IA32 version 9.1 Build no 20070322Z Microsoft Visual Studio .Net 2003 (for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	SmartHeap Library Version 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard X7DA8

SPECint_rate2006 = 80.2

SPECint_rate_base2006 = 77.6

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Apr-2007
Hardware Availability: May-2007
Software Availability: Apr-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	**547**	**143**	547	143	549	142	8	**496**	**158**	497	157	496	158
401.bzip2	8	**1187**	**65.1**	1186	65.1	1187	65.0	8	1173	65.8	1174	65.7	**1173**	**65.8**
403.gcc	8	1999	32.2	**2005**	**32.1**	2006	32.1	8	2001	32.2	**1995**	**32.3**	1991	32.3
429.mcf	8	1247	58.5	**1245**	**58.6**	1243	58.7	8	1247	58.5	**1245**	**58.6**	1243	58.7
445.gobmk	8	627	134	**628**	**134**	629	134	8	577	145	**578**	**145**	579	145
456.hmmer	8	842	88.6	844	88.4	**844**	**88.4**	8	**826**	**90.4**	826	90.4	827	90.2
458.sjeng	8	769	126	**769**	**126**	770	126	8	724	134	723	134	**724**	**134**
462.libquantum	8	**4752**	**34.9**	4751	34.9	4752	34.9	8	**4738**	**35.0**	4737	35.0	4743	35.0
464.h264ref	8	**856**	**207**	856	207	857	207	8	837	212	**836**	**212**	835	212
471.omnetpp	8	1144	43.7	**1145**	**43.7**	1146	43.6	8	**1104**	**45.3**	1104	45.3	1105	45.2
473.astar	8	883	63.6	882	63.6	**883**	**63.6**	8	839	66.9	839	67.0	**839**	**66.9**
483.xalancbmk	8	607	90.9	605	91.2	**606**	**91.1**	8	600	92.1	598	92.3	**599**	**92.2**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Tested systems can be used with SC816S-R700 case,
To ensure system stability, a 500W (minimum) ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Product description located as of http://www.supermicro.com/products/motherboard/Xeon1333/5000X/X7DA8.cfm
The system bus runs at 1333 MHz
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib                -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:
icl -Qvc7.1 -Qc99

C++ benchmarks:
icl -Qvc7.1

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32

Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000
shlw32m.lib -link /FORCE:MULTIPLE

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: Same as 400.perlbench

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 400.perlbench

Continued on next page

Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxP -O2 -Qipo
-Qprec-div- -Qunroll4 -Ob2 -Qsfalign16 -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

483.xalancbmk: Same as 471.omnetpp

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic91-ia32-flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic91-ia32-flags.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.
Report generated on Tue Jul 22 11:26:15 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 26 June 2007.