SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard X7DA8

SPECint®2006 = 16.2

SPECint_base2006 = 15.5

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Apr-2007
Hardware Availability: May-2007
Software Availability: Apr-2007



Hardware

CPU Name:	Intel Xeon X5355
CPU Characteristics:	2.66GHz, 1333 MHz Bus
CPU MHz:	2660
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1, 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 X 2GB ECC PC2-5300, CL5, FBDIMM)
Disk Subsystem:	750GB IDE, 7200RPM
Other Hardware:	None

Software

Operating System:	Windows Server 2003 Enterprise Edition W/ SP1
Compiler:	Intel C++ Compiler for IA32 version 9.1 Build no 20070322Z Microsoft Visual Studio .Net 2003 (for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	SmartHeap Library Version 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Supermicro Motherboard X7DA8

SPECint2006 = 16.2

SPECint_base2006 = 15.5

CPU2006 license: 001176
Test sponsor: Supermicro
Tested by: Supermicro

Test date: Apr-2007
Hardware Availability: May-2007
Software Availability: Apr-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	513	19.1	511	19.1	**512**	**19.1**	460	21.2	**460**	**21.2**	463	21.1
401.bzip2	700	13.8	**700**	**13.8**	700	13.8	683	14.1	**684**	**14.1**	684	14.1
403.gcc	**687**	**11.7**	687	11.7	686	11.7	666	12.1	**660**	**12.2**	659	12.2
429.mcf	537	17.0	**537**	**17.0**	537	17.0	537	17.0	**537**	**17.0**	537	17.0
445.gobmk	589	17.8	590	17.8	**589**	**17.8**	**539**	**19.5**	538	19.5	539	19.5
456.hmmer	832	11.2	827	11.3	**830**	**11.2**	**810**	**11.5**	810	11.5	810	11.5
458.sjeng	**735**	**16.5**	737	16.4	733	16.5	691	17.5	690	17.5	**691**	**17.5**
462.libquantum	**1454**	**14.2**	1473	14.1	1450	14.3	**1448**	**14.3**	1456	14.2	1446	14.3
464.h264ref	796	27.8	**793**	**27.9**	793	27.9	774	28.6	**774**	**28.6**	774	28.6
471.omnetpp	549	11.4	561	11.1	**552**	**11.3**	506	12.4	499	12.5	**506**	**12.4**
473.astar	**557**	**12.6**	555	12.6	557	12.6	**506**	**13.9**	508	13.8	505	13.9
483.xalancbmk	**349**	**19.7**	350	19.7	349	19.8	354	19.5	355	19.4	**355**	**19.5**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Tested systems can be used with SC816S-R700 case,
To ensure system stability, a 500W (minimum) ATX power supply [4-pin (+12V), 8-pin (+12V) and 24-pin are required]
Product description located as of http://www.supermicro.com/products/motherboard/Xeon1333/5000X/X7DA8.cfm
The system bus runs at 1333 MHz
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:

```
-fast /F512000000 shlw32m.lib                -link /FORCE:MULTIPLE
```

Continued on next page

Base Optimization Flags (Continued)

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlw32m.lib
                -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:
```
icl -Qvc7.1
```

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Peak Optimization Flags

C benchmarks:

400.perlbench: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

401.bzip2: Same as 400.perlbench

403.gcc: Same as 400.perlbench

429.mcf: basepeak = yes

445.gobmk: Same as 400.perlbench

456.hmmer: Same as 400.perlbench

458.sjeng: Same as 400.perlbench

Continued on next page

Peak Optimization Flags (Continued)

462.libquantum: Same as 400.perlbench

464.h264ref: Same as 400.perlbench

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxP -O2 -Qipo
-Qprec-div- -Qunroll4 -Ob2 -Qsfalign16 -Qcxx_features
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

483.xalancbmk: Same as 471.omnetpp

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic91-ia32-flags.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic91-ia32-flags.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.
Report generated on Tue Jul 22 11:20:50 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 26 June 2007.