SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (Intel Xeon E5335)

SPECint®_rate2006 = 84.1

SPECint_rate_base2006 = 77.7

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Jun-2007
Hardware Availability: Nov-2006
Software Availability: Jun-2007



Hardware

CPU Name:	Intel Xeon E5335
CPU Characteristics:	1333MHz system bus
CPU MHz:	2000
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1, 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
Disk Subsystem:	1 x 73GB 10000RPM SAS HDD
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 10 EM64T (kernel 2.6.16.21-0.8-smp)
Compiler:	Intel C++ Compiler for Linux32 version 10.0 Build 20070426 Package ID: l_cc_p_10.0.023
Auto Parallel:	No
File System:	ReiserFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	None

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (Intel Xeon E5335)

SPECint_rate2006 = 84.1

SPECint_rate_base2006 = 77.7

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Jun-2007
Hardware Availability: Nov-2006
Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	751	104	747	105	**748**	**104**	8	631	124	638	122	**634**	**123**
401.bzip2	8	1274	60.6	1284	60.1	**1280**	**60.3**	8	1215	63.5	1208	63.9	**1208**	**63.9**
403.gcc	8	867	74.3	864	74.6	**865**	**74.4**	8	867	74.3	864	74.6	**865**	**74.4**
429.mcf	8	1203	60.6	**1203**	**60.6**	1203	60.7	8	1195	61.0	1197	60.9	**1197**	**61.0**
445.gobmk	8	836	100	**836**	**100**	836	100	8	766	110	768	109	**768**	**109**
456.hmmer	8	936	79.8	935	79.9	**935**	**79.8**	8	**754**	**99.1**	755	98.8	753	99.2
458.sjeng	8	1033	93.7	**1030**	**94.0**	1028	94.1	8	920	105	**917**	**106**	916	106
462.libquantum	8	**3536**	**46.9**	3537	46.9	3535	46.9	8	**3081**	**53.8**	3078	53.9	3082	53.8
464.h264ref	8	**1108**	**160**	1106	160	1109	160	8	**1050**	**169**	1047	169	1052	168
471.omnetpp	8	891	56.1	900	55.5	**892**	**56.0**	8	855	58.5	854	58.5	**855**	**58.5**
473.astar	8	974	57.7	973	57.7	**973**	**57.7**	8	910	61.7	909	61.8	**909**	**61.8**
483.xalancbmk	8	594	92.9	593	93.1	**593**	**93.1**	8	594	92.9	593	93.1	**593**	**93.1**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
This result was measured on the Acer Altos R520
The Altos R720 and Altos R520 are electronically equivalent.

taskset was used to bind copies to cores
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
`-fast`

C++ benchmarks:
`-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs`
`-L/spec/cpu2006.1.0/lib -lsmartheap`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks (except as noted below):
`icc`

401.bzip2: `/opt/intel/cce/10.0.023/bin/icc`
`-L/opt/intel/cce/10.0.023/lib`
`-I/opt/intel/cce/10.0.023/include`

456.hmmer: `/opt/intel/cce/10.0.023/bin/icc`
`-L/opt/intel/cce/10.0.023/lib`
`-I/opt/intel/cce/10.0.023/include`

C++ benchmarks:
`icpc`

Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
401.bzip2: `-DSPEC_CPU_LP64`
456.hmmer: `-DSPEC_CPU_LP64`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

Continued on next page

Peak Optimization Flags (Continued)

400.perlbench: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -ansi-alias -prefetch`

401.bzip2: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast`

403.gcc: `basepeak = yes`

429.mcf: `-fast -prefetch`

445.gobmk: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O2 -ipo -no-prec_div -ansi-alias`

456.hmmer: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -ansi-alias`

458.sjeng: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4`

462.libquantum: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always`

464.h264ref: `Same as 456.hmmer`

C++ benchmarks:

471.omnetpp: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O3 -ipo -no-prec_div -ansi-alias -Wl,-z,muldefs -L/spec/cpu2006.1.0/lib -lsmartheap`

473.astar: `Same as 471.omnetpp`

483.xalancbmk: `basepeak = yes`

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.41.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.41.xml`

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (Intel Xeon E5335)

SPECint_rate2006 = 84.1

SPECint_rate_base2006 = 77.7

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Jun-2007
Hardware Availability: Nov-2006
Software Availability: Jun-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 12:40:48 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 August 2007.