



# SPEC<sup>®</sup> CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Acer Incorporated

## SPECfp<sup>®</sup>\_rate2006 = 54.2

## Acer Altos R720 (Intel Xeon E5335)

## SPECfp\_rate\_base2006 = 52.7

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Jun-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007



### Hardware

CPU Name: Intel Xeon E5335  
 CPU Characteristics: 1333MHz system bus  
 CPU MHz: 2000  
 FPU: Integrated  
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
 CPU(s) orderable: 1, 2 chips  
 Primary Cache: 32 KB I + 32 KB D on chip per core  
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

### Software

Operating System: SuSE Linux Enterprise Server 10 EM64T (kernel 2.6.16.21-0.8-smp)  
 Compiler: Intel C++ Compiler for Linux32 version 10.0 Build 20070426 Package ID: l\_cc\_p\_10.0.023  
 Intel Fortran Compiler for Linux32 version 10.0 Build 20070426 Package ID: l\_fc\_p\_10.0.023  
 Auto Parallel: No  
 File System: ReiserFS  
 System State: Default

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 54.2

Acer Altos R720 (Intel Xeon E5335)

SPECfp\_rate\_base2006 = 52.7

CPU2006 license: 97  
Test sponsor: Acer Incorporated  
Tested by: Acer Incorporated

Test date: Jun-2007  
Hardware Availability: Nov-2006  
Software Availability: Jun-2007

L3 Cache: None  
Other Cache: None  
Memory: 16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)  
Disk Subsystem: 1 x 73GB 10000RPM SAS HDD  
Other Hardware: None

Base Pointers: 32-bit  
Peak Pointers: 32-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3509	31.0	3507	31.0	<b>3508</b>	<b>31.0</b>	8	<b>3507</b>	<b>31.0</b>	3507	31.0	3507	31.0
416.gamess	8	1371	114	1376	114	<b>1373</b>	<b>114</b>	8	<b>1329</b>	<b>118</b>	1328	118	1331	118
433.milc	8	<b>2548</b>	<b>28.8</b>	2545	28.9	2550	28.8	8	2581	28.4	2574	28.5	<b>2578</b>	<b>28.5</b>
434.zeusmp	8	1282	56.8	1289	56.5	<b>1288</b>	<b>56.5</b>	8	<b>1284</b>	<b>56.7</b>	1287	56.6	1283	56.7
435.gromacs	8	611	93.4	610	93.7	<b>610</b>	<b>93.6</b>	8	<b>607</b>	<b>94.1</b>	609	93.8	605	94.4
436.cactusADM	8	1541	62.0	<b>1540</b>	<b>62.1</b>	1536	62.2	8	<b>1574</b>	<b>60.7</b>	1571	60.8	1585	60.3
437.leslie3d	8	<b>3211</b>	<b>23.4</b>	3217	23.4	3209	23.4	8	3148	23.9	<b>3152</b>	<b>23.9</b>	3156	23.8
444.namd	8	763	84.1	<b>767</b>	<b>83.7</b>	767	83.6	8	758	84.6	757	84.8	<b>757</b>	<b>84.7</b>
447.dealII	8	893	102	<b>883</b>	<b>104</b>	870	105	8	863	106	<b>866</b>	<b>106</b>	869	105
450.soplex	8	<b>2112</b>	<b>31.6</b>	2110	31.6	2113	31.6	8	1952	34.2	<b>1949</b>	<b>34.2</b>	1943	34.3
453.povray	8	334	127	337	126	<b>335</b>	<b>127</b>	8	<b>281</b>	<b>152</b>	280	152	284	150
454.calculix	8	<b>836</b>	<b>78.9</b>	844	78.2	834	79.1	8	835	79.1	837	78.9	<b>836</b>	<b>79.0</b>
459.GemsFDTD	8	3644	23.3	3637	23.3	<b>3643</b>	<b>23.3</b>	8	<b>3627</b>	<b>23.4</b>	3618	23.5	3635	23.3
465.tonto	8	<b>1038</b>	<b>75.8</b>	1044	75.4	1037	75.9	8	1029	76.5	<b>1032</b>	<b>76.3</b>	1032	76.3
470.lbm	8	4619	23.8	<b>4619</b>	<b>23.8</b>	4619	23.8	8	4294	25.6	<b>4294</b>	<b>25.6</b>	4296	25.6
481.wrf	8	<b>2015</b>	<b>44.3</b>	2016	44.3	2014	44.4	8	<b>2019</b>	<b>44.3</b>	2028	44.1	2016	44.3
482.sphinx3	8	3313	47.1	<b>3310</b>	<b>47.1</b>	3306	47.2	8	3096	50.4	3088	50.5	<b>3092</b>	<b>50.4</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

All programs compiled with the 64-bit compiler except 437.leslie3d, 450.soplex, 470.lbm and 482.sphinx3, at peak, compiled with the 32-bit compiler  
This result was measured on the Acer Altos R520  
The Altos R720 and Altos R520 are electronically equivalent.

taskset was used to bind copies to cores

## Base Compiler Invocation

C benchmarks:  
icc

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 54.2

Acer Altos R720 (Intel Xeon E5335)

SPECfp\_rate\_base2006 = 52.7

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Jun-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

## Base Compiler Invocation (Continued)

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64  
436.cactusADM: -DSPEC\_CPU\_LP64  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-fast -auto-ilp32

C++ benchmarks:  
-fast -auto-ilp32

Fortran benchmarks:  
-fast

Benchmarks using both Fortran and C:  
435.gromacs: -fast -auto-ilp32 -nofor\_main(\*)  
436.cactusADM: Same as 435.gromacs

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 54.2

Acer Altos R720 (Intel Xeon E5335)

SPECfp\_rate\_base2006 = 52.7

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Jun-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

## Base Optimization Flags (Continued)

454.calculix: Same as 435.gromacs

481.wrf: -fast -auto-ilp32

(\*) Indicates an optimization flag that was found in a portability variable.

## Peak Compiler Invocation

C benchmarks (except as noted below):

/opt/intel/cc/10.0.023/bin/icc -L/opt/intel/cc/10.0.023/lib  
-I/opt/intel/cc/10.0.023/include

433.milc: icc

C++ benchmarks (except as noted below):

icpc

450.soplex: /opt/intel/cc/10.0.023/bin/icpc -L/opt/intel/cc/10.0.023/lib  
-I/opt/intel/cc/10.0.023/include

Fortran benchmarks (except as noted below):

ifort

437.leslie3d: /opt/intel/fc/10.0.023/bin/ifort -L/opt/intel/fc/10.0.023/lib  
-I/opt/intel/fc/10.0.023/include

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

Same as Base Portability Flags

## Peak Optimization Flags

C benchmarks:

433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-scalar-rep- -prefetch

482.sphinx3: -fast -unroll2

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 54.2

Acer Altos R720 (Intel Xeon E5335)

SPECfp\_rate\_base2006 = 52.7

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Jun-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

## Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xT -ipo -O3  
-no-prec-div

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4  
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: Same as 434.zeusmp

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -Ob0

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -auto-ilp32  
-nofor\_main(\*)

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2  
-auto-ilp32 -nofor\_main(\*)

454.calculix: -fast -auto-ilp32 -nofor\_main(\*)

481.wrf: -fast -auto-ilp32

(\*) Indicates an optimization flag that was found in a portability variable.

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.16.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.16.xml>



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp\_rate2006 = 54.2

Acer Altos R720 (Intel Xeon E5335)

SPECfp\_rate\_base2006 = 52.7

CPU2006 license: 97

Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Jun-2007

Hardware Availability: Nov-2006

Software Availability: Jun-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.  
Report generated on Tue Jul 22 12:56:07 2014 by SPEC CPU2006 PS/PDF formatter v6932.  
Originally published on 8 August 2007.