



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Bb-6  
(Intel Xeon processor X5355)

**SPECfp®\_rate2006 = 53.9**

**SPECfp\_rate\_base2006 = 52.2**

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Jul-2007

Hardware Availability: Jan-2007

Software Availability: Apr-2007



**SPECfp\_rate\_base2006 = 52.2**

**SPECfp\_rate2006 = 53.9**

### Hardware

CPU Name: Intel Xeon X5355  
CPU Characteristics: 2.66 GHz, 2x4 MB L2 shared, 1333 MHz bus  
CPU MHz: 2666  
FPU: Integrated  
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip  
CPU(s) orderable: 1,2 chips  
Primary Cache: 32 KB I + 32 KB D on chip per core  
Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

### Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10, Kernel 2.6.16.21-0.8-smp on an x86\_64  
Compiler: Intel C++ Compiler for IA32/EM64T application, Version 9.1 - Build 20070320, Package ID: l\_cc\_c\_9.1.049  
Intel Fortran Compiler for IA32/EM64T application, Version 9.1 - Build 20070320, Package ID: l\_fc\_c\_9.1.045  
Auto Parallel: No  
File System: ext2

Continued on next page

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Bb-6  
(Intel Xeon processor X5355)

**SPECfp\_rate2006 = 53.9**

**SPECfp\_rate\_base2006 = 52.2**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Jul-2007

**Hardware Availability:** Jan-2007

**Software Availability:** Apr-2007

L3 Cache: None  
Other Cache: None  
Memory: 16 GB (4x4 GB DDR2 5300F, 2 rank, CL5-5-5, ECC)  
Disk Subsystem: 1x146.5 GB SAS, 10000RPM  
Other Hardware: None

System State: Multiuser, Runlevel 3  
Base Pointers: 64-bit  
Peak Pointers: 32/64-bit  
Other Software: None

## Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	<b>3629</b>	<b>30.0</b>	3630	30.0	3626	30.0	8	<b>3629</b>	<b>30.0</b>	3630	30.0	3626	30.0
416.gamess	8	1071	146	<b>1073</b>	<b>146</b>	1077	145	8	1071	146	<b>1073</b>	<b>146</b>	1077	145
433.milc	8	3886	18.9	3889	18.9	<b>3888</b>	<b>18.9</b>	8	<b>4009</b>	<b>18.3</b>	4008	18.3	4009	18.3
434.zeusmp	8	<b>1250</b>	<b>58.3</b>	1246	58.4	1251	58.2	8	1244	58.5	1256	57.9	<b>1249</b>	<b>58.3</b>
435.gromacs	8	449	127	<b>452</b>	<b>127</b>	453	126	8	437	131	437	131	<b>437</b>	<b>131</b>
436.cactusADM	8	1518	63.0	1521	62.9	<b>1520</b>	<b>62.9</b>	8	1518	63.0	1521	62.9	<b>1520</b>	<b>62.9</b>
437.leslie3d	8	<b>3689</b>	<b>20.4</b>	3703	20.3	3686	20.4	8	<b>3689</b>	<b>20.4</b>	3703	20.3	3686	20.4
444.namd	8	<b>574</b>	<b>112</b>	574	112	574	112	8	<b>574</b>	<b>112</b>	574	112	574	112
447.dealII	8	738	124	<b>748</b>	<b>122</b>	774	118	8	<b>767</b>	<b>119</b>	769	119	727	126
450.soplex	8	<b>2594</b>	<b>25.7</b>	2594	25.7	2593	25.7	8	2361	28.3	2363	28.2	<b>2363</b>	<b>28.2</b>
453.povray	8	293	145	<b>291</b>	<b>146</b>	291	146	8	225	189	<b>224</b>	<b>190</b>	220	193
454.calculix	8	<b>634</b>	<b>104</b>	635	104	633	104	8	620	106	<b>619</b>	<b>107</b>	614	107
459.GemsFDTD	8	4666	18.2	4662	18.2	<b>4663</b>	<b>18.2</b>	8	4666	18.2	4662	18.2	<b>4663</b>	<b>18.2</b>
465.tonto	8	1135	69.4	1097	71.7	<b>1111</b>	<b>70.9</b>	8	<b>1080</b>	<b>72.9</b>	1062	74.1	1090	72.2
470.lbm	8	5788	19.0	<b>5789</b>	<b>19.0</b>	5789	19.0	8	5453	20.2	5451	20.2	<b>5452</b>	<b>20.2</b>
481.wrf	8	2263	39.5	<b>2266</b>	<b>39.4</b>	2270	39.4	8	2263	39.5	<b>2266</b>	<b>39.4</b>	2270	39.4
482.sphinx3	8	3909	39.9	<b>3911</b>	<b>39.9</b>	3912	39.9	8	<b>3602</b>	<b>43.3</b>	3594	43.4	<b>3599</b>	<b>43.3</b>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
'/usr/bin/taskset' used to bind processes to CPUs

## General Notes

The system bus runs at 1333 MHz  
All binaries were built with 64-bit Intel compiler except:  
433.milc, 434.zeusmp, 450.soplex, 470.lbm and 482.sphinx3 in peak were built with  
32-bit Intel compiler by changing the path for include and library files.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Bb-6  
(Intel Xeon processor X5355)

**SPECfp\_rate2006 = 53.9**

**SPECfp\_rate\_base2006 = 52.2**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Jul-2007

**Hardware Availability:** Jan-2007

**Software Availability:** Apr-2007

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:  
-fast

C++ benchmarks:  
-fast

Fortran benchmarks:  
-fast

Benchmarks using both Fortran and C:  
-fast



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Bb-6  
(Intel Xeon processor X5355)

**SPECfp\_rate2006 = 53.9**

**SPECfp\_rate\_base2006 = 52.2**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Jul-2007

**Hardware Availability:** Jan-2007

**Software Availability:** Apr-2007

## Peak Compiler Invocation

C benchmarks:

```
/opt/intel/cc/9.1.049/bin/icc -I/opt/intel/cc/9.1.049/include  
-L/opt/intel/cc/9.1.049/lib
```

C++ benchmarks (except as noted below):

```
icpc
```

```
450.soplex: /opt/intel/cc/9.1.049/bin/icpc  
-I/opt/intel/cc/9.1.049/include -L/opt/intel/cc/9.1.049/lib
```

Fortran benchmarks (except as noted below):

```
ifort
```

```
434.zeusmp: /opt/intel/fc/9.1.045/bin/ifort  
-I/opt/intel/fc/9.1.045/include -L/opt/intel/fc/9.1.045/lib
```

Benchmarks using both Fortran and C:

```
icc ifort
```

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64  
416.gamess: -DSPEC_CPU_LP64  
435.gromacs: -DSPEC_CPU_LP64 -nofor_main  
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main  
437.leslie3d: -DSPEC_CPU_LP64  
444.namd: -DSPEC_CPU_LP64  
447.dealII: -DSPEC_CPU_LP64  
453.povray: -DSPEC_CPU_LP64  
454.calculix: -DSPEC_CPU_LP64 -nofor_main  
459.GemsFDTD: -DSPEC_CPU_LP64  
465.tonto: -DSPEC_CPU_LP64  
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof_gen(pass 1) -prof_use(pass 2) -fast
```

```
470.lbm: Same as 433.milc
```

```
482.sphinx3: -fast
```

C++ benchmarks:

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## NEC Corporation

Express5800/120Bb-6  
(Intel Xeon processor X5355)

**SPECfp\_rate2006 = 53.9**

**SPECfp\_rate\_base2006 = 52.2**

**CPU2006 license:** 9006

**Test sponsor:** NEC Corporation

**Tested by:** NEC Corporation

**Test date:** Jul-2007

**Hardware Availability:** Jan-2007

**Software Availability:** Apr-2007

## Peak Optimization Flags (Continued)

444.namd: basepeak = yes

447.dealII: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

450.soplex: Same as 447.dealII

453.povray: Same as 447.dealII

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: basepeak = yes

434.zeusmp: -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

Benchmarks using both Fortran and C:

435.gromacs: -prof\_gen(pass 1) -prof\_use(pass 2) -fast

436.cactusADM: basepeak = yes

454.calculix: Same as 435.gromacs

481.wrf: basepeak = yes

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/NEC-ic91-linux-flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/NEC-ic91-linux-flags.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 12:50:57 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 8 August 2007.