



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5335,2.00GHz)

SPECfp®2006 = 13.9

SPECfp_base2006 = 13.5

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2007

Hardware Availability: Feb-2007

Software Availability: Dec-2006



Hardware

CPU Name: Intel Xeon E5335
 CPU Characteristics: 2.00 GHz, 8 MB L2, 1333 MHz system bus
 CPU MHz: 2000
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1 to 2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 8 MB I+D on chip per chip, 4 MB shared / 2 cores

Continued on next page

Software

Operating System: Windows Server 2003 Enterprise Edition X64 Edition Service Pack 1
 Compiler: Intel C++ Compiler for EM64T version 9.1
 Package ID W_CC_C_9.1.033 Build no 20061104
 Intel Fortran Compiler for EM64T version 9.1
 Package ID W_FC_C_9.1.033 Build no 20061104
 Microsoft Visual Studio 2005 (lib & linker)
 Auto Parallel: Yes
 File System: NTFS
 System State: Default

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5335,2.00GHz)

SPECfp2006 = 13.9

SPECfp_base2006 = 13.5

CPU2006 license: 20

Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Sep-2007

Hardware Availability: Feb-2007

Software Availability: Dec-2006

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2 GB) FB-DIMM PC2-5300F ECC CL5
Disk Subsystem: 1x73 GB SAS, 15000 RPM
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 64-bit
Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	<u>424</u>	<u>32.0</u>	425	32.0	424	32.1	425	32.0	<u>425</u>	<u>32.0</u>	423	32.1
416.gamess	<u>1486</u>	<u>13.2</u>	1486	13.2	1485	13.2	1459	13.4	1459	13.4	<u>1459</u>	<u>13.4</u>
433.milc	961	9.56	<u>962</u>	<u>9.54</u>	963	9.53	964	9.53	<u>962</u>	<u>9.54</u>	960	9.56
434.zeusmp	800	11.4	801	11.4	<u>800</u>	<u>11.4</u>	800	11.4	801	11.4	<u>800</u>	<u>11.4</u>
435.gromacs	<u>575</u>	<u>12.4</u>	575	12.4	575	12.4	<u>563</u>	<u>12.7</u>	563	12.7	563	12.7
436.cactusADM	239	50.0	238	50.3	<u>238</u>	<u>50.3</u>	239	50.0	238	50.3	<u>238</u>	<u>50.3</u>
437.leslie3d	<u>699</u>	<u>13.4</u>	701	13.4	693	13.6	<u>699</u>	<u>13.4</u>	701	13.4	693	13.6
444.namd	<u>771</u>	<u>10.4</u>	771	10.4	771	10.4	<u>771</u>	<u>10.4</u>	771	10.4	771	10.4
447.dealII	1055	10.8	1054	10.9	<u>1054</u>	<u>10.8</u>	<u>1007</u>	<u>11.4</u>	1007	11.4	1007	11.4
450.soplex	767	10.9	<u>767</u>	<u>10.9</u>	767	10.9	755	11.1	<u>755</u>	<u>11.1</u>	754	11.1
453.povray	395	13.5	395	13.5	<u>395</u>	<u>13.5</u>	<u>301</u>	<u>17.7</u>	301	17.7	301	17.7
454.calculix	<u>839</u>	<u>9.84</u>	839	9.83	838	9.84	800	10.3	<u>800</u>	<u>10.3</u>	800	10.3
459.GemsFDTD	<u>679</u>	<u>15.6</u>	679	15.6	679	15.6	<u>679</u>	<u>15.6</u>	679	15.6	679	15.6
465.tonto	<u>925</u>	<u>10.6</u>	926	10.6	923	10.7	833	11.8	833	11.8	<u>833</u>	<u>11.8</u>
470.lbm	1971	6.97	<u>1967</u>	<u>6.98</u>	1967	6.99	<u>1974</u>	<u>6.96</u>	1974	6.96	1974	6.96
481.wrf	<u>792</u>	<u>14.1</u>	796	14.0	792	14.1	<u>792</u>	<u>14.1</u>	796	14.0	792	14.1
482.sphinx3	<u>1257</u>	<u>15.5</u>	1257	15.5	1256	15.5	1214	16.1	1215	16.0	<u>1214</u>	<u>16.1</u>

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

The NovaScale R440 and the NovaScale R460 models are electronically equivalent.
The results have been measured on a NovaScale R460 model.

Base Compiler Invocation

C benchmarks:
icl -Qvc8 -Qc99

C++ benchmarks:
icl -Qvc8

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5335,2.00GHz)

SPECfp2006 = 13.9

SPECfp_base2006 = 13.5

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Sep-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc8 -Qc99 ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_P64
416.gamess: -DSPEC_CPU_P64
433.milc: -D_Complex= -DSPEC_CPU_P64
434.zeusmp: -DSPEC_CPU_P64
435.gromacs: -D_Complex= -DSPEC_CPU_P64
436.cactusADM: -D_Complex= -DSPEC_CPU_P64 -Qlowercase /assume:underscore
437.leslie3d: -DSPEC_CPU_P64
444.namd: -DSPEC_CPU_P64 /TP
447.dealII: -D_Complex= -DSPEC_CPU_P64 -DBOOST_NO_INTRINSIC_WCHAR_T
-DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
450.soplex: -DSPEC_CPU_P64
453.povray: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
454.calculix: -D_Complex= -DSPEC_CPU_P64 -DSPEC_CPU_NOZMODIFIER
-Qlowercase
459.GemsFDTD: -DSPEC_CPU_P64
465.tonto: -DSPEC_CPU_P64
470.lbm: -D_Complex= -DSPEC_CPU_P64
481.wrf: -DSPEC_CPU_P64 -DSPEC_CPU_WINDOWS_ICL
482.sphinx3: -D_Complex= -DSPEC_CPU_P64

Base Optimization Flags

C benchmarks:
-fast -Qparallel

C++ benchmarks:
-fast -Qparallel -Qcxx-features

Fortran benchmarks:
-fast -Qparallel

Benchmarks using both Fortran and C:
-fast -Qparallel



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5335,2.00GHz)

SPECfp2006 = 13.9

SPECfp_base2006 = 13.5

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Sep-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

Base Other Flags

C benchmarks:
-F950000000

C++ benchmarks:
-F950000000

Fortran benchmarks:
-F950000000

Benchmarks using both Fortran and C:
-F950000000

Peak Compiler Invocation

C benchmarks:
icl -Qvc8 -Qc99

C++ benchmarks:
icl -Qvc8

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc8 -Qc99 ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast

C++ benchmarks:

444.namd: basepeak = yes

447.dealII: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx-features

450.soplex: Same as 447.dealII

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5335,2.00GHz)

SPECfp2006 = 13.9

SPECfp_base2006 = 13.5

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Sep-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

Peak Optimization Flags (Continued)

453.povray: Same as 447.dealII

Fortran benchmarks:

410.bwaves: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qparallel

416.gamess: -fast

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: Same as 410.bwaves

Benchmarks using both Fortran and C:

435.gromacs: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast

436.cactusADM: basepeak = yes

454.calculix: Same as 435.gromacs

481.wrf: basepeak = yes

Peak Other Flags

C benchmarks:
-F950000000

C++ benchmarks:
-F950000000

Fortran benchmarks:
-F950000000

Benchmarks using both Fortran and C:
-F950000000

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/flags.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/flags.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R460
(Intel Xeon processor E5335,2.00GHz)

SPECfp2006 = 13.9

SPECfp_base2006 = 13.5

CPU2006 license: 20
Test sponsor: Bull SAS
Tested by: Bull SAS

Test date: Sep-2007
Hardware Availability: Feb-2007
Software Availability: Dec-2006

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 13:55:57 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 October 2007.