



SPEC[®] CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp[®]_rate2006 = 35.4

PowerEdge 2970 (AMD Opteron 2210, 1.80 GHz)

SPECfp_rate_base2006 = 34.8

CPU2006 license: 55


Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Apr-2007

Tested by: Dell Inc.

Software Availability: Oct-2007



SPECfp_rate_base2006 = 34.8

SPECfp_rate2006 = 35.4

Hardware

CPU Name: AMD Opteron 2210
 CPU Characteristics:
 CPU MHz: 1800
 FPU: Integrated
 CPU(s) enabled: 4 cores, 2 chips, 2 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 64 KB I + 64 KB D on chip per core
 Secondary Cache: 1 MB I+D on chip per core

Continued on next page

Software

Operating System: 64-Bit SUSE LINUX Enterprise Server 10 SP1
 Compiler: The Portland Group (PGI)
 PGI pgf90 7.1-0 Fortran Compiler
 PGI pgcc 7.1-0 C Compiler
 PGI pgCC 7.1-0 C++ Compiler
 Auto Parallel: No
 File System: ReiserFS
 System State: Multi-user, run level 3

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.4

PowerEdge 2970 (AMD Opteron 2210, 1.80 GHz)

SPECfp_rate_base2006 = 34.8

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Apr-2007

Tested by: Dell Inc.

Software Availability: Oct-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8x2GB, DDR2-667 CL5 ECC Dual Rank)
Disk Subsystem: 1 x 73 GB SAS 10k RPM
Other Hardware: None

Base Pointers: 32/64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base								Peak							
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio		
410.bwaves	4	1136	47.8	<u>1138</u>	<u>47.8</u>	1141	47.7	4	1102	49.3	<u>1104</u>	<u>49.2</u>	1106	49.1		
416.gamess	4	2041	38.4	<u>2040</u>	<u>38.4</u>	2039	38.4	4	<u>2013</u>	<u>38.9</u>	2015	38.9	2013	38.9		
433.milc	4	1180	31.1	1171	31.3	<u>1172</u>	<u>31.3</u>	4	1136	32.3	<u>1136</u>	<u>32.3</u>	1138	32.3		
434.zeusmp	4	1045	34.8	1051	34.6	<u>1050</u>	<u>34.7</u>	4	1045	34.8	1051	34.6	<u>1050</u>	<u>34.7</u>		
435.gromacs	4	907	31.5	<u>907</u>	<u>31.5</u>	908	31.5	4	749	38.1	<u>749</u>	<u>38.1</u>	749	38.1		
436.cactusADM	4	<u>1614</u>	<u>29.6</u>	1608	29.7	1623	29.5	4	<u>1614</u>	<u>29.6</u>	1608	29.7	1623	29.5		
437.leslie3d	4	1359	27.7	1356	27.7	<u>1357</u>	<u>27.7</u>	4	1359	27.7	1356	27.7	<u>1357</u>	<u>27.7</u>		
444.namd	4	931	34.4	930	34.5	<u>931</u>	<u>34.5</u>	4	923	34.8	919	34.9	<u>922</u>	<u>34.8</u>		
447.dealII	4	1206	37.9	1199	38.2	<u>1206</u>	<u>37.9</u>	4	1206	37.9	1199	38.2	<u>1206</u>	<u>37.9</u>		
450.soplex	4	1134	29.4	<u>1129</u>	<u>29.5</u>	1129	29.6	4	1134	29.4	<u>1129</u>	<u>29.5</u>	1129	29.6		
453.povray	4	507	41.9	506	42.0	<u>507</u>	<u>42.0</u>	4	506	42.0	<u>507</u>	<u>42.0</u>	508	41.9		
454.calculix	4	919	35.9	918	35.9	<u>918</u>	<u>35.9</u>	4	919	35.9	918	35.9	<u>918</u>	<u>35.9</u>		
459.GemsFDTD	4	1473	28.8	1465	29.0	<u>1470</u>	<u>28.9</u>	4	1473	28.8	1465	29.0	<u>1470</u>	<u>28.9</u>		
465.tonto	4	1075	36.6	1075	36.6	<u>1075</u>	<u>36.6</u>	4	1055	37.3	<u>1050</u>	<u>37.5</u>	1050	37.5		
470.lbm	4	1735	31.7	<u>1721</u>	<u>31.9</u>	1690	32.5	4	1703	32.3	1715	32.0	<u>1708</u>	<u>32.2</u>		
481.wrf	4	1143	39.1	<u>1143</u>	<u>39.1</u>	1149	38.9	4	<u>1115</u>	<u>40.1</u>	1115	40.1	1115	40.1		
482.sphinx3	4	1958	39.8	<u>1958</u>	<u>39.8</u>	1955	39.9	4	1958	39.8	<u>1958</u>	<u>39.8</u>	1955	39.9		

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

'ulimit -s unlimited' was used to set environment stack size
'ulimit -l 2457600' was used to set environment locked pages in memory quantity
'numactl' was used to bind one copy per core, and memory to a local NUMA node
Set vm/nr_hugepages=1200 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages
Environment variable PGI_HUGE_PAGES set to 150

Base Compiler Invocation

C benchmarks:
pgcc

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.4

PowerEdge 2970 (AMD Opteron 2210, 1.80 GHz)

SPECfp_rate_base2006 = 34.8

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Apr-2007

Tested by: Dell Inc.

Software Availability: Oct-2007

Base Compiler Invocation (Continued)

C++ benchmarks:

pgcpp

Fortran benchmarks:

pgf95

Benchmarks using both Fortran and C:

pgcc pgf95

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -Mnomain
436.cactusADM: -DSPEC_CPU_LP64 -Mnomain
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -Mnomain
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:

-fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc=huge:8
-tp k8-64 -Bstatic_pgi

C++ benchmarks:

-fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc=huge:8
--zc_eh -tp k8-64 -Bstatic_pgi

Fortran benchmarks:

-fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc=huge:8
-tp k8-64 -Bstatic_pgi

Benchmarks using both Fortran and C:

-fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc=huge:8
-tp k8-64 -Bstatic_pgi



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.4

PowerEdge 2970 (AMD Opteron 2210, 1.80 GHz)

SPECfp_rate_base2006 = 34.8

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Apr-2007

Tested by: Dell Inc.

Software Availability: Oct-2007

Base Other Flags

C benchmarks:

-w

C++ benchmarks:

-w

Fortran benchmarks:

-w

Benchmarks using both Fortran and C:

-w

Peak Compiler Invocation

C benchmarks:

pgcc

C++ benchmarks:

pgcpp

Fortran benchmarks:

pgf95

Benchmarks using both Fortran and C:

pgcc pgf95

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -Mphi(pass 1) -Mipa=fast(pass 2) -Mipa=inline(pass 2)
-Mipa=noarg(pass 2) -Mpfo(pass 2) -fast -O4 -Mdse
-Mfprelaxed -Msmartalloc=huge:8 -tp k8-64 -Bstatic_pgi

470.lbm: -fast -Mfprelaxed -Msmartalloc=huge:8 -Mipa=fast
-Mipa=noarg -tp k8-64 -Bstatic_pgi

482.sphinx3: basepeak = yes

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.4

PowerEdge 2970 (AMD Opteron 2210, 1.80 GHz)

SPECfp_rate_base2006 = 34.8

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Apr-2007

Tested by: Dell Inc.

Software Availability: Oct-2007

Peak Optimization Flags (Continued)

C++ benchmarks:

444.namd: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=fast(pass 2)
-Mipa=inline(pass 2) -fast -O4 -Mfprelaxed
-Msmartalloc=huge:32 --zc_eh -tp k8-64 -Bstatic_pgi

447.dealIII: basepeak = yes

450.soplex: basepeak = yes

453.povray: -fast -Mfprelaxed -Msmartalloc=huge:32 -Mipa=fast
-Mipa=inline --zc_eh -tp k8-64 -Bstatic_pgi

Fortran benchmarks:

410.bwaves: -fast -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc
-tp k8-64 -Bstatic_pgi

416.gamess: -fast -Mipa=fast -Mipa=inline -Mfprelaxed -Mvect=noaltcode
-Msmartalloc=huge:64 -tp k8-64 -Bstatic_pgi

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: basepeak = yes

465.tonto: -fast -Mfprelaxed -Msmartalloc=huge:128 -Mipa=fast
-Mipa=inline -Mvect=noaltcode -tp k8-64 -Bstatic_pgi

Benchmarks using both Fortran and C:

435.gromacs: -fast -O4 -Mipa=fast -Mipa=inline -Mfprelaxed
-Msmartalloc=huge:16 -tp k8-64 -Mfpapprox=rsqrt
-Bstatic_pgi

436.cactusADM: basepeak = yes

454.calculix: basepeak = yes

481.wrf: -fast -Mfprelaxed -Msmartalloc=huge:32 -Mvect=noaltcode
-tp k8-64 -Bstatic_pgi

Peak Other Flags

C benchmarks:

-w

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECfp_rate2006 = 35.4

PowerEdge 2970 (AMD Opteron 2210, 1.80 GHz)

SPECfp_rate_base2006 = 34.8

CPU2006 license: 55

Test date: Sep-2007

Test sponsor: Dell Inc.

Hardware Availability: Apr-2007

Tested by: Dell Inc.

Software Availability: Oct-2007

Peak Other Flags (Continued)

C++ benchmarks:

-w

Fortran benchmarks:

-w

Benchmarks using both Fortran and C:

-w

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/pgi710_flags.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/pgi710_flags.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:17:14 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 30 October 2007.