SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 6800 (Intel Xeon 7130M, 3.20 GHz)

SPECint®_rate2006 = 75.4

SPECint_rate_base2006 = 67.0

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Sep-2007
Hardware Availability: Aug-2006
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Xeon 7130M
CPU Characteristics:	800 MHz system bus
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chip
CPU(s) orderable:	1,2,4 chips
Primary Cache:	12 K micro-ops I + 16 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip
Other Cache:	None
Memory:	16 GB (16 x 1 GB ECC 400 MHz DDR2 SDRAM)
Disk Subsystem:	2 x 36 GB SCSI 15k RPM
Other Hardware:	None

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 10 SP1
Compiler:	Intel C++ Compiler for Linux32 and Linux64 version 10.1 Build 20070725
Auto Parallel:	Yes
File System:	ReiserFS
System State:	Multi-user, run level 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap library V8.1

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 6800 (Intel Xeon 7130M, 3.20 GHz)

SPECint_rate2006 = 75.4

SPECint_rate_base2006 = 67.0

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Sep-2007
Hardware Availability: Aug-2006
Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	904	86.5	**902**	**86.6**	900	86.8	8	**804**	**97.2**	804	97.2	801	97.6
401.bzip2	8	**1171**	**65.9**	1166	66.2	1178	65.5	8	**1089**	**70.9**	1091	70.8	1088	70.9
403.gcc	8	**964**	**66.8**	962	66.9	965	66.8	8	956	67.4	966	66.7	**964**	**66.8**
429.mcf	8	**1127**	**64.7**	1129	64.6	1127	64.7	8	**1134**	**64.4**	1135	64.3	1133	64.4
445.gobmk	8	1215	69.1	**1215**	**69.1**	1215	69.1	8	**1132**	**74.1**	1135	74.0	1132	74.2
456.hmmer	8	1167	63.9	1173	63.6	**1167**	**63.9**	8	1036	72.1	**1036**	**72.0**	1039	71.8
458.sjeng	8	1651	58.6	**1650**	**58.7**	1649	58.7	8	1424	68.0	**1424**	**68.0**	1425	67.9
462.libquantum	8	3663	45.3	3663	45.3	**3663**	**45.3**	1	208	99.8	188	110	**207**	**99.9**
464.h264ref	8	**1232**	**144**	1232	144	1232	144	8	**1154**	**153**	1153	154	1157	153
471.omnetpp	8	1261	39.7	1255	39.8	**1256**	**39.8**	8	**1226**	**40.8**	1226	40.8	1228	40.7
473.astar	8	1000	56.2	**1001**	**56.1**	1002	56.0	8	980	57.3	**983**	**57.1**	984	57.1
483.xalancbmk	8	625	88.3	625	88.3	**625**	**88.3**	8	625	88.3	625	88.3	**625**	**88.3**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
OMP_NUM_THREADS set to number of cores
KMP_STACK_SIZE set to 64M
KMP_AFFINITY set to physical,0
```

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
```

Platform Notes

```
BIOS Settings:
Logical Processor = Disabled (default Enabled)
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:
`-xP -ipo -O3 -no-prec-div -static -inline-calloc -opt-malloc-options=3`

C++ benchmarks:
`-xP -ipo -O3 -no-prec-div -Wl,-z,muldefs -L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks (except as noted below):
`icc`

401.bzip2: `/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include`

456.hmmer: `/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include`

C++ benchmarks:
`icpc`

Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
401.bzip2: `-DSPEC_CPU_LP64`
456.hmmer: `-DSPEC_CPU_LP64`

Continued on next page

Peak Portability Flags (Continued)

462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3
-no-prec-div -static -ansi-alias -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3
-no-prec-div -static -prefetch

403.gcc: -xP -ipo -O3 -no-prec-div -static -inline-calloc
-opt-malloc-options=3

429.mcf: -xP -ipo -O3 -no-prec-div -static -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xP -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -xP -ipo -O3 -no-prec-div -static -unroll2 -ansi-alias
-opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3
-no-prec-div -static -unroll4

462.libquantum: -xP -ipo -O3 -no-prec-div -static -unroll4 -Ob0
-prefetch -opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3
-no-prec-div -static -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xP -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xP -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.30.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.30.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:08:59 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 1 November 2007.