SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 6800 (Intel Xeon 7130M, 3.20 GHz)

SPECfp®_rate2006 = 53.7

SPECfp_rate_base2006 = 51.2

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Sep-2007
Hardware Availability: Aug-2006
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Xeon 7130M
CPU Characteristics:	800 MHz system bus
CPU MHz:	3200
FPU:	Integrated
CPU(s) enabled:	8 cores, 4 chips, 2 cores/chip
CPU(s) orderable:	1,2,4 chips
Primary Cache:	12 K micro-ops I + 16 KB D on chip per core
Secondary Cache:	1 MB I+D on chip per core

Continued on next page

Software

Operating System:	64-Bit SUSE LINUX Enterprise Server 10 SP1
Compiler:	Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070725
Auto Parallel:	No
File System:	ReiserFS
System State:	Multi-user, run level 3
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 6800 (Intel Xeon 7130M, 3.20 GHz)

SPECfp_rate2006 = 53.7

SPECfp_rate_base2006 = 51.2

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Sep-2007
Hardware Availability: Aug-2006
Software Availability: Nov-2007

L3 Cache: 8 MB I+D on chip per chip
Other Cache: None
Memory: 16 GB (16 x 1 GB ECC 400 MHz DDR2 SDRAM)
Disk Subsystem: 2 x 36 GB SCSI 15k RPM
Other Hardware: None

Other Software: SmartHeap library V8.1

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	**3223**	**33.7**	3234	33.6	3221	33.8	8	3229	33.7	**3227**	**33.7**	3227	33.7
416.gamess	8	1912	81.9	**1907**	**82.2**	1906	82.2	8	1934	81.0	**1930**	**81.1**	1927	81.3
433.milc	8	**3432**	**21.4**	3433	21.4	3432	21.4	8	3539	20.8	**3538**	**20.8**	3538	20.8
434.zeusmp	8	1301	56.0	**1309**	**55.6**	1312	55.5	8	1308	55.7	**1304**	**55.8**	1303	55.9
435.gromacs	8	760	75.1	**765**	**74.7**	767	74.5	8	**764**	**74.7**	758	75.4	765	74.7
436.cactusADM	8	**1259**	**75.9**	1259	75.9	1255	76.2	8	**1274**	**75.0**	1276	75.0	1253	76.3
437.leslie3d	8	2935	25.6	**2934**	**25.6**	2933	25.6	8	2892	26.0	2906	25.9	**2898**	**26.0**
444.namd	8	**873**	**73.5**	873	73.5	874	73.4	8	**866**	**74.1**	866	74.1	866	74.1
447.dealII	8	854	107	845	108	**852**	**107**	8	792	116	**799**	**115**	806	114
450.soplex	8	**2059**	**32.4**	2059	32.4	2062	32.4	8	**1840**	**36.3**	1840	36.3	1835	36.4
453.povray	8	**451**	**94.5**	452	94.1	451	94.5	8	**402**	**106**	402	106	402	106
454.calculix	8	**968**	**68.2**	967	68.2	969	68.1	8	696	94.9	**696**	**94.8**	698	94.6
459.GemsFDTD	8	3676	23.1	**3672**	**23.1**	3672	23.1	8	3677	23.1	3667	23.1	**3669**	**23.1**
465.tonto	8	**965**	**81.6**	966	81.5	964	81.7	8	894	88.1	**895**	**87.9**	896	87.9
470.lbm	8	4462	24.6	**4458**	**24.7**	4457	24.7	8	4393	25.0	4397	25.0	**4394**	**25.0**
481.wrf	8	**1811**	**49.3**	1809	49.4	1814	49.3	8	1810	49.4	1804	49.5	**1806**	**49.5**
482.sphinx3	8	2465	63.2	2469	63.1	**2466**	**63.2**	8	**2183**	**71.4**	2173	71.7	2203	70.8

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
```

Platform Notes

```
BIOS Settings:
Logical Processor = Disabled (default Enabled)
```

Base Compiler Invocation

C benchmarks:

```
icc
```

Continued on next page

Base Compiler Invocation (Continued)

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-xP -ipo -O3 -no-prec-div -static

C++ benchmarks:
-xP -ipo -O3 -no-prec-div -static

Fortran benchmarks:
-xP -ipo -O3 -no-prec-div -static

Benchmarks using both Fortran and C:
-xP -ipo -O3 -no-prec-div -static

Peak Compiler Invocation

C benchmarks (except as noted below):
```
/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include
```

433.milc: `icc`

C++ benchmarks (except as noted below):
```
icpc
```

450.soplex: `/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/icpc -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include`

Fortran benchmarks (except as noted below):
```
ifort
```

437.leslie3d: `/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/bin/ifort -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux32/include`

Benchmarks using both Fortran and C:
```
icc ifort
```

Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

433.milc: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xP -ipo -O3 -no-prec-div -static -fno-alias -auto-ilp32`

Continued on next page

Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -unroll2 -scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -xP -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -unroll2 -ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xP -ipo -O3 -no-prec-div -static -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -prefetch -opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -unroll2 -Ob0 -prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xP -ipo -O3 -no-prec-div -static -unroll2 -prefetch -auto-ilp32

454.calculix: -xP -ipo -O3 -no-prec-div -static -unroll-aggressive -auto-ilp32

Continued on next page

Peak Optimization Flags (Continued)

481.wrf: `-xP -ipo -O3 -no-prec-div -static -auto-ilp32`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.25.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.25.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:07:59 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 1 November 2007.