SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 2900 (Intel Xeon E5320, 1.86 GHz)

SPECint®_rate2006 = 69.8

SPECint_rate_base2006 = 64.2

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Aug-2007
Hardware Availability: Dec-2006
Software Availability: Jun-2007



Hardware

CPU Name:	Intel Xeon E5320
CPU Characteristics:	1066 MHz Bus Speed
CPU MHz:	1866
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	8 GB (8 x 1 GB 667MHz CL5 DDR2 FB-DIMM SDRAM)
Disk Subsystem:	2 x 146 GB SAS, 15000RPM
Other Hardware:	1 x Gigabit Ethernet card Dual Port Integrated

Software

Operating System:	Microsoft Windows Server 2003 Enterprise x64 Edition
Compiler:	Intel C++ Compiler for IA32 version 10.0 Build 20070426 Package ID: W_CC_P_10.0.025 Microsoft Visual Studio .Net 2003 (for libraries)
Auto Parallel:	No
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	MicroQuill SmartHeap Library Version 8.0

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge 2900 (Intel Xeon E5320, 1.86 GHz)

SPECint_rate2006 = 69.8

SPECint_rate_base2006 = 64.2

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Aug-2007
Hardware Availability: Dec-2006
Software Availability: Jun-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	784	99.7	**794**	**98.4**	799	97.8	8	701	112	**702**	**111**	704	111
401.bzip2	8	1431	53.9	1424	54.2	**1429**	**54.0**	8	**1393**	**55.4**	1394	55.4	1384	55.8
403.gcc	8	**2281**	**28.2**	2281	28.2	2276	28.3	8	1650	39.0	1647	39.1	**1647**	**39.1**
429.mcf	8	1346	54.2	**1348**	**54.1**	1349	54.1	8	1346	54.2	**1348**	**54.1**	1349	54.1
445.gobmk	8	**900**	**93.3**	903	92.9	899	93.4	8	**821**	**102**	820	102	822	102
456.hmmer	8	**995**	**75.0**	995	75.0	995	75.0	8	**982**	**76.0**	982	76.0	982	76.0
458.sjeng	8	1110	87.2	1110	87.2	**1110**	**87.2**	8	992	97.6	992	97.6	**992**	**97.6**
462.libquantum	8	4417	37.5	**4417**	**37.5**	4417	37.5	8	3742	44.3	**3742**	**44.3**	3743	44.3
464.h264ref	8	1193	148	1193	148	**1193**	**148**	8	1126	157	1127	157	**1126**	**157**
471.omnetpp	8	1108	45.1	**1107**	**45.1**	1107	45.2	8	1064	47.0	1060	47.2	**1064**	**47.0**
473.astar	8	**1096**	**51.3**	1096	51.3	1095	51.3	8	1039	54.0	**1039**	**54.0**	1039	54.1
483.xalancbmk	8	717	77.0	**717**	**77.0**	717	77.0	8	728	75.8	729	75.7	**729**	**75.8**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
"start /b /wait /affinity" used to bind processes to cores
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:

```
icl -Qvc7.1
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Base Optimization Flags

C benchmarks:
```
-fast /F512000000 shlw32m.lib            -link /FORCE:MULTIPLE
```

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlw32m.lib
            -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc7.1 -Qc99
```

C++ benchmarks:
```
icl -Qvc7.1
```

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Peak Optimization Flags

C benchmarks:

400.perlbench: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast -Qansi-alias -Qprefetch /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

401.bzip2: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

403.gcc: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast /F512000000 -link /FORCE:MULTIPLE`

429.mcf: `basepeak = yes`

Continued on next page

Peak Optimization Flags (Continued)

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qipo -Qprec_div- -Qansi-alias /F512000000 -link /FORCE:MULTIPLE

456.hmmer: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2 -Qansi-alias /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4 /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

462.libquantum: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4 -Ob0 -Qprefetch -Qopt-streaming-stores:always /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

464.h264ref: Same as 456.hmmer

C++ benchmarks:
-Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias -Qcxx_features /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Dell-Intel-ic10-ia32.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Dell-Intel-ic10-ia32.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:37:20 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 13 November 2007.