



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp®_rate2006 = 104

Acer Altos R920 (Intel Xeon E7330)

SPECfp_rate_base2006 = 97.7

CPU2006 license: 97


Test sponsor: Acer Incorporated

Tested by: Acer Incorporated

Test date: Nov-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007



SPECfp_rate_base2006 = 97.7

SPECfp_rate2006 = 104

Hardware

CPU Name: Intel Xeon E7330
 CPU Characteristics: 1066MHz system bus
 CPU MHz: 2400
 FPU: Integrated
 CPU(s) enabled: 16 cores, 4 chips, 4 cores/chip
 CPU(s) orderable: 1, 2, 4 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 6 MB I+D on chip per chip, 3 MB shared / 2 cores

Software

Operating System: SuSE Linux Enterprise Server 10 SP1 EM64T (kernel 2.6.16.46-0.12-smp)
 Compiler: Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070725
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Multi-user, level 3
 Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 104

Acer Altos R920 (Intel Xeon E7330)

SPECfp_rate_base2006 = 97.7

CPU2006 license: 97

Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2007

Tested by: Acer Incorporated

Software Availability: Nov-2007

L3 Cache: None
 Other Cache: None
 Memory: 16 GB (16 x 1048MB ECC FB-DIMM DDR2-667 CL5-5-5)
 Disk Subsystem: 1 x 73GB 10000PRM SAS HDD
 Other Hardware: None

Peak Pointers: 32/64-bit
 Other Software: MicroQuill SmartHeap Library 8.1

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	16	4052	53.7	4043	53.8	4043	53.8	16	3962	54.9	3963	54.9	3962	54.9
416.gamess	16	1168	268	1165	269	1164	269	16	1146	273	1144	274	1148	273
433.milc	16	3120	47.1	3119	47.1	3119	47.1	16	3117	47.1	3120	47.1	3116	47.1
434.zeusmp	16	1357	107	1365	107	1357	107	16	1354	108	1354	107	1352	108
435.gromacs	16	517	221	514	222	519	220	16	511	224	510	224	510	224
436.cactusADM	16	1630	117	1630	117	1635	117	1	80.8	148	80.6	148	80.2	149
437.leslie3d	16	3844	39.1	3847	39.1	3846	39.1	16	3711	40.5	3708	40.6	3711	40.5
444.namd	16	647	198	641	200	641	200	16	646	199	637	202	637	201
447.dealII	16	972	188	1009	181	960	191	16	937	195	929	197	928	197
450.soplex	16	2710	49.2	2706	49.3	2704	49.3	16	2444	54.6	2445	54.6	2443	54.6
453.povray	16	284	299	278	306	277	307	16	235	362	236	361	235	362
454.calculix	16	753	175	766	172	764	173	16	570	232	564	234	570	232
459.GemsFDTD	16	4305	39.4	4300	39.5	4302	39.5	16	4285	39.6	4287	39.6	4287	39.6
465.tonto	16	1265	124	1267	124	1265	124	16	1242	127	1249	126	1245	126
470.lbm	16	6691	32.9	6691	32.9	6691	32.9	16	5942	37.0	5941	37.0	5941	37.0
481.wrf	16	2309	77.4	2306	77.5	2303	77.6	16	2306	77.5	2308	77.4	2318	77.1
482.sphinx3	16	4183	74.6	4175	74.7	4183	74.5	16	3934	79.3	3940	79.1	3931	79.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

BIOS Settings

Hardware Prefetcher set to OFF

Adjacent Cache Line Prefetch set to OFF

Optimization for high-frequency FSB applications set to OFF

All results used taskset to bind processes to cores.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 104

Acer Altos R920 (Intel Xeon E7330)

SPECfp_rate_base2006 = 97.7

CPU2006 license: 97

Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2007

Tested by: Acer Incorporated

Software Availability: Nov-2007

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 104

Acer Altos R920 (Intel Xeon E7330)

SPECfp_rate_base2006 = 97.7

CPU2006 license: 97

Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2007

Tested by: Acer Incorporated

Software Availability: Nov-2007

Peak Compiler Invocation

C benchmarks (except as noted below):

```
/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/bin/icc
-L/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/lib
-I/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/bin/icpc
-L/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/lib
-I/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/include
```

Fortran benchmarks (except as noted below):

ifort

```
437.leslie3d: /home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/bin/ifort
-L/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/lib
-I/home/cmpllr/usr3/alrahate/compilers/icl0.1mainline/20070725/Linux32/include
```

Benchmarks using both Fortran and C:

icc ifort

Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
    444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
    465.tonto: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
    -auto-ilp32
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 104

Acer Altos R920 (Intel Xeon E7330)

SPECfp_rate_base2006 = 97.7

CPU2006 license: 97

Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2007

Tested by: Acer Incorporated

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
-scalar-rep- -prefetch -opt-malloc-options=3

482.sphinx3: -fast -unroll12

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll14
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12 -O0
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-opt-malloc-options=3

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12 -O0
-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll14 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -auto-ilp32



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

SPECfp_rate2006 = 104

Acer Altos R920 (Intel Xeon E7330)

SPECfp_rate_base2006 = 97.7

CPU2006 license: 97

Test date: Nov-2007

Test sponsor: Acer Incorporated

Hardware Availability: Nov-2007

Tested by: Acer Incorporated

Software Availability: Nov-2007

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.html>

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.17.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 13:37:59 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 30 November 2007.