



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint_rate2006 = 76.7

Asus P5E3 Deluxe (Intel Core 2 Extreme QX9650)

SPECint_rate_base2006 = 69.0

CPU2006 license: 13


Test sponsor: Intel Corporation

Tested by: Intel Corporation

Test date: Nov-2007

Hardware Availability: Nov-2007

Software Availability: Nov-2007



Hardware

CPU Name:	Intel Core 2 Extreme QX9650
CPU Characteristics:	3.00 GHz 1333 MHz FSB
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	4 GB (4x1GB Corsair TWIN3X2048-1333C9DHX DDR3-1333 CL9)
Disk Subsystem:	Seagate 320GB NCQ SATA, 16MB cache, 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows Vista64 Ultimate
Compiler:	Intel C++ Compiler for IA32 version 10.1 Build 20070913 Package ID: w_cc_p_10.1.011 Microsoft Visual Studio 2005 SP1 (for libraries)
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	SmartHeap Library Version 8.1 from http://www.microquill.com/



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint_rate2006 = 76.7

Asus P5E3 Deluxe (Intel Core 2 Extreme QX9650)

SPECint_rate_base2006 = 69.0

CPU2006 license: 13

Test date: Nov-2007

Test sponsor: Intel Corporation

Hardware Availability: Nov-2007

Tested by: Intel Corporation

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	543	71.9	546	71.5	545	71.7	4	417	93.8	419	93.4	419	93.4
401.bzip2	4	636	60.7	634	60.9	634	60.9	4	612	63.0	615	62.8	614	62.8
403.gcc	4	492	65.4	489	65.8	495	65.1	4	497	64.7	500	64.4	501	64.3
429.mcf	4	466	78.4	465	78.5	465	78.4	4	472	77.3	473	77.2	472	77.2
445.gobmk	4	526	79.7	527	79.6	526	79.8	4	482	87.1	483	86.8	481	87.3
456.hammer	4	592	63.0	592	63.0	593	63.0	4	546	68.4	546	68.3	546	68.4
458.sjeng	4	677	71.4	678	71.4	678	71.4	4	598	80.9	598	80.9	598	80.9
462.libquantum	4	1317	62.9	1319	62.8	1319	62.8	1	198	105	198	105	198	105
464.h264ref	4	712	124	712	124	712	124	4	674	131	674	131	674	131
471.omnetpp	4	530	47.2	530	47.1	530	47.1	4	506	49.4	506	49.4	506	49.4
473.astar	4	565	49.7	563	49.8	564	49.8	4	521	53.9	521	53.9	521	53.9
483.xalancbmk	4	352	78.3	352	78.5	352	78.5	4	341	80.9	341	81.0	341	81.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply Product description located as of 11/2007:

<http://www.asus.com/products.aspx?li=3&l2=11&l3=572&l4=0&model=1872&modelmenu=1>

The system bus runs at 1333 MHz

System was configured with Asus EN8800GTX discrete graphics card

Binaries were built on Windows Vista32

The following VS 2005 SP1 updates were applied: KB926601 and KB932232

The start command with the /affinity switch was used to bind processes to cores OMP_NUM_THREADS was set to number of logical processors as seen by the OS

KMP_AFFINITY was set to physical,0

submit was disabled for 462.libquantum at peak.

Base Compiler Invocation

C benchmarks:

icl -Qvc8 -Qc99

C++ benchmarks:

icl -Qvc8

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint_rate2006 = 76.7

Asus P5E3 Deluxe (Intel Core 2 Extreme QX9650)

SPECint_rate_base2006 = 69.0

CPU2006 license: 13

Test date: Nov-2007

Test sponsor: Intel Corporation

Hardware Availability: Nov-2007

Tested by: Intel Corporation

Software Availability: Nov-2007

Base Portability Flags (Continued)

464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
483.xalancbmk: -Qoption,cpp, --no_wchar_t_keyword

Base Optimization Flags

C benchmarks:

-fast -Qvec-guard-write /F512000000

C++ benchmarks:

-fast -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks:

icl -Qvc8 -Qc99

C++ benchmarks:

icl -Qvc8

Peak Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
483.xalancbmk: -Qoption,cpp, --no_wchar_t_keyword

Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qprefetch /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint_rate2006 = 76.7

Asus P5E3 Deluxe (Intel Core 2 Extreme QX9650)

SPECint_rate_base2006 = 69.0

CPU2006 license: 13

Test date: Nov-2007

Test sponsor: Intel Corporation

Hardware Availability: Nov-2007

Tested by: Intel Corporation

Software Availability: Nov-2007

Peak Optimization Flags (Continued)

401.bzip2: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qprefetch
/F512000000

403.gcc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast /F512000000

429.mcf: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qprefetch
/F512000000 shlw32m.lib -link /FORCE:MULTIPLE

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qipo
-Qprec-div- -Qansi-alias /F512000000

456.hmmr: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll12
-Qansi-alias -Qopt-multi-version-aggressive /F512000000

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll14
/F512000000

462.libquantum: -fast -Qunroll14 -Ob0 -Qprefetch
-Qopt-streaming-stores:always -Qparallel
-Qpar-runtime-control /F512000000

464.h264ref: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll12
-Qansi-alias /F512000000

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qopt-ra-region-strategy=block -Qcxx_features /F512000000
shlw32m.lib -link /FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qopt-ra-region-strategy=routine -Qcxx_features /F512000000
shlw32m.lib -link /FORCE:MULTIPLE

483.xalancbmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.09.html>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

SPECint_rate2006 = 76.7

Asus P5E3 Deluxe (Intel Core 2 Extreme QX9650)

SPECint_rate_base2006 = 69.0

CPU2006 license: 13

Test date: Nov-2007

Test sponsor: Intel Corporation

Hardware Availability: Nov-2007

Tested by: Intel Corporation

Software Availability: Nov-2007

You can also download the XML flags source by saving the following link:

<http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.09.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 14:24:16 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 27 November 2007.