SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Asus P5E3 Deluxe (Intel Core 2 Duo E6850)

SPECint®2006 = 23.0

SPECint_base2006 = 21.3

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Nov-2007
Hardware Availability: Nov-2007
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Core 2 Duo E6850
CPU Characteristics:	3.00 GHz 1333 MHz FSB
CPU MHz:	3000
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	4 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	2 GB (2x1GB Corsair TWIN3X2048-1333C9DHX DDR3-1333 CL9)
Disk Subsystem:	Seagate 320GB NCQ SATA, 16MB cache, 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows Vista64 Ultimate
Compiler:	Intel C++ Compiler for IA32 version 10.1 Build 20070913 Package ID: w_cc_p_10.1.011 Microsoft Visual Studio 2005 SP1 (for libraries)
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	SmartHeap Library Version 8.1 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Asus P5E3 Deluxe (Intel Core 2 Duo E6850)

SPECint2006 = 23.0

SPECint_base2006 = 21.3

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Nov-2007
Hardware Availability: Nov-2007
Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	510	19.2	509	19.2	**509**	**19.2**	397	24.6	396	24.6	**396**	**24.6**
401.bzip2	**602**	**16.0**	626	15.4	598	16.1	605	15.9	**578**	**16.7**	575	16.8
403.gcc	**382**	**21.0**	375	21.5	385	20.9	351	22.9	**351**	**22.9**	351	22.9
429.mcf	328	27.8	327	27.9	**327**	**27.9**	328	27.8	327	27.9	**327**	**27.9**
445.gobmk	548	19.2	**548**	**19.2**	548	19.2	469	22.4	**469**	**22.4**	469	22.4
456.hmmer	**593**	**15.7**	592	15.8	593	15.7	545	17.1	**545**	**17.1**	545	17.1
458.sjeng	679	17.8	679	17.8	**679**	**17.8**	606	20.0	606	20.0	**606**	**20.0**
462.libquantum	422	49.1	423	48.9	**423**	**49.0**	468	44.2	468	44.3	**468**	**44.3**
464.h264ref	708	31.3	**707**	**31.3**	707	31.3	682	32.4	**681**	**32.5**	681	32.5
471.omnetpp	362	17.3	362	17.3	**362**	**17.3**	325	19.2	325	19.2	**325**	**19.2**
473.astar	466	15.1	466	15.1	**466**	**15.1**	416	16.9	**416**	**16.9**	416	16.9
483.xalancbmk	**302**	**22.8**	302	22.8	302	22.8	290	23.8	290	23.8	**290**	**23.8**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
Product description located as of 11/2007:
http://www.asus.com/products.aspx?l1=3&l2=11&l3=572&l4=0&model=1872&modelmenu=1
The system bus runs at 1333 MHz
System was configured with Asus EN8800GTX discrete graphics card
Binaries were built on Windows Vista32
The following VS 2005 SP1 updates were applied: KB926601 and KB932232
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc8 -Qc99
```

C++ benchmarks:

```
icl -Qvc8
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:
```
-fast -Qparallel -Qpar-runtime-control -Qvec-guard-write /F512000000
libguide40.lib
```

C++ benchmarks:
```
-fast -Qcxx_features /F512000000 shlw32m.lib libguide40.lib
            -link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc8 -Qc99
```

C++ benchmarks:
```
icl -Qvc8
```

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Peak Optimization Flags

C benchmarks:

400.perlbench: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast -Qansi-alias -Qprefetch -Qparallel -Qpar-runtime-control /F512000000 shlw32m.lib libguide40.lib -link /FORCE:MULTIPLE`

401.bzip2: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast -Qprefetch /F512000000 libguide40.lib`

403.gcc: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast /F512000000 libguide40.lib`

Continued on next page

Peak Optimization Flags (Continued)

429.mcf: basepeak = yes

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qipo -Qprec-div- -Qansi-alias /F512000000

456.hmmer: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2 -Qansi-alias -Qopt-multi-version-aggressive /F512000000 libguide40.lib

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4 /F512000000 libguide40.lib

462.libquantum: -fast -Qunroll4 -Ob0 -Qprefetch -Qopt-streaming-stores:always -Qparallel -Qpar-runtime-control /F512000000 libguide40.lib

464.h264ref: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2 -Qansi-alias /F512000000 libguide40.lib

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias -Qopt-ra-region-strategy=block -Qcxx_features /F512000000 shlw32m.lib libguide40.lib -link /FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias -Qopt-ra-region-strategy=routine -Qcxx_features /F512000000 shlw32m.lib libguide40.lib -link /FORCE:MULTIPLE

483.xalancbmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias -Qcxx_features /F512000000 shlw32m.lib libguide40.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.09.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.09.xml

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Asus P5E3 Deluxe (Intel Core 2 Duo E6850)

SPECint2006 = 23.0

SPECint_base2006 = 21.3

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Nov-2007
Hardware Availability: Nov-2007
Software Availability: Nov-2007

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 14:34:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 27 November 2007.