SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP BladeSystem bc2500 Blade PC
(1.6GHz AMD Athlon 64 X2 3000+)

SPECfp®2006 = 8.36

SPECfp_base2006 = 7.92

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: AMD Performance Labs

Test date: Dec-2007
Hardware Availability: Jun-2007
Software Availability: Mar-2008



Hardware

CPU Name:	AMD Athlon 64 X2 3000+
CPU Characteristics:	
CPU MHz:	1600
FPU:	Integrated
CPU(s) enabled:	2 cores, 1 chip, 2 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core

Continued on next page

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
Compiler:	QLogic PathScale Compiler Suite, Release 3.0
Auto Parallel:	No
File System:	ext3
System State:	Multi-user, run level 3
Base Pointers:	64-bit
Peak Pointers:	32/64-bit

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

HP BladeSystem bc2500 Blade PC
(1.6GHz AMD Athlon 64 X2 3000+)

SPECfp2006 = 8.36

SPECfp_base2006 = 7.92

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: AMD Performance Labs

Test date: Dec-2007
Hardware Availability: Jun-2007
Software Availability: Mar-2008

L3 Cache: None
Other Cache: None
Memory: 4 GB (2x2GB, DDR2-667 CL5 ECC Reg Dual Rank)
Disk Subsystem: 1x80 GB SATA, 5400 RPM
Other Hardware: None

Other Software: None

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	1196	11.4	**1196**	**11.4**	1201	11.3	**1099**	**12.4**	1099	12.4	1102	12.3
416.gamess	2512	7.79	**2507**	**7.81**	2500	7.83	**2190**	**8.94**	2210	8.86	2189	8.94
433.milc	1110	8.27	**1109**	**8.27**	1109	8.28	1043	8.80	**1050**	**8.74**	1053	8.71
434.zeusmp	1320	6.89	**1313**	**6.93**	1311	6.94	1298	7.01	1301	7.00	**1299**	**7.00**
435.gromacs	1059	6.74	**1054**	**6.78**	1052	6.79	**936**	**7.63**	934	7.65	936	7.63
436.cactusADM	1546	7.73	**1503**	**7.95**	1503	7.95	**1535**	**7.78**	1483	8.06	1536	7.78
437.leslie3d	1292	7.27	**1288**	**7.30**	1274	7.38	1292	7.27	**1288**	**7.30**	1274	7.38
444.namd	1166	6.88	**1167**	**6.87**	1168	6.86	1102	7.28	**1101**	**7.29**	1100	7.29
447.dealII	1146	9.98	**1144**	**10.0**	1142	10.0	878	13.0	**883**	**13.0**	884	12.9
450.soplex	1262	6.61	**1252**	**6.66**	1248	6.68	1116	7.47	**1120**	**7.45**	1122	7.44
453.povray	584	9.10	**585**	**9.09**	591	9.00	535	9.94	**535**	**9.95**	534	9.97
454.calculix	1997	4.13	**1995**	**4.13**	1992	4.14	**1854**	**4.45**	1854	4.45	1854	4.45
459.GemsFDTD	**1401**	**7.57**	1401	7.57	1403	7.56	1462	7.26	**1463**	**7.25**	1464	7.25
465.tonto	1175	8.38	1167	8.43	**1169**	**8.42**	1175	8.38	1167	8.43	**1169**	**8.42**
470.lbm	1367	10.1	**1364**	**10.1**	1357	10.1	1367	10.1	**1364**	**10.1**	1357	10.1
481.wrf	1208	9.24	**1209**	**9.24**	1211	9.23	1208	9.24	**1209**	**9.24**	1211	9.23
482.sphinx3	2101	9.28	2087	9.34	**2100**	**9.28**	**2114**	**9.22**	2119	9.20	2111	9.23

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Base Compiler Invocation

C benchmarks:
`pathcc`

C++ benchmarks:
`pathCC`

Fortran benchmarks:
`pathf95`

Benchmarks using both Fortran and C:
`pathcc pathf95`

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX -fno-second-underscore
482.sphinx3: -DSPEC_CPU_LP64

Base Optimization Flags

C benchmarks:
-Ofast

C++ benchmarks:
-Ofast

Fortran benchmarks:
-Ofast -OPT:malloc_alg=1

Benchmarks using both Fortran and C:
-Ofast -OPT:malloc_alg=1

Peak Compiler Invocation

C benchmarks:
pathcc

C++ benchmarks:
pathCC

Fortran benchmarks:
pathf95

Benchmarks using both Fortran and C:
pathcc pathf95

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64
436.cactusADM: -DSPEC_CPU_LP64 -fno-second-underscore
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX -fno-second-underscore
482.sphinx3: -DSPEC_CPU_LP64

Peak Optimization Flags

C benchmarks:

433.milc: -Ofast -CG:cflow=off -LNO:prefetch=1 -OPT:malloc_alg=1

470.lbm: basepeak = yes

482.sphinx3: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-OPT:Ofast -WOPT:aggstr=0 -m32

C++ benchmarks:

444.namd: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-fno-exceptions

447.dealII: -Ofast -INLINE:aggressive=on -OPT:malloc_alg=1 -m32
-fno-exceptions

450.soplex: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -m32 -O3
-OPT:IEEE_arith=3 -CG:load_exe=0 -CG:movnti=1
-LNO:minvariant=off -LNO:prefetch=1 -fno-exceptions

453.povray: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -Ofast
-fno-fast-math

Fortran benchmarks:

410.bwaves: -fb_create fbdata(pass 1) -fb_opt fbdata(pass 2) -O3
-OPT:Ofast -OPT:IEEE_arith=3 -LNO:blocking=off
-LNO:ignore_feedback=off

Continued on next page

Peak Optimization Flags (Continued)

416.gamess: `-fb_create fbdata`(pass 1) `-fb_opt fbdata`(pass 2) `-O2 -OPT:Ofast -OPT:ro=3 -OPT:unroll_size=256`

434.zeusmp: `-Ofast -CG:local_fwd_sched=on -LNO:blocking=off -LNO:interchange=off -LNO:fu=10 -LNO:full_unroll_outer=on`

437.leslie3d: `basepeak = yes`

459.GemsFDTD: `-Ofast -LNO:fission=2 -LNO:prefetch=0`

465.tonto: `basepeak = yes`

Benchmarks using both Fortran and C:

435.gromacs: `-O3 -OPT:rsqrt=2 -OPT:ro=3`

436.cactusADM: `-fb_create fbdata`(pass 1) `-fb_opt fbdata`(pass 2) `-O3 -LNO:prefetch=3 -LNO:prefetch_ahead=5 -LNO:ou_prod_max=10 -LNO:full_unroll=5 -ipa`

454.calculix: `-Ofast -LNO:simd=0 -WOPT:mem_opnds=on`

481.wrf: `basepeak = yes`

Peak Other Flags

C++ benchmarks:

447.dealII: `-static`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090714.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 16:11:45 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 January 2008.