SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Lenovo ThinkPad T43 (Intel Pentium M 780)

SPECint®_rate2006 = 11.4

SPECint_rate_base2006 = 10.7

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Dec-2007
Hardware Availability: Jan-2008
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Pentium M 780
CPU Characteristics:	
CPU MHz:	2266
FPU:	Integrated
CPU(s) enabled:	1 core, 1 chip, 1 core/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per chip
Secondary Cache:	2 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	2 GB (2x1GB Hynix DDR2-667 CL5)
Disk Subsystem:	Hitachi 100 GB SATA, 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows Vista Ultimate (32-bit)
Compiler:	Intel C++ Compiler for IA32 version 10.1 Build 20070913 Package ID: w_cc_p_10.1.011 Microsoft Visual Studio 2005 SP1 (for libraries)
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	None SmartHeap Library Version 8.1 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Intel Corporation

Lenovo ThinkPad T43 (Intel Pentium M 780)

SPECint_rate2006 = 11.4

SPECint_rate_base2006 = 10.7

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: Dec-2007
Hardware Availability: Jan-2008
Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	1	902	10.8	900	10.9	**900**	**10.9**	1	688	14.2	689	14.2	**689**	**14.2**
401.bzip2	1	1143	8.44	1089	8.86	**1090**	**8.86**	1	1064	9.07	**1064**	**9.07**	1069	9.03
403.gcc	1	1140	7.06	**1135**	**7.09**	1134	7.10	1	**1060**	**7.59**	1060	7.59	1062	7.58
429.mcf	1	676	13.5	**676**	**13.5**	677	13.5	1	684	13.3	684	13.3	**684**	**13.3**
445.gobmk	1	782	13.4	783	13.4	**783**	**13.4**	1	722	14.5	722	14.5	**722**	**14.5**
456.hmmer	1	1113	8.38	1114	8.38	**1113**	**8.38**	1	1043	8.95	**1042**	**8.95**	1042	8.95
458.sjeng	1	997	12.1	**997**	**12.1**	997	12.1	1	932	13.0	932	13.0	**932**	**13.0**
462.libquantum	1	1667	12.4	**1667**	**12.4**	1666	12.4	1	1677	12.4	**1677**	**12.4**	1677	12.4
464.h264ref	1	**1374**	**16.1**	1374	16.1	1375	16.1	1	**1217**	**18.2**	1217	18.2	1218	18.2
471.omnetpp	1	**723**	**8.65**	723	8.65	723	8.65	1	**702**	**8.90**	702	8.90	702	8.90
473.astar	1	789	8.90	788	8.90	**788**	**8.90**	1	749	9.37	**749**	**9.37**	749	9.37
483.xalancbmk	1	**583**	**11.8**	584	11.8	583	11.8	1	573	12.0	**573**	**12.0**	573	12.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
The system bus runs at 533 MHz
Binaries were built on Windows Vista (32-bit)
The following VS 2005 SP1 updates were applied: KB926601 and KB932232
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc8 -Qc99
```

C++ benchmarks:

```
icl -Qvc8
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:
```
-QxB -Qipo -O3 -Qprec-div- -Qvec-guard-write /F512000000
```

C++ benchmarks:
```
-QxB -Qipo -O3 -Qprec-div- -Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
```
icl -Qvc8 -Qc99
```

C++ benchmarks:
```
icl -Qvc8
```

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Peak Optimization Flags

C benchmarks:

400.perlbench: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-QxB -Qipo -O3 -Qprec-div- -Qansi-alias -Qprefetch /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

401.bzip2: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-QxB -Qipo -O3 -Qprec-div- -Qprefetch /F512000000`

403.gcc: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-QxB -Qipo -O3 -Qprec-div- /F512000000`

Continued on next page

Peak Optimization Flags (Continued)

429.mcf: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxB -Qipo -O3
-Qprec-div- -Qprefetch /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxB -O2 -Qipo
-Qprec-div- -Qansi-alias /F512000000

456.hmmer: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxB -Qipo -O3
-Qprec-div- -Qunroll2 -Qansi-alias
-Qopt-multi-version-aggressive /F512000000

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxB -Qipo -O3
-Qprec-div- -Qunroll4 /F512000000

462.libquantum: -QxB -Qipo -O3 -Qprec-div- -Qunroll4 -Ob0 -Qprefetch
-Qopt-streaming-stores:always -Qparallel
-Qpar-runtime-control /F512000000

464.h264ref: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxB -Qipo -O3
-Qprec-div- -Qunroll2 -Qansi-alias /F512000000

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxB -Qipo -O3
-Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=block
-Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxB -Qipo -O3
-Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=routine
-Qcxx_features /F512000000 shlw32m.lib
-link /FORCE:MULTIPLE

483.xalancbmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxB -Qipo -O3
-Qprec-div- -Qansi-alias -Qcxx_features /F512000000
shlw32m.lib -link /FORCE:MULTIPLE

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.09.html

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.09.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 16:09:48 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 January 2008.