# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

## IBM BladeCenter HS21 (Intel Xeon E5420)

SPECfp®_rate2006 = Not Run

SPECfp_rate_base2006 = 63.3

**CPU2006 license:** 11
**Test sponsor:** IBM Corporation
**Tested by:** IBM Corporation

**Test date:** Dec-2007
**Hardware Availability:** Jan-2008
**Software Availability:** Nov-2007




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5420 |
| CPU Characteristics: | 1333MHz system bus |
| CPU MHz: | 2493 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 12 MB I+D on chip per chip, 6 MB shared / 2 cores |

Continued on next page

### Software

| | |
|---|---|
| Operating System: | SuSE Linux Enterprise Server 10 (x86_64), Kernel 2.6.16.21-0.8-smp |
| Compiler: | Intel C++ and Fortran Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008, l_fc_p_10.1.008 |
| Auto Parallel: | No |
| File System: | ReiserFS |
| System State: | Multi-user, run level 3 |
| Base Pointers: | 64-bit |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

## IBM BladeCenter HS21 (Intel Xeon E5420)

SPECfp_rate2006 = Not Run

SPECfp_rate_base2006 = 63.3

**CPU2006 license:** 11
**Test sponsor:** IBM Corporation
**Tested by:** IBM Corporation

**Test date:** Dec-2007
**Hardware Availability:** Jan-2008
**Software Availability:** Nov-2007

L3 Cache: None
Other Cache: None
Memory: 16 GB (8 x 2 GB DDR2-5300F ECC)
Disk Subsystem: 1 x 36 GB SAS, 10000 RPM
Other Hardware: None

Peak Pointers: Not Applicable
Other Software: Binutils 2.17.50.0.15

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 8 | **3222** | **33.7** | 3221 | 33.8 | 3222 | 33.7 | | | | | | | |
| 416.gamess | 8 | 1064 | 147 | **1063** | **147** | 1063 | 147 | | | | | | | |
| 433.milc | 8 | **2533** | **29.0** | 2534 | 29.0 | 2531 | 29.0 | | | | | | | |
| 434.zeusmp | 8 | 1083 | 67.2 | 1089 | 66.8 | **1087** | **67.0** | | | | | | | |
| 435.gromacs | 8 | **467** | **122** | 466 | 122 | 467 | 122 | | | | | | | |
| 436.cactusADM | 8 | 1370 | 69.8 | 1374 | 69.6 | **1371** | **69.7** | | | | | | | |
| 437.leslie3d | 8 | **2852** | **26.4** | 2852 | 26.4 | 2849 | 26.4 | | | | | | | |
| 444.namd | 8 | 609 | 105 | **609** | **105** | 609 | 105 | | | | | | | |
| 447.dealII | 8 | 749 | 122 | **774** | **118** | 775 | 118 | | | | | | | |
| 450.soplex | 8 | **1837** | **36.3** | 1838 | 36.3 | 1837 | 36.3 | | | | | | | |
| 453.povray | 8 | 254 | 168 | 251 | 169 | **252** | **169** | | | | | | | |
| 454.calculix | 8 | **657** | **100** | 658 | 100 | 656 | 101 | | | | | | | |
| 459.GemsFDTD | 8 | 3079 | 27.6 | 3069 | 27.7 | **3070** | **27.6** | | | | | | | |
| 465.tonto | 8 | 757 | 104 | 759 | 104 | **758** | **104** | | | | | | | |
| 470.lbm | 8 | **4214** | **26.1** | 4229 | 26.0 | 4210 | 26.1 | | | | | | | |
| 481.wrf | 8 | 1763 | 50.7 | **1760** | **50.8** | 1760 | 50.8 | | | | | | | |
| 482.sphinx3 | 8 | 2356 | 66.2 | **2370** | **65.8** | 2394 | 65.1 | | | | | | | |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

```
All benchmarks compiled in 64-bit mode
Hardware Sector Prefetch Disabled and Adjacent Sector Prefetch Disabled
taskset utility used to bind CPU(s) to processes
```

## Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Continued on next page

## Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
-fast

C++ benchmarks:
-fast

Fortran benchmarks:
-fast

Benchmarks using both Fortran and C:
-fast

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.11.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic10.1-FP-intel64-linux-flags.20090714.11.xml

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 16:33:29 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 6 February 2008.