SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4150

SPECint®_rate2006 = 133

SPECint_rate_base2006 = 108

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Jan-2008
Hardware Availability: Feb-2008
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Xeon X5460
CPU Characteristics:	3.16 GHz, 2x6 MB L2 shared, 1333 MHz system bus
CPU MHz:	3166
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 (order by number of chips)
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8x2GB DDR2 PC2-5300F 2rank CAS 5-5-5 with ECC)
Disk Subsystem:	SAS, 72 GB, 10K RPM
Other Hardware:	None

Software

Operating System:	SUSE LINUX Enterprise Server 10 SP1 for x86_64
Compiler:	Intel C++ and Fortran Compiler for Linux32 and Linux64 version 10.1 Build 20070725
Auto Parallel:	Yes
File System:	ReiserFS
System State:	Multi-user, run level 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	SmartHeap library V8.1 Binutils 2.17.50.0.15

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun Fire X4150

SPECint_rate2006 = 133

SPECint_rate_base2006 = 108

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Jan-2008
Hardware Availability: Feb-2008
Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	498	157	**495**	**158**	493	159	8	422	185	420	186	**420**	**186**
401.bzip2	8	696	111	693	111	**695**	**111**	8	663	116	**663**	**116**	662	117
403.gcc	8	738	87.2	**737**	**87.4**	735	87.6	8	739	87.2	734	87.7	**735**	**87.7**
429.mcf	8	**925**	**78.8**	923	79.0	928	78.6	8	**925**	**78.8**	923	79.0	928	78.6
445.gobmk	8	**529**	**159**	530	158	523	160	8	496	169	486	173	**493**	**170**
456.hmmer	8	562	133	563	132	**563**	**133**	8	334	224	**333**	**224**	333	224
458.sjeng	8	658	147	**659**	**147**	661	147	8	602	161	603	160	**603**	**161**
462.libquantum	8	3352	49.5	**3351**	**49.5**	3351	49.5	1	**93.7**	**221**	93.9	221	93.5	222
464.h264ref	8	671	264	672	264	**671**	**264**	8	**642**	**276**	641	276	643	276
471.omnetpp	8	**950**	**52.6**	951	52.6	949	52.7	8	**941**	**53.1**	941	53.1	941	53.1
473.astar	8	718	78.2	712	78.9	**717**	**78.3**	8	668	84.1	**668**	**84.1**	670	83.8
483.xalancbmk	8	448	123	448	123	**448**	**123**	8	448	123	448	123	**448**	**123**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited
OMP_NUM_THREADS set to 8
KMP_STACKSIZE set to 64M
KMP_AFFINITY set to physical,0
```

Platform Notes

```
BIOS configuration:
Hardware Prefetch = Disable; Adjacent Sector Prefetch = Disable
```

General Notes

```
All benchmarks were compiled in 32-bit mode except 401.bzip2
and 456.hmmer for peak were compiled in 64-bit mode
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Base Optimization Flags

C benchmarks:
`-fast -inline-calloc -opt-malloc-options=3`

C++ benchmarks:
`-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs`
`-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks (except as noted below):
`icc`

401.bzip2: `/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc`

456.hmmer: `/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/bin/icc`

C++ benchmarks:
`icpc`

Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
401.bzip2: `-DSPEC_CPU_LP64`
456.hmmer: `-DSPEC_CPU_LP64`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias -prefetch

401.bzip2: -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: basepeak = yes

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo -no-prec-div -ansi-alias

456.hmmer: -L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/lib -I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070725/Linux64/include -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always -vec-guard-write -opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs -L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs -L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.24.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.24.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 15:38:05 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 7 March 2008.