SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (Intel Xeon X5260)

SPECint®_rate2006 = 81.0

SPECint_rate_base2006 = 69.4

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Mar-2008
Hardware Availability: Nov-2007
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Xeon X5260
CPU Characteristics:	1333MHz system bus
CPU MHz:	3333
FPU:	Integrated
CPU(s) enabled:	4 cores, 2 chips, 2 cores/chip
CPU(s) orderable:	1, 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	6 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8 x 2048MB ECC FB-DIMM DDR2-667 CL5-5-5)
Disk Subsystem:	1 x 73GB 10000PRM SAS HDD
Other Hardware:	None

Software

Operating System:	SuSE Linux Enterprise Server 10 SP1 (x86_64) Kernel 2.6.16.46-0.12-smp
Compiler:	Intel C++ Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008
Auto Parallel:	Yes
File System:	ReiserFS
System State:	Multi-user, level 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V8.1 Binutils 2.17.50.0.15

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Acer Incorporated

Acer Altos R520 (Intel Xeon X5260)

SPECint_rate2006 = 81.0

SPECint_rate_base2006 = 69.4

CPU2006 license: 97
Test sponsor: Acer Incorporated
Tested by: Acer Incorporated

Test date: Mar-2008
Hardware Availability: Nov-2007
Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	4	475	82.3	464	84.2	**468**	**83.5**	4	392	99.7	**392**	**99.6**	394	99.1
401.bzip2	4	**636**	**60.7**	636	60.7	643	60.1	4	598	64.5	**604**	**63.9**	605	63.8
403.gcc	4	532	60.5	526	61.3	**526**	**61.2**	4	**527**	**61.1**	528	61.0	526	61.2
429.mcf	4	583	62.6	581	62.8	**581**	**62.8**	4	593	61.5	**592**	**61.6**	592	61.7
445.gobmk	4	496	84.6	497	84.4	**496**	**84.5**	4	458	91.7	**458**	**91.6**	458	91.6
456.hmmer	4	531	70.2	531	70.3	**531**	**70.3**	4	309	121	308	121	**309**	**121**
458.sjeng	4	629	77.0	624	77.5	**627**	**77.2**	4	567	85.3	**568**	**85.3**	568	85.3
462.libquantum	4	**1500**	**55.3**	1500	55.3	1502	55.2	1	177	117	**176**	**117**	176	118
464.h264ref	4	633	140	634	140	**633**	**140**	4	605	146	**605**	**146**	605	146
471.omnetpp	4	596	41.9	597	41.9	**596**	**41.9**	4	565	44.3	566	44.2	**565**	**44.2**
473.astar	4	**548**	**51.3**	547	51.4	549	51.1	4	508	55.2	**508**	**55.3**	508	55.3
483.xalancbmk	4	330	83.7	**329**	**83.9**	329	84.0	4	330	83.7	**329**	**83.9**	329	84.0

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
This result was measured on the Acer Altos R520.
The Altos R720 and Altos R520 are electronically equivalent.

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer,
for peak, are compiled in 64-bit mode
BIOS Settings
  Hardware Prefetcher set to ON

  Adjacent Cache Line Prefetch set to ON

All results but peak 462.libquantum used taskset to bind
processes to cores.
"ulimit -s unlimited" was set for stacksize unlimited
OMP_NUM_THREADS set to number of cores
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page

Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo -no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always -vec-guard-write -opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs -L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs -L/spec/users/rahul/cpu2006.1.0/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revC.20090713.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revC.20090713.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 18:12:13 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 9 April 2008.