Fujitsu Siemens Computers

PRIMERGY TX300 S4, Intel Xeon E5430, 2.66 GHz

SPECint®_rate2006 = Not Run

SPECint_rate_base2006 = 102

CPU2006 license: 22		**Test date:**	Mar-2008
Test sponsor:	Fujitsu Siemens Computers	**Hardware Availability:**	Dec-2007
Tested by:	Fujitsu Siemens Computers	**Software Availability:**	Nov-2007



Hardware

CPU Name:	Intel Xeon E5430
CPU Characteristics:	1333 MHz system bus
CPU MHz:	2667
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8x2 GB PC2-5300F, 2 rank, CL 5-5-5, ECC)
Disk Subsystem:	1x SAS, 73 GB, 15000 rpm
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
Compiler:	Intel C++ Compiler for Linux32 and Linux64, Version 10.1, Build 20070913
Auto Parallel:	No
File System:	ext2
System State:	Multi-User Run Level 3
Base Pointers:	32-bit
Peak Pointers:	Not Applicable
Other Software:	MicroQuill SmartHeap Library, Version 8.1 binutils-2.17.50.0.5-0.1.x86_64

SPEC CINT2006 Result

Fujitsu Siemens Computers

PRIMERGY TX300 S4, Intel Xeon E5430, 2.66 GHz

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 102

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers
Test date: Mar-2008
Hardware Availability: Dec-2007
Software Availability: Nov-2007

Results Table

	Base							Peak						
Benchmark	**Copies**	**Seconds**	**Ratio**	**Seconds**	**Ratio**	**Seconds**	**Ratio**	**Copies**	**Seconds**	**Ratio**	**Seconds**	**Ratio**	**Seconds**	**Ratio**
400.perlbench	8	**597**	**131**	594	132	597	131							
401.bzip2	8	**834**	**92.6**	842	91.7	826	93.5							
403.gcc	8	696	92.6	**697**	**92.4**	697	92.4							
429.mcf	8	909	80.2	**913**	**79.9**	914	79.8							
445.gobmk	8	629	134	**629**	**133**	632	133							
456.hmmer	8	682	109	**681**	**110**	681	110							
458.sjeng	8	771	126	**772**	**125**	772	125							
462.libquantum	8	3259	50.9	3258	50.9	**3259**	**50.9**							
464.h264ref	8	**795**	**223**	795	223	793	223							
471.omnetpp	8	**719**	**69.5**	718	69.6	720	69.5							
473.astar	8	**733**	**76.6**	735	76.4	731	76.8							
483.xalancbmk	8	**454**	**122**	454	122	454	122							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
```

Platform Notes

```
BIOS configuration:
Hardware Prefetch = Disable, Adjacent Sector Prefetch = Disable
```

General Notes

```
For information about Fujitsu Siemens Computers please see:
http://www.fujitsu-siemens.com
```

Base Compiler Invocation

C benchmarks:
    icc

C++ benchmarks:
    icpc

SPEC CINT2006 Result

Fujitsu Siemens Computers

PRIMERGY TX300 S4, Intel Xeon E5430, 2.66 GHz

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 102

CPU2006 license: 22		**Test date:**	Mar-2008
Test sponsor:	Fujitsu Siemens Computers	**Hardware Availability:**	Dec-2007
Tested by:	Fujitsu Siemens Computers	**Software Availability:**	Nov-2007

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/opt/SmartHeap_8.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090713.01.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090713.01.xml

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:55:06 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 April 2008.