SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M460, Intel Core 2 Quad Q9550

SPECint®2006 = 22.9

SPECint_base2006 = 20.6

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: Feb-2008
Hardware Availability: Mar-2008
Software Availability: Nov-2007



Hardware

CPU Name:	Intel Core 2 Quad Q9550
CPU Characteristics:	
CPU MHz:	2833
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	4 GB (4x1 GB PC2-6400 CL6 SDRAM)
Disk Subsystem:	1 x 400 GB SATA 7200 RPM
Other Hardware:	None

Software

Operating System:	Windows Vista Ultimate, 64 bit Version
Compiler:	Intel C++ Compiler for applications running on IA-32, Version 10.1, Build 20070913 Intel C++ Compiler for applications running on Intel 64, Version 10.1, Build 20070913 Microsoft Visual Studio 2005 with SP1 (for libraries)
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	MicroQuill SmartHeap Library 8.1

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M460, Intel Core 2 Quad Q9550

SPECint2006 = 22.9

SPECint_base2006 = 20.6

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: Feb-2008
Hardware Availability: Mar-2008
Software Availability: Nov-2007

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	544	18.0	543	18.0	**543**	**18.0**	426	22.9	**428**	**22.8**	430	22.7
401.bzip2	622	15.5	616	15.7	**616**	**15.7**	581	16.6	**582**	**16.6**	589	16.4
403.gcc	**442**	**18.2**	448	18.0	441	18.2	385	20.9	**392**	**20.5**	399	20.2
429.mcf	**337**	**27.1**	337	27.1	337	27.1	**337**	**27.1**	337	27.1	337	27.1
445.gobmk	567	18.5	567	18.5	**567**	**18.5**	500	21.0	**502**	**20.9**	502	20.9
456.hmmer	624	14.9	624	15.0	**624**	**14.9**	441	21.2	442	21.1	**442**	**21.1**
458.sjeng	697	17.4	**698**	**17.3**	698	17.3	627	19.3	**630**	**19.2**	630	19.2
462.libquantum	395	52.5	**392**	**52.8**	389	53.3	395	52.5	**392**	**52.8**	389	53.3
464.h264ref	735	30.1	734	30.1	**734**	**30.1**	690	32.1	**693**	**31.9**	693	31.9
471.omnetpp	370	16.9	**370**	**16.9**	370	16.9	329	19.0	**331**	**18.9**	331	18.9
473.astar	482	14.6	482	14.6	**482**	**14.6**	431	16.3	**433**	**16.2**	433	16.2
483.xalancbmk	311	22.2	310	22.2	**310**	**22.2**	303	22.8	**304**	**22.7**	304	22.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

```
BIOS default settings have been used.
```

General Notes

```
 All binaries were built with 32-bit Intel compiler except:
 401.bzip2 and 456.hmmer in peak were built with 64-bit Intel
 compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers please see:
http://www.fujitsu-siemens.com/
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc8 -Qc99
```

C++ benchmarks:

```
icl -Qvc8
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:
```
-fast -Qparallel -Qvec-guard-write -Qpar-runtime-control -F512000000
libguide40.lib
```

C++ benchmarks:
```
-fast -Qcxx-features -F512000000 libguide40.lib shlW32M.lib
-link -FORCE:MULTIPLE
```

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks (except as noted below):
```
icl -Qvc8 -Qc99
```

401.bzip2:
```
C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Bin\\icl.exe
-IC:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Include
-link -LIBPATH:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Lib
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib"
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib\\amd64"
```

456.hmmer:
```
C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Bin\\icl.exe
-IC:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Include
-link -LIBPATH:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Lib
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib"
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib\\amd64"
```

C++ benchmarks:
```
icl -Qvc8
```

Peak Portability Flags

401.bzip2: -DSPEC_CPU_P64
403.gcc: -DSPEC_CPU_WIN32
456.hmmer: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
483.xalancbmk: -Qoption,cpp,--no_wchar_t_keyword

Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qparallel -Qpar-runtime-control -Qansi-alias -Qprefetch -F512000000 libguide40.lib shlW32M.lib -link -FORCE:MULTIPLE

401.bzip2: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qprefetch -F512000000 libguide40.lib

403.gcc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -F512000000 libguide40.lib

429.mcf: basepeak = yes

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -O2 -Qipo -QxT -Qprec-div- -Qansi-alias -F512000000

456.hmmer: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2 -Qansi-alias -Qopt-multi-version-aggressive -F512000000 libguide40.lib

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4 -F512000000 libguide40.lib

462.libquantum: basepeak = yes

464.h264ref: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2 -Qansi-alias -F512000000 libguide40.lib

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx-features -Qansi-alias -Qopt-ra-region-strategy=block -F512000000 libguide40.lib shlW32M.lib -link -FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qcxx-features -Qansi-alias -Qopt-ra-region-strategy=routine -F512000000 libguide40.lib shlW32M.lib -link -FORCE:MULTIPLE

Continued on next page

Peak Optimization Flags (Continued)

483.xalancbmk: `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-fast -Qcxx-features -Qansi-alias -F512000000 libguide40.lib shlW32M.lib -link -FORCE:MULTIPLE`

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.02.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.02.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:52:02 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 April 2008.