



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M460, Intel Core 2 Duo E8400

SPECint_rate2006 = 40.4

CPU2006 license: 22


Test date: Mar-2008

Hardware Availability: Mar-2008

Software Availability: Nov-2007

Test sponsor: Fujitsu Siemens Computers

Tested by: Fujitsu Siemens Computers



Hardware

CPU Name: Intel Core 2 Duo E8400
CPU Characteristics: 3000
CPU MHz: Integrated
FPU: 2 cores, 1 chip, 2 cores/chip
CPU(s) enabled: 1 chip
CPU(s) orderable: Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 6 MB I+D on chip per chip
L3 Cache: None
Other Cache: None
Memory: 4 GB (4x1 GB PC2-6400 CL6 SDRAM)
Disk Subsystem: 1 x 400 GB SATA 7200 RPM
Other Hardware: None

Software

Operating System: Windows Vista64 Ultimate
Compiler: Intel C++ Compiler for applications running on IA-32, Version 10.1, Build 20070913
Intel C++ Compiler for applications running on Intel 64, Version 10.1, Build 20070913
Microsoft Visual Studio 2005 with SP1 (for libraries)
Auto Parallel: No
File System: NTFS
System State: Default
Base Pointers: 32-bit
Peak Pointers: 32/64-bit
Other Software: SmartHeap Library Version 8.1 from <http://www.microquill.com/>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M460, Intel Core 2 Duo E8400

SPECint_rate2006 = 40.4

CPU2006 license: 22

Test date: Mar-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Mar-2008

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	2	533	36.6	544	35.9	543	36.0	2	414	47.2	415	47.1	414	47.3
401.bzip2	2	624	30.9	632	30.5	633	30.5	2	586	32.9	587	32.9	590	32.7
403.gcc	2	456	35.3	457	35.3	459	35.1	2	446	36.1	449	35.8	457	35.2
429.mcf	2	424	43.0	422	43.2	424	43.1	2	424	43.0	422	43.2	424	43.1
445.gobmk	2	526	39.9	526	39.9	526	39.9	2	487	43.1	485	43.2	487	43.1
456.hammer	2	595	31.4	594	31.4	595	31.4	2	419	44.5	419	44.5	422	44.2
458.sjeng	2	682	35.5	682	35.5	682	35.5	2	602	40.2	602	40.2	607	39.9
462.libquantum	2	951	43.6	952	43.5	952	43.5	2	951	43.6	952	43.5	952	43.5
464.h264ref	2	698	63.5	698	63.4	698	63.4	2	662	66.9	662	66.9	667	66.4
471.omnetpp	2	465	26.9	465	26.9	465	26.9	2	424	29.5	424	29.5	431	29.0
473.astar	2	530	26.5	530	26.5	530	26.5	2	484	29.0	484	29.0	493	28.5
483.xalancbmk	2	342	40.3	342	40.4	342	40.3	2	334	41.3	334	41.3	341	40.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Platform Notes

BIOS default settings have been used.

General Notes

All binaries were built with 32-bit Intel compiler except:
401.bzip2 and 456.hammer in peak were built with 64-bit Intel compiler by changing the path for include and library files.

For information about Fujitsu Siemens Computers please see:
<http://www.fujitsu-siemens.com/>

Base Compiler Invocation

C benchmarks:

```
icl -Qvc8 -Qc99
```

C++ benchmarks:

```
icl -Qvc8
```



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M460, Intel Core 2 Duo E8400

SPECint_rate2006 = 40.4

CPU2006 license: 22

Test date: Mar-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Mar-2008

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Base Portability Flags

403.gcc: -DSPEC_CPU_WIN32
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
483.xalancbmk: -Qoption,cpp, --no_wchar_t_keyword

Base Optimization Flags

C benchmarks:

-fast -Qvec-guard-write -F512000000

C++ benchmarks:

-fast -Qcxx_features -F512000000 shlw32M.lib -link -FORCE:MULTIPLE

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icl -Qvc8 -Qc99

401.bzip2: C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Bin\\icl.exe
-IC:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Include
-link -LIBPATH:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Lib
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib"
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib\\amd64"

456.hummer: C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Bin\\icl.exe
-IC:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Include
-link -LIBPATH:C:\\DevelTools\\Intel\\Compiler\\C++\\10.1.011\\EM64T\\Lib
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib"
-link -LIBPATH:"C:\\Program Files\\Microsoft Visual Studio 8\\vc\\lib\\amd64"

C++ benchmarks:

icl -Qvc8

Peak Portability Flags

401.bzip2: -DSPEC_CPU_P64

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M460, Intel Core 2 Duo E8400

SPECint_rate2006 = 40.4

CPU2006 license: 22

Test date: Mar-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Mar-2008

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Peak Portability Flags (Continued)

403.gcc: -DSPEC_CPU_WIN32
456.hmmr: -DSPEC_CPU_P64
464.h264ref: -DSPEC_CPU_NO_INTTYPES -DWIN32
483.xalancbmk: -Qoption,cpp, --no_wchar_t_keyword

Peak Optimization Flags

C benchmarks:

400.perlbench: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qprefetch -F512000000 shlw32M.lib -link -FORCE:MULTIPLE

401.bzip2: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qprefetch
-F512000000

403.gcc: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -F512000000

429.mcf: basepeak = yes

445.gobmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -QxT -O2 -Qipo
-Qprec-div- -Qansi-alias -F512000000

456.hmmr: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2
-Qansi-alias -Qopt-multi-version-aggressive -F512000000

458.sjeng: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll4
-F512000000

462.libquantum: basepeak = yes

464.h264ref: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qunroll2
-Qansi-alias -F512000000

C++ benchmarks:

471.omnetpp: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qopt-ra-region-strategy=block -Qcxx_features -F512000000
shlw32M.lib -link -FORCE:MULTIPLE

473.astar: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qopt-ra-region-strategy=routine -Qcxx_features -F512000000
shlw32M.lib -link -FORCE:MULTIPLE

483.xalancbmk: -Qprof_gen(pass 1) -Qprof_use(pass 2) -fast -Qansi-alias
-Qcxx_features -F512000000 shlw32M.lib
-link -FORCE:MULTIPLE



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS M460, Intel Core 2 Duo E8400

SPECint_rate2006 = 40.4

SPECint_rate_base2006 = 36.7

CPU2006 license: 22

Test date: Mar-2008

Test sponsor: Fujitsu Siemens Computers

Hardware Availability: Mar-2008

Tested by: Fujitsu Siemens Computers

Software Availability: Nov-2007

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.02.html

You can also download the XML flags source by saving the following link:

http://www.spec.org/cpu2006/flags/CPU2006_flags.20090713.02.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 17:54:31 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 3 April 2008.