SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL465c G5
(2.3 GHz AMD Opteron 2356)

SPECint®2006 = 14.8

SPECint_base2006 = 13.2

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Mar-2008
Hardware Availability: Mar-2008
Software Availability: May-2008



Hardware

CPU Name:	AMD Opteron 2356
CPU Characteristics:	
CPU MHz:	2300
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	2 MB I+D on chip per chip
Other Cache:	None
Memory:	32 GB (8x4 GB, PC2-5300P CL5)
Disk Subsystem:	1x146 GB 10 K SAS
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
Compiler:	PGI Server Complete Version 7.2
Auto Parallel:	Yes
File System:	ext2
System State:	Run level 3 (multi-user)
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	binutils-2.18.50 SmartHeap 8.1 32-bit Library for Linux

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Hewlett-Packard Company

ProLiant BL465c G5
(2.3 GHz AMD Opteron 2356)

SPECint2006 = 14.8

SPECint_base2006 = 13.2

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company

Test date: Mar-2008
Hardware Availability: Mar-2008
Software Availability: May-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	899	10.9	**898**	**10.9**	897	10.9	704	13.9	708	13.8	**705**	**13.9**
401.bzip2	**972**	**9.93**	957	10.1	975	9.90	**917**	**10.5**	921	10.5	904	10.7
403.gcc	762	10.6	761	10.6	**761**	**10.6**	**735**	**11.0**	736	10.9	735	11.0
429.mcf	1026	8.89	764	11.9	**764**	**11.9**	**631**	**14.4**	634	14.4	631	14.5
445.gobmk	898	11.7	898	11.7	**898**	**11.7**	904	11.6	904	11.6	**904**	**11.6**
456.hmmer	**641**	**14.6**	642	14.5	640	14.6	400	23.3	395	23.6	**395**	**23.6**
458.sjeng	1005	12.0	**1001**	**12.1**	1001	12.1	**913**	**13.3**	914	13.2	910	13.3
462.libquantum	448	46.2	513	40.4	**449**	**46.2**	**402**	**51.5**	402	51.6	403	51.5
464.h264ref	1219	18.2	**1209**	**18.3**	1207	18.3	1219	18.2	**1209**	**18.3**	1207	18.3
471.omnetpp	580	10.8	**581**	**10.7**	582	10.7	580	10.8	**581**	**10.7**	582	10.7
473.astar	**727**	**9.66**	726	9.67	729	9.63	717	9.79	**717**	**9.79**	716	9.80
483.xalancbmk	591	11.7	**591**	**11.7**	591	11.7	**533**	**13.0**	531	13.0	533	12.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
Environment stack size set to 'unlimited'
Max locked memory set to 2097152
PGI_HUGE_PAGES set to 896.
Total number of huge pages available is 7168.
NCPUS set to number of cores
numactl used to bind processes to CPUs
```

Platform Notes

```
BIOS configuration:
  Power Regulator set to Static High Performance Mode
```

Base Compiler Invocation

C benchmarks:
pgcc

C++ benchmarks:
pgcpp

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -Mipa=jobs:8 -Mipa=fast -Mipa=inline -Mfprelaxed -Mloop32
-Mconcur=innermost -Msmartalloc=huge:896 -tp barcelona-64 -Bstatic_pgi

C++ benchmarks:
-fastsse -Mipa=jobs:8 -Mipa=fast -Mipa=inline -Mfprelaxed -Mloop32
-Msmartalloc=huge:896 --zc_eh -tp barcelona -Bstatic_pgi

Base Other Flags

C benchmarks:
-w

C++ benchmarks:
-w

Peak Compiler Invocation

C benchmarks:
pgcc

C++ benchmarks:
pgcpp

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64

Continued on next page

Peak Portability Flags (Continued)

445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:8(pass 2)
-Mipa=inline(pass 2) -fast -O4 -Mfprelaxed
-Msmartalloc=huge:896 -Mnounroll -Mnovect -tp barcelona-64
-Bstatic_pgi

401.bzip2: -Mpfi(pass 1) -Mconcur=innermost(pass 2) -Mpfo(pass 2)
-fast -O4 -Msmartalloc=huge:896 -Mnounroll
-tp barcelona-64 -Bstatic_pgi

403.gcc: -Mpfi(pass 1) -Mpfo(pass 2) -Mconcur(pass 2)
-Mipa=jobs:8(pass 2) -Mipa=fast(pass 2)
-Mipa=inline(pass 2) -fastsse -Mfprelaxed
-Msmartalloc=huge:896 -tp barcelona -Bstatic_pgi

429.mcf: -fastsse -Mconcur -Mipa=jobs:8 -Mipa=fast -Mipa=inline:1
-Msmartalloc=huge:896 -Mloop32 -tp barcelona -Bstatic_pgi

445.gobmk: -Mpfi(pass 1) -Mpfo(pass 2) -Mconcur(pass 2)
-Mipa=jobs:8(pass 2) -Mipa=fast(pass 2) -fast -O4
-Msmartalloc=huge:896 -Mfprelaxed -Mnovect
-tp barcelona-64 -Bstatic_pgi

456.hmmer: -fastsse -Munroll=n:8 -Msmartalloc=huge:896 -Mfprelaxed
-Mvect=partial -Msafeptr -Mipa=jobs:8 -Mipa=const
-Mipa=ptr -Mipa=arg -Mipa=inline -tp barcelona-64
-Bstatic_pgi

458.sjeng: -Mpfi(pass 1) -Mipa=jobs:8(pass 2) -Mipa=fast(pass 2)
-Mipa=inline:1(pass 2) -Mipa=noarg(pass 2) -Mconcur(pass 2)
-Mpfo(pass 2) -fastsse -Msmartalloc=huge:896 -Mfprelaxed
-tp barcelona-64 -Bstatic_pgi

462.libquantum: -fastsse -Mfprelaxed -Msmartalloc -Mvect=nosse
-Munroll=m:8 -Mconcur=innermost -Mconcur=noaltcode
-Mipa=jobs:8 -Mipa=fast -Mipa=noarg -tp barcelona-64
-Bstatic_pgi

Continued on next page

Peak Optimization Flags (Continued)

464.h264ref: `basepeak = yes`

C++ benchmarks:

471.omnetpp: `basepeak = yes`

473.astar: `-Mpfi`(pass 1) `-Mipa=jobs:8`(pass 2) `-Mipa=fast`(pass 2) `-Mipa=inline`(pass 2) `-Mpfo`(pass 2) `-fastsse -O4 -Msmartalloc=huge:896 -Mfprelaxed -Mloop32 --zc_eh -tp barcelona -Bstatic_pgi`

483.xalancbmk: `-fastsse -O4 -Mipa=jobs:8 -Mipa=fast -Mipa=inline -Mfprelaxed -Msmartalloc -Mloop32 --zc_eh -tp barcelona -Bstatic_pgi -L/proj/qa/smartheap/SmartHeap_8.1/lib -lsmartheap`

Peak Other Flags

C benchmarks:
`-w`

C++ benchmarks:
`-w`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/hp-PGI72-PS32-flags.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/hp-PGI72-PS32-flags.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:51:44 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 3 April 2008.