



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEQUEST 540A

SPECfp®_rate2006 = 406
SPECfp_rate_base2006 = 386

CPU2006 license: 19


Test sponsor: Fujitsu Limited

Tested by: Fujitsu Limited

Test date: Mar-2008

Hardware Availability: May-2008

Software Availability: Feb-2008



Hardware

CPU Name: Dual-Core Intel Itanium 9150M
CPU Characteristics: 1.66GHz/24MB, 667MHz FSB
CPU MHz: 1667
FPU: Integrated
CPU(s) enabled: 32 cores, 16 chips, 2 cores/chip
CPU(s) orderable: 2-16 chips
Primary Cache: 16 KB I + 16 KB D on chip per core
Secondary Cache: 1 MB I + 256 KB D on chip per core

Software

Operating System: Red Hat Enterprise Linux 5.1, Kernel 2.6.18-53.el5 on an ia64
Compiler: Intel C++ Compiler for Linux 10.1 (Build 20080112)
Intel Fortran Compiler for Linux 10.1 (Build 20080112)
Auto Parallel: No
File System: ext2

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEQUEST 540A

SPECfp_rate2006 = 406
SPECfp_rate_base2006 = 386

CPU2006 license: 19

Test date: Mar-2008

Test sponsor: Fujitsu Limited

Hardware Availability: May-2008

Tested by: Fujitsu Limited

Software Availability: Feb-2008

L3 Cache: 12 MB I+D on chip per core
Other Cache: None
Memory: 256 GB (128 x 2GB DDR2-667 DIMMs)
Disk Subsystem: 2 x 147GB (SCSI Ultra 320, 10000rpm)
No RAID configuration
Other Hardware: None

System State: Runlevel 1 (single user mode)
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	32	1404	310	1404	310	1396	312	32	1366	318	1366	318	1366	318
416.gamess	32	1968	318	1968	318	1968	318	32	1749	358	1748	358	1749	358
433.milc	32	1378	213	1378	213	1381	213	32	1379	213	1375	214	1378	213
434.zeusmp	32	774	376	782	372	782	373	32	753	387	757	385	778	374
435.gromacs	32	502	455	505	452	506	452	32	477	479	476	480	474	482
436.cactusADM	32	484	789	485	788	485	789	32	486	788	484	790	484	790
437.leslie3d	32	1043	288	1040	289	1041	289	32	1037	290	1037	290	1037	290
444.namd	32	336	763	336	763	336	763	32	291	883	291	882	291	882
447.dealII	32	877	417	877	417	878	417	32	852	430	851	430	852	430
450.soplex	32	1106	241	1104	242	1105	242	32	1057	253	1055	253	1058	252
453.povray	32	557	306	557	306	557	306	32	481	354	480	354	481	354
454.calculix	32	530	498	530	498	530	498	32	512	515	511	516	512	516
459.GemsFDTD	32	1469	231	1459	233	1469	231	32	1461	232	1463	232	1438	236
465.tonto	32	792	398	791	398	792	398	32	721	437	723	436	722	436
470.lbm	32	1195	368	1195	368	1197	367	32	1195	368	1195	368	1197	367
481.wrf	32	831	430	826	433	830	430	32	824	434	824	434	833	429
482.sphinx3	32	896	696	901	692	898	694	32	804	776	814	766	810	770

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

Processes are bound to CPUs using taskset.

limit stacksize unlimited

Memory system is in "Non Mirror Mode".

The following 2 environment variables were set
MALLOC_MMAP_MAX_=0
MALLOC_TRIM_THRESHOLD_=-1

This will cause use of sbrk() calls instead of mmap() calls to get memory from the system.



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEQUEST 540A

SPECfp_rate2006 = 406
SPECfp_rate_base2006 = 386

CPU2006 license: 19

Test sponsor: Fujitsu Limited

Tested by: Fujitsu Limited

Test date: Mar-2008

Hardware Availability: May-2008

Software Availability: Feb-2008

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX -DSPEC_CPU_CASE_FLAG
482.sphinx3: -DSPEC_CPU_LP64
```

Base Optimization Flags

C benchmarks:
-fast -IPF_fp_relaxed -opt-prefetch-next-iteration -ansi-alias

C++ benchmarks:
-fast -IPF_fp_relaxed -opt-prefetch-next-iteration -ansi-alias

Fortran benchmarks:
-fast -IPF-fp-relaxed -opt-prefetch-next-iteration

Benchmarks using both Fortran and C:
-fast -IPF_fp_relaxed -opt-prefetch-next-iteration -ansi-alias
-IPF-fp-relaxed



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEQUEST 540A

SPECfp_rate2006 = 406
SPECfp_rate_base2006 = 386

CPU2006 license: 19

Test date: Mar-2008

Test sponsor: Fujitsu Limited

Hardware Availability: May-2008

Tested by: Fujitsu Limited

Software Availability: Feb-2008

Peak Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Peak Portability Flags

Same as Base Portability Flags

Peak Optimization Flags

C benchmarks:

433.milc: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration
-fno-alias -ansi-alias

470.lbm: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration
-ansi-alias

482.sphinx3: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed
-opt-prefetch-next-iteration -fno-alias
-no-opt-prefetch-initial-values -ansi-alias

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed
-opt-prefetch-next-iteration -no-prefetch -auto-ilp32
-fno-alias -ansi-alias

447.dealII: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration
-inline-factor=150 -no-alias-args -no-opt-loadpair
-ansi-alias

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed
-opt-prefetch-next-iteration -auto-ilp32 -no-alias-args
-ansi-alias

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed
-opt-prefetch-next-iteration -inline-factor=150 -ansi-alias

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEQUEST 540A

SPECfp_rate2006 = 406
SPECfp_rate_base2006 = 386

CPU2006 license: 19

Test sponsor: Fujitsu Limited

Tested by: Fujitsu Limited

Test date: Mar-2008

Hardware Availability: May-2008

Software Availability: Feb-2008

Peak Optimization Flags (Continued)

Fortran benchmarks:

```
410.bwaves: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
           -opt-prefetch-next-iteration  
  
416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
           -opt-prefetch-next-iteration -no-prefetch  
  
434.zeusmp: Same as 410.bwaves  
  
437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
           -opt-prefetch-next-iteration -no-opt-loadpair  
  
459.GemsFDTD: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
  
465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
           -opt-prefetch-next-iteration -inline-factor=150 -no-prefetch
```

Benchmarks using both Fortran and C:

```
435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -IPF-fp-relaxed  
           -opt-prefetch-next-iteration -no-prefetch -fno-alias  
           -ansi-alias  
  
436.cactusADM: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
           -ansi-alias  
  
454.calculix: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
           -inline-factor=150 -no-opt-prefetch-initial-values  
           -ansi-alias  
  
481.wrf: -fast -IPF-fp-relaxed -opt-prefetch-next-iteration  
           -no-opt-loadpair -ansi-alias
```

The flags file that was used to format this result can be browsed at
<http://www.spec.org/cpu2006/flags/Fujitsu.PQ580A.ipf.linux.flags.html>

You can also download the XML flags source by saving the following link:
<http://www.spec.org/cpu2006/flags/Fujitsu.PQ580A.ipf.linux.flags.xml>



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Limited
PRIMEQUEST 540A

SPECfp_rate2006 = 406
SPECfp_rate_base2006 = 386

CPU2006 license: 19

Test date: Mar-2008

Test sponsor: Fujitsu Limited

Hardware Availability: May-2008

Tested by: Fujitsu Limited

Software Availability: Feb-2008

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.1.

Report generated on Tue Jul 22 18:36:35 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 15 April 2008.