SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX (Intel Xeon E5472, 3.00 GHz)

SPECint®2006 = 26.7

SPECint_base2006 = 23.3

CPU2006 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: May-2008
Hardware Availability: Mar-2008
Software Availability: Apr-2008



Hardware

CPU Name:	Intel Xeon E5472
CPU Characteristics:	Quad Core, 3.0 GHz
CPU MHz:	2992
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	12 MB I+D on chip per chip, 6 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (8*2GB PC2-6400 CL5-5-5 FB-DIMMs)
Disk Subsystem:	16 TB RAID 6+1 32 x 500 GB SATA (Seagate Barracuda 7200 rpm)
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1 Kernel 2.6.16.46-0.12-smp
Compiler:	Intel C++ and Fortran Compiler for Linux Version 10.1, Build 20070913
Auto Parallel:	Yes
File System:	NFSv3 IPoIB
System State:	Multi-user, run level 3
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	SGI ProPack 5 for Linux Service Pack 5 Binutils 2.17 SmartHeap library V8.1

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

SGI

SGI Altix ICE 8200EX (Intel Xeon E5472, 3.00 GHz)

SPECint2006 = 26.7

SPECint_base2006 = 23.3

CPU2006 license: 4
Test sponsor: SGI
Tested by: SGI

Test date: May-2008
Hardware Availability: Mar-2008
Software Availability: Apr-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	**502**	**19.5**	500	19.5	504	19.4	**405**	**24.1**	404	24.2	410	23.8
401.bzip2	**598**	**16.1**	594	16.2	603	16.0	**553**	**17.5**	552	17.5	553	17.4
403.gcc	**505**	**15.9**	499	16.1	510	15.8	416	19.4	414	19.4	**414**	**19.4**
429.mcf	**415**	**22.0**	415	22.0	416	21.9	374	24.4	373	24.5	**374**	**24.4**
445.gobmk	546	19.2	536	19.6	**544**	**19.3**	490	21.4	487	21.5	**488**	**21.5**
456.hmmer	593	15.7	**593**	**15.7**	594	15.7	344	27.1	342	27.3	**342**	**27.3**
458.sjeng	**675**	**17.9**	675	17.9	680	17.8	**608**	**19.9**	609	19.9	607	19.9
462.libquantum	85.2	243	93.9	221	**85.2**	**243**	85.4	243	**85.9**	**241**	86.8	239
464.h264ref	711	31.1	709	31.2	**710**	**31.2**	665	33.3	**665**	**33.3**	665	33.3
471.omnetpp	409	15.3	**409**	**15.3**	409	15.3	377	16.6	**378**	**16.6**	378	16.6
473.astar	466	15.1	471	14.9	**470**	**14.9**	425	16.5	425	16.5	**425**	**16.5**
483.xalancbmk	**273**	**25.2**	273	25.2	273	25.2	**273**	**25.2**	273	25.2	273	25.2

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
BIOS settings:
  Snoop Filter:             Enabled
  Hardware Prefetcher:      Enabled
  Adjacent Sector Prefetch: Disabled
All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer,
for peak, are compiled in 64-bit mode
Benchmarks compiled with automatic parallelization use
the following environment settings:
  OMP_NUM_THREADS = 8
  KMP_AFFINITY = physical,0
  KMP_STACKSIZE = 64M
```

Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:
`icpc`

Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`

Continued on next page

Base Portability Flags (Continued)

462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -vec-guard-write -parallel -par-runtime-control

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/include

456.hmmer: /home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/bin/icc
-L/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/lib
-I/home/cmplr/usr3/alrahate/compilers/ic10.1mainline/20070824/Linux64/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -ansi-alias -prefetch`

401.bzip2: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -prefetch -auto-ilp32`

403.gcc: `-fast -inline-calloc -opt-malloc-options=3`

429.mcf: `-fast -prefetch`

445.gobmk: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O2 -ipo -no-prec-div -ansi-alias`

456.hmmer: `-fast -unroll2 -ansi-alias -opt-multi-version-aggressive -auto-ilp32`

458.sjeng: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll4`

462.libquantum: `-fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always -vec-guard-write -opt-malloc-options=3 -parallel -par-runtime-control`

464.h264ref: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-fast -unroll2 -ansi-alias`

C++ benchmarks:

471.omnetpp: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs -L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap`

473.astar: `-prof-gen`(pass 1) `-prof-use`(pass 2) `-xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs -L/home/cmplr/usr3/alrahate/cpu2006.1.0/lib -lsmartheap`

483.xalancbmk: `basepeak = yes`

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.05.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Intel-ic10-ia32-intel64-linux-flags.20090714.05.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 17:36:05 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 11 June 2008.