SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS V840, AMD Opteron 2346 HE (1.8 GHz)

SPECint®2006 = 12.4

SPECint_base2006 = 10.9

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: May-2008



Hardware

CPU Name:	AMD Opteron 2346 HE
CPU Characteristics:	
CPU MHz:	1800
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	2 MB I+D on chip per chip
Other Cache:	None
Memory:	16 GB (8x2GB PC2-5300P, CL5, dual rank ECC)
Disk Subsystem:	1 x 400 GB SATA II, 7200 rpm
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
Compiler:	PGI Workstation Complete Version 7.2-1
Auto Parallel:	Yes
File System:	ext3
System State:	Multi-User SuSE Run Level 3
Base Pointers:	32/64-bit
Peak Pointers:	32/64-bit
Other Software:	binutils 2.18.50 Microquill SmartHeap 8.1 32-bit Library for Linux

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Fujitsu Siemens Computers

CELSIUS V840, AMD Opteron 2346 HE (1.8 GHz)

SPECint2006 = 12.4

SPECint_base2006 = 10.9

CPU2006 license: 22
Test sponsor: Fujitsu Siemens Computers
Tested by: Fujitsu Siemens Computers

Test date: Jun-2008
Hardware Availability: May-2008
Software Availability: May-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	1073	9.11	1056	9.25	**1065**	**9.18**	**856**	**11.4**	858	11.4	855	11.4
401.bzip2	**1222**	**7.89**	1227	7.86	1214	7.95	**1128**	**8.55**	1128	8.56	1129	8.55
403.gcc	**973**	**8.27**	973	8.27	973	8.28	958	8.40	**958**	**8.40**	959	8.40
429.mcf	901	10.1	1133	8.05	**903**	**10.1**	742	12.3	**743**	**12.3**	744	12.3
445.gobmk	1141	9.20	1141	9.19	**1141**	**9.20**	**1012**	**10.4**	1012	10.4	1012	10.4
456.hmmer	784	11.9	**785**	**11.9**	788	11.8	464	20.1	464	20.1	**464**	**20.1**
458.sjeng	1245	9.72	**1244**	**9.72**	1243	9.73	**1147**	**10.5**	1146	10.6	1148	10.5
462.libquantum	**395**	**52.5**	411	50.4	394	52.6	398	52.1	384	53.9	**385**	**53.9**
464.h264ref	1484	14.9	**1491**	**14.8**	1503	14.7	1378	16.1	1389	15.9	**1379**	**16.0**
471.omnetpp	782	7.99	775	8.06	**778**	**8.03**	782	7.99	775	8.06	**778**	**8.03**
473.astar	**920**	**7.63**	919	7.64	921	7.62	**883**	**7.95**	883	7.95	884	7.94
483.xalancbmk	**722**	**9.56**	722	9.56	721	9.57	650	10.6	**650**	**10.6**	649	10.6

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
powersave -f is applied to set CPU to maximum frequency prior to run
stacksize is set to unlimited prior to run
ulimit -l 2457600
PGI_HUGE_PAGES set to 150
(Total number of huge pages available is 1200)
```

General Notes

```
For information about Fujitsu Siemens Computers please see:
http://www.fujitsu-siemens.com
```

Base Compiler Invocation

C benchmarks:
pgcc

C++ benchmarks:
pgcpp

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fastsse -Msmartalloc=huge:896 -Mloop32 -Mconcur=innermost
-Mfprelaxed -Mipa=jobs:4 -Mipa=fast -Mipa=inline -tp barcelona-64
-Bstatic_pgi

C++ benchmarks:
-fastsse -Msmartalloc=huge:896 -Mloop32 -Mfprelaxed --zc_eh
-Mipa=jobs:4 -Mipa=fast -Mipa=inline -tp barcelona -Bstatic_pgi

Peak Compiler Invocation

C benchmarks:
pgcc

C++ benchmarks:
pgcpp

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2) -Mipa=inline(pass 2) -fastsse -O4 -Msmartalloc=huge:896 -Mnovect -Mnounroll -Mfprelaxed -tp barcelona-64 -Bstatic_pgi

401.bzip2: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2) -fastsse -O4 -Msmartalloc=huge:896 -Mprefetch=t0 -Mnounroll -tp barcelona-64 -Bstatic_pgi

403.gcc: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2) -Mipa=fast(pass 2) -Mipa=inline(pass 2) -fastsse -Msmartalloc=huge:896 -Mprefetch=t0 -Mnodalign -Mloop32 -Mfprelaxed -tp barcelona -Bstatic_pgi

429.mcf: -fastsse -Msmartalloc=huge:896 -Mipa=jobs:4 -Mipa=fast -Mipa=inline:1 -tp barcelona -Bstatic_pgi

445.gobmk: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2) -Mipa=fast(pass 2) -fastsse -O4 -Msmartalloc=huge:896 -Mnovect -Mfprelaxed -tp barcelona-64 -Bstatic_pgi

456.hmmer: -fastsse -Mvect=partial -Munroll=n:8 -Msmartalloc=huge:896 -Msafeptr -Mprefetch=t0 -Mfprelaxed -Mipa=jobs:4 -Mipa=const -Mipa=ptr -Mipa=arg -Mipa=inline -tp barcelona-64 -Bstatic_pgi

458.sjeng: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2) -Mipa=fast(pass 2) -Mipa=inline:1(pass 2) -Mipa=noarg(pass 2) -fastsse -Msmartalloc=huge:896 -Mfprelaxed -tp barcelona-64 -Bstatic_pgi

462.libquantum: -fastsse -Munroll=m:8 -Msmartalloc=huge:896 -Mprefetch=distance:8 -Mconcur=innermost -Mconcur=noaltcode -Mfprelaxed -Mipa=jobs:4 -Mipa=fast -Mipa=inline -Mipa=noarg -tp barcelona-64 -Bstatic_pgi

464.h264ref: -Mpfi=indirect(pass 1) -Mpfo=indirect(pass 2) -Mipa=jobs:4(pass 2) -Mipa=fast(pass 2) -Mipa=inline(pass 2) -fastsse -Msmartalloc=huge:896 -Mfprelaxed -tp barcelona-64 -Bstatic_pgi

C++ benchmarks:

471.omnetpp: basepeak = yes

473.astar: -Mpfi(pass 1) -Mpfo(pass 2) -Mipa=jobs:4(pass 2) -Mipa=fast(pass 2) -Mipa=inline:6(pass 2) -fastsse -O4 -Msmartalloc=huge:896 -Msafeptr=global -Mloop32 -Mfprelaxed --zc_eh -tp barcelona -Bstatic_pgi

Continued on next page

Peak Optimization Flags (Continued)

483.xalancbmk: `--zc_eh -fastsse -O4 -Mfprelaxed -Msmartalloc -Mipa=jobs:4 -Mipa=fast -Mipa=inline -tp barcelona -Bstatic_pgi -lsmartheap`

Peak Other Flags

C++ benchmarks:

483.xalancbmk: `-L/opt/SmartHeap_8.1/lib`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/fsc-mix-pgi-path.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/fsc-mix-pgi-path.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 19:53:52 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 July 2008.