# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1
(Intel Xeon E5430, 2.66 GHz)

SPECint®_rate2006 = 120

SPECint_rate_base2006 = 98.2

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Bull SAS

**Test date:** May-2008
**Hardware Availability:** Jan-2008
**Software Availability:** Nov-2007




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5430 |
| CPU Characteristics: | 1333 MHz system bus |
| CPU MHz: | 2666 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 12 MB I+D on chip per chip, 6 MB shared / 2 cores |
| L3 Cache: | None |
| Other Cache: | None |
| Memory: | 24 GB (12x2 GB) FB-DIMM PC2-5300F ECC CL5 |
| Disk Subsystem: | 1x73 GB SAS, 15000 RPM |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | SUSE LINUX Enterprise Server 10 SP1<br>Kernel 2.6.16.46-0.12-smp for x86_64 |
| Compiler: | Intel C++ Compiler 10.1 for Linux<br>Build 20070913 Package ID: l_cc_p_10.1.008 |
| Auto Parallel: | Yes |
| File System: | ext2 |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 32-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | Binutils 2.17.50.0.15<br>SmartHeap library V8.1 |

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R460 E1
(Intel Xeon E5430, 2.66 GHz)

SPECint_rate2006 = 120

SPECint_rate_base2006 = 98.2

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** Bull SAS

**Test date:** May-2008
**Hardware Availability:** Jan-2008
**Software Availability:** Nov-2007

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 8 | **577** | **135** | 575 | 136 | 580 | 135 | 8 | 488 | 160 | **486** | **161** | 484 | 161 |
| 401.bzip2 | 8 | 795 | 97.1 | 793 | 97.3 | **794** | **97.2** | 8 | **755** | **102** | 755 | 102 | 759 | 102 |
| 403.gcc | 8 | 778 | 82.8 | 771 | 83.5 | **775** | **83.0** | 8 | 773 | 83.3 | 779 | 82.7 | **777** | **82.9** |
| 429.mcf | 8 | 915 | 79.7 | **914** | **79.8** | 911 | 80.1 | 8 | **949** | **76.9** | 949 | 76.9 | 947 | 77.0 |
| 445.gobmk | 8 | **624** | **135** | 624 | 135 | 624 | 135 | 8 | 574 | 146 | 572 | 147 | **574** | **146** |
| 456.hmmer | 8 | 667 | 112 | 666 | 112 | **666** | **112** | 8 | 390 | 191 | 391 | 191 | **391** | **191** |
| 458.sjeng | 8 | 778 | 124 | **778** | **124** | 779 | 124 | 8 | 702 | 138 | 700 | 138 | **700** | **138** |
| 462.libquantum | 8 | 3185 | 52.0 | **3256** | **50.9** | 3266 | 50.8 | 1 | **101** | **206** | 101 | 206 | 101 | 205 |
| 464.h264ref | 8 | 792 | 224 | 791 | 224 | **791** | **224** | 8 | 783 | 226 | **761** | **233** | 760 | 233 |
| 471.omnetpp | 8 | 960 | 52.1 | **960** | **52.1** | 962 | 52.0 | 8 | **949** | **52.7** | 949 | 52.7 | 950 | 52.6 |
| 473.astar | 8 | **788** | **71.2** | 788 | 71.2 | 787 | 71.3 | 8 | 730 | 76.9 | **731** | **76.9** | 732 | 76.8 |
| 483.xalancbmk | 8 | 476 | 116 | 477 | 116 | **476** | **116** | 8 | 476 | 116 | 477 | 116 | **476** | **116** |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
'/usr/bin/taskset' used to bind processes to CPUs
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to physical,0
KMP_STACKSIZE set to 64M
```

## General Notes

```
All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer,
for peak, are compiled in 64-bit mode
The Bull NovaScale R440 E1 (Intel Xeon E5430, 2.66 GHz) and
the Bull NovaScale R460 E1 (Intel Xeon E5430, 2.66 GHz) models are electronically equivalent.
The results have been measured on a Bull NovaScale R460 E1 (Intel Xeon E5430, 2.66 GHz) model.
```

## Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

## Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

## Base Optimization Flags

C benchmarks:
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/cpu2006/lib -lsmartheap

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

456.hmmer: /opt/intel/cce/10.1.008/bin/icc
-L/opt/intel/cce/10.1.008/lib
-I/opt/intel/cce/10.1.008/include

C++ benchmarks:
icpc

## Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX

Continued on next page

## Peak Portability Flags (Continued)

483.xalancbmk: -DSPEC_CPU_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo -no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always -vec-guard-write -opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs -L/spec/cpu2006/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs -L/spec/cpu2006/lib -lsmartheap

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

Continued on next page

## Peak Other Flags (Continued)

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/EM64T_Intel101_int_flags.20090713.00.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/EM64T_Intel101_int_flags.20090713.00.xml`


SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.0.
Report generated on Tue Jul 22 20:00:22 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 8 July 2008.