SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun SPARC Enterprise M8000

SPECint®_rate2006 = 637

SPECint_rate_base2006 = 565

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Jun-2008
Hardware Availability: Jul-2008
Software Availability: Jul-2008



Hardware

CPU Name:	SPARC64 VII
CPU Characteristics:	
CPU MHz:	2520
FPU:	Integrated
CPU(s) enabled:	64 cores, 16 chips, 4 cores/chip, 2 threads/core
CPU(s) orderable:	1 to 4 CMUs; each CMU contains 2 or 4 chips
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	6 MB I+D on chip per chip
L3 Cache:	None
Other Cache:	None
Memory:	256 GB (128 x 2 GB)
Disk Subsystem:	805 GB RAID 0 Solaris Volume 12 x Fujitsu 73 GB 10000 RPM SAS Stripe interlace size 512 Kbytes
Other Hardware:	None

Software

Operating System:	Solaris 10 5/08 with Patch 137111-03
Compiler:	Sun Studio 12 with patches 124867-06, 124861-07, 124863-05 (see patch information below)
Auto Parallel:	No
File System:	ufs
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	None

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems
Sun SPARC Enterprise M8000

SPECint_rate2006 = 637

SPECint_rate_base2006 = 565

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Jun-2008
Hardware Availability: Jul-2008
Software Availability: Jul-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	127	1663	746	**1645**	**754**	1641	756	127	1157	1070	**1148**	**1080**	1138	1090
401.bzip2	127	3354	365	3316	370	**3341**	**367**	64	1410	438	1378	448	**1379**	**448**
403.gcc	127	2686	381	**2705**	**378**	2712	377	127	2061	496	2052	498	**2058**	**497**
429.mcf	127	1889	613	1894	612	**1891**	**612**	127	**1883**	**615**	1887	614	1883	615
445.gobmk	127	**1562**	**853**	1571	848	1559	854	127	1343	992	**1360**	**979**	1362	978
456.hmmer	127	1873	633	**1868**	**634**	1868	634	127	1870	634	1866	635	**1869**	**634**
458.sjeng	127	2212	695	**2215**	**694**	2215	694	127	2082	738	**2083**	**738**	2085	737
462.libquantum	127	3802	692	**3801**	**692**	3801	692	127	3804	692	**3807**	**691**	3807	691
464.h264ref	127	2559	1100	**2564**	**1100**	2576	1090	127	**2067**	**1360**	2085	1350	2066	1360
471.omnetpp	127	3983	199	3908	203	**3926**	**202**	127	**3293**	**241**	3273	242	3326	239
473.astar	127	2340	381	**2338**	**381**	2336	382	127	**2351**	**379**	2348	380	2355	379
483.xalancbmk	127	1164	753	1167	751	**1164**	**753**	127	1146	765	**1148**	**763**	1150	762

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Compiler Invocation Notes

```
Sun Studio compiler patches are available at
    http://developers.sun.com/sunstudio/downloads/patches/ss12_patches.jsp
```

Submit Notes

```
Processes were assigned to specific processors using 'pbind' commands.  The
config file option 'submit' was used, along with a list of processors in the
'BIND' variable, to generate the pbind commands.  (For details, please see
the config file.)
```

Operating System Notes

```
System Tunables (/etc/system parameters):

tune_t_fsflushr=10
    Controls how many seconds elapse between runs of the
    page flush daemon, fsflush.
autoup=300
    Causes pages older than the listed number of seconds to
    be written by fsflush.
bufhwm=3000
    Memory byte limit for caching I/O buffers
segmap_percent=3
    Set maximum percent memory for file system cache
```

Continued on next page

Operating System Notes (Continued)

```
lpg_alloc_prefer=1
    Set lgroup page allocation to strongly prefer local pages

Other System Settings:

The webconsole service was turned off using
    svcadm disable webconsole
```

Platform Notes

```
Memory is 8-way interleaved by filling all slots with
the same capacity DIMMs.

This result is measured on a Sun SPARC Enterprise M8000 Server.
Note that the Sun SPARC Enterprise M8000 and Fujitsu SPARC Enterprise
M8000 are electrically equivalent.
```

Base Compiler Invocation

C benchmarks:
`cc`

C++ benchmarks:
`CC`

Base Portability Flags

400.perlbench: `-DSPEC_CPU_SOLARIS_SPARC`
403.gcc: `-DSPEC_CPU_SOLARIS`
462.libquantum: `-DSPEC_CPU_SOLARIS`
483.xalancbmk: `-DSPEC_CPU_SOLARIS`

Base Optimization Flags

C benchmarks:
`-fast -fma=fused -xipo=2 -xpagesize=4M -xprefetch_level=1 -xalias_level=std`

C++ benchmarks:
`-xdepend -library=stlport4 -fast -fma=fused -xipo=2 -xpagesize=4M -xprefetch_level=2 -xalias_level=compatible -lfast`

Base Other Flags

C benchmarks:
`-xjobs=16 -V -#`

C++ benchmarks:
`-xjobs=16 -verbose=diags,version`

Peak Compiler Invocation

C benchmarks:
`cc`

C++ benchmarks:
`CC`

Peak Portability Flags

400.perlbench: `-DSPEC_CPU_SOLARIS_SPARC`
403.gcc: `-DSPEC_CPU_SOLARIS`
462.libquantum: `-DSPEC_CPU_SOLARIS`
483.xalancbmk: `-DSPEC_CPU_SOLARIS`

Peak Optimization Flags

C benchmarks:

400.perlbench: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -fma=fused -xalias_level=std -xipo=2 -xprefetch_level=2 -xrestrict -lfast`

401.bzip2: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -xpagesize=4M -xalias_level=strong -fma=fused`

403.gcc: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -xpagesize=4M -xipo=2 -xalias_level=std -xprefetch=no -fma=fused -ll2amm`

429.mcf: `-fast -xpagesize=4M -xipo=2 -xprefetch=no -xrestrict -xalias_level=std -lfast`

445.gobmk: `-xprofile=collect:./feedback`(pass 1)
`-xprofile=use:./feedback`(pass 2) `-fast -xpagesize=4M -xalias_level=std -xrestrict -fma=fused`

Continued on next page

Peak Optimization Flags (Continued)

456.hmmer: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xipo=2 -fma=fused

458.sjeng: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xipo=2 -fma=fused -xchip=ultra3cu -xpagesize=4m

462.libquantum: -fast -xpagesize=4M -xipo=2 -xprefetch=latx:3 -fma=fused
-xpagesize=64K -lbsdmalloc

464.h264ref: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xipo=2 -xalias_level=std -xprefetch=no -ll2amm

C++ benchmarks:

471.omnetpp: -xdepend -library=stlport4
-xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xpagesize=4M
-xalias_level=compatible -xipo=2 -xprefetch_level=2
-Qoption cg -Qlp-av=0 -fma=fused -lfast

473.astar: -xdepend -library=stlport4 -fast -xpagesize=4M
-xalias_level=compatible -xipo=2 -xprefetch_level=2
-fma=fused -lfast

483.xalancbmk: -xdepend -library=stlport4 -fast -xpagesize=4M
-xalias_level=compatible -xipo=2 -xprefetch=no -fma=fused
-lfast

Peak Other Flags

C benchmarks:
-xjobs=16 -V -#

C++ benchmarks:
-xjobs=16 -verbose=diags,version

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-and-gccfss4.2.20090713.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Sun-Solaris-Studio12-and-gccfss4.2.20090713.xml

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 18:53:44 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 5 August 2008.