



SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint®2006 = 21.6

PowerEdge M600 (Intel Xeon E5410, 2.33 GHz)

SPECint_base2006 = 18.8

CPU2006 license: 55


Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Jan-2008

Tested by: Dell Inc.

Software Availability: May-2008



Hardware

CPU Name: Intel Xeon E5410
 CPU Characteristics: 2333
 CPU MHz: 2333
 FPU: Integrated
 CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
 CPU(s) orderable: 1,2 chips
 Primary Cache: 32 KB I + 32 KB D on chip per core
 Secondary Cache: 12 MB I+D on chip per chip, 6 MB shared / 2 cores
 L3 Cache: None
 Other Cache: None
 Memory: 16 GB (8 x 2 GB 667 MHz ECC CL5 FB-DIMM)
 Disk Subsystem: 1 x 80 GB 5400 RPM SATA
 Other Hardware: None

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16-60.0.21-smp
 Compiler: Intel C++ Compiler 10.1 for Linux Build 20080312 Package ID: l_cc_p_10.1.015
 Auto Parallel: Yes
 File System: ReiserFS
 System State: Run level 3 (multi-user)
 Base Pointers: 32-bit
 Peak Pointers: 32/64-bit
 Other Software: Microquill SmartHeap V8.1 Binutils 2.18.50.0.7.20080502



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint2006 = 21.6

PowerEdge M600 (Intel Xeon E5410, 2.33 GHz)

SPECint_base2006 = 18.8

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Aug-2008
Hardware Availability: Jan-2008
Software Availability: May-2008

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio										
400.perlbench	638	15.3	636	15.4	635	15.4	<u>511</u>	<u>19.1</u>	513	19.1	510	19.2
401.bzip2	<u>758</u>	<u>12.7</u>	759	12.7	757	12.8	697	13.9	697	13.8	<u>697</u>	<u>13.9</u>
403.gcc	644	12.5	613	13.1	642	12.5	486	16.6	486	16.6	487	16.5
429.mcf	468	19.5	468	19.5	468	19.5	<u>434</u>	<u>21.0</u>	435	21.0	434	21.0
445.gobmk	658	15.9	659	15.9	659	15.9	611	17.2	611	17.2	611	17.2
456.hmmer	762	12.2	764	12.2	764	12.2	440	21.2	440	21.2	440	21.2
458.sjeng	857	14.1	853	14.2	854	14.2	767	15.8	769	15.7	768	15.8
462.libquantum	112	185	115	180	122	170	<u>111</u>	186	111	186	112	185
464.h264ref	<u>912</u>	<u>24.3</u>	928	23.8	910	24.3	<u>855</u>	<u>25.9</u>	854	25.9	856	25.8
471.omnetpp	<u>458</u>	<u>13.6</u>	458	13.7	458	13.6	<u>421</u>	<u>14.9</u>	421	14.9	420	14.9
473.astar	586	12.0	584	12.0	586	12.0	<u>532</u>	<u>13.2</u>	532	13.2	533	13.2
483.xalanbmk	333	20.7	333	20.7	334	20.7	<u>333</u>	<u>20.7</u>	333	20.7	334	20.7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

'ulimit -s unlimited' was used to set the stack size to unlimited prior to run

General Notes

All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer, for peak, are compiled in 64-bit mode
OMP_NUM_THREADS set to number of processors
KMP_AFFINITY set to "physical,0"

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalanbmk: -DSPEC_CPU_LINUX



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint2006 = 21.6

PowerEdge M600 (Intel Xeon E5410, 2.33 GHz)

SPECint_base2006 = 18.8

CPU2006 license: 55

Test sponsor: Dell Inc.

Tested by: Dell Inc.

Test date: Aug-2008

Hardware Availability: Jan-2008

Software Availability: May-2008

Base Optimization Flags

C benchmarks:

-fast -vec-guard-write -parallel -par-runtime-control

C++ benchmarks:

-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/cpu2006.1.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):

icc

401.bzip2: /opt/intel/cce/10.1.015/bin/icc
-L/opt/intel/cce/10.1.015/lib
-I/opt/intel/cce/10.1.015/include

456.hmmer: /opt/intel/cce/10.1.015/bin/icc
-L/opt/intel/cce/10.1.015/lib
-I/opt/intel/cce/10.1.015/include

C++ benchmarks:

icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

Continued on next page



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint2006 = 21.6

PowerEdge M600 (Intel Xeon E5410, 2.33 GHz)

SPECint_base2006 = 18.8

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Jan-2008

Tested by: Dell Inc.

Software Availability: May-2008

Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias
-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch
-auto-ilp32

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo
-no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive
-auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch
-opt-streaming-stores always -vec-guard-write
-opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2
-ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=block
-Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmarheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo
-no-prec-div -ansi-alias -opt-ra-region-strategy=routine
-Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmarheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revD.20090713.00.html>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.07.html>



SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

SPECint2006 = 21.6

PowerEdge M600 (Intel Xeon E5410, 2.33 GHz)

SPECint_base2006 = 18.8

CPU2006 license: 55

Test date: Aug-2008

Test sponsor: Dell Inc.

Hardware Availability: Jan-2008

Tested by: Dell Inc.

Software Availability: May-2008

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revD.20090713.00.xml>

<http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.07.xml>

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 19:02:31 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 2 September 2008.