



# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R410 E1  
(Intel Xeon X3320, 2.50 GHz)

**SPECfp®2006 = 20.1**

**SPECfp\_base2006 = 18.6**

CPU2006 license: 20


Test sponsor: Bull SAS

Tested by: Bull SAS

Test date: Jul-2008

Hardware Availability: Jan-2008

Software Availability: Nov-2007



Hardware		Software	
CPU Name:	Intel Xeon X3320	Operating System:	SUSE LINUX Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp
CPU Characteristics:	1333 MHz system bus	Compiler:	Intel C++ and Fortran Compiler 10.1 for Linux Build 20070913 Package ID: l_cc_p_10.1.008, l_fc_p_10.1.008
CPU MHz:	2500	Auto Parallel:	Yes
FPU:	Integrated	File System:	ext2
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip	System State:	Run level 3 (multi-user)
CPU(s) orderable:	1 chip	Base Pointers:	64-bit
Primary Cache:	32 KB I + 32 KB D on chip per core	Continued on next page	
Secondary Cache:	6 MB I+D on chip per chip, 3 MB shared / 2 cores	Continued on next page	

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R410 E1  
(Intel Xeon X3320, 2.50 GHz)

**SPECfp2006 =** 20.1

**SPECfp\_base2006 =** 18.6

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Jul-2008

**Hardware Availability:** Jan-2008

**Software Availability:** Nov-2007

L3 Cache: None  
Other Cache: None  
Memory: 8 GB (4x2 GB) FB-DIMM PC2-6400E ECC CL6  
Disk Subsystem: 1x80 GB SATA, 7200 RPM  
Other Hardware: None

Peak Pointers: 32/64-bit  
Other Software: Binutils 2.17.50.0.15

## Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	417	32.6	<b>417</b>	<b>32.6</b>	417	32.6	418	32.5	419	32.4	<b>419</b>	<b>32.5</b>
416.gamess	1079	18.2	1077	18.2	<b>1078</b>	<b>18.2</b>	<b>1049</b>	<b>18.7</b>	1048	18.7	1050	18.6
433.milc	707	13.0	709	12.9	<b>709</b>	<b>13.0</b>	715	12.8	715	12.8	<b>715</b>	<b>12.8</b>
434.zeusmp	536	17.0	<b>536</b>	<b>17.0</b>	536	17.0	548	16.6	<b>548</b>	<b>16.6</b>	549	16.6
435.gromacs	444	16.1	444	16.1	<b>444</b>	<b>16.1</b>	<b>442</b>	<b>16.2</b>	442	16.2	442	16.2
436.cactusADM	<b>291</b>	<b>41.1</b>	290	41.2	293	40.8	202	59.0	207	57.8	<b>204</b>	<b>58.5</b>
437.leslie3d	534	17.6	538	17.5	<b>536</b>	<b>17.5</b>	534	17.6	538	17.5	<b>536</b>	<b>17.5</b>
444.namd	<b>607</b>	<b>13.2</b>	607	13.2	606	13.2	<b>603</b>	<b>13.3</b>	603	13.3	602	13.3
447.dealII	443	25.8	<b>443</b>	<b>25.8</b>	443	25.8	414	27.6	415	27.6	<b>414</b>	<b>27.6</b>
450.soplex	546	15.3	548	15.2	<b>547</b>	<b>15.2</b>	503	16.6	<b>503</b>	<b>16.6</b>	505	16.5
453.povray	259	20.5	<b>256</b>	<b>20.8</b>	255	20.9	<b>216</b>	<b>24.7</b>	215	24.7	216	24.6
454.calculix	594	13.9	<b>596</b>	<b>13.9</b>	596	13.8	<b>400</b>	<b>20.6</b>	400	20.6	400	20.6
459.GemsFDTD	661	16.0	<b>659</b>	<b>16.1</b>	659	16.1	646	16.4	<b>647</b>	<b>16.4</b>	647	16.4
465.tonto	555	17.7	<b>557</b>	<b>17.7</b>	557	17.7	528	18.7	<b>530</b>	<b>18.6</b>	530	18.6
470.lbm	979	14.0	980	14.0	<b>980</b>	<b>14.0</b>	818	16.8	<b>816</b>	<b>16.8</b>	816	16.8
481.wrf	<b>508</b>	<b>22.0</b>	508	22.0	510	21.9	<b>543</b>	20.6	<b>544</b>	<b>20.5</b>	545	20.5
482.sphinx3	<b>991</b>	<b>19.7</b>	989	19.7	997	19.6	<b>950</b>	<b>20.5</b>	<b>957</b>	<b>20.4</b>	961	20.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run  
OMP\_NUM\_THREADS set to number of cores  
KMP\_AFFINITY set to physical,0  
KMP\_STACKSIZE set to 200M

## General Notes

All benchmarks compiled in 64-bit mode except 450.soplex,  
470.lbm and 482.sphinx3, at peak, are compiled in 32-bit mode  
The Bull NovaScale T810 E1(Intel Xeon X3320, 2.50 GHz),  
the Bull NovaScale T830 E1(Intel Xeon X3320, 2.50 GHz) and  
the Bull NovaScale R410 E1(Intel Xeon X3320, 2.50 GHz) models are electronically equivalent.  
The results have been measured on a Bull NovaScale R410 E1(Intel Xeon X3320, 2.50 GHz) model.



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R410 E1  
(Intel Xeon X3320, 2.50 GHz)

**SPECfp2006 =** 20.1

**SPECfp\_base2006 =** 18.6

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Jul-2008

**Hardware Availability:** Jan-2008

**Software Availability:** Nov-2007

## Base Compiler Invocation

C benchmarks:  
icc

C++ benchmarks:  
icpc

Fortran benchmarks:  
ifort

Benchmarks using both Fortran and C:  
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC\_CPU\_LP64  
416.gamess: -DSPEC\_CPU\_LP64  
433.milc: -DSPEC\_CPU\_LP64  
434.zeusmp: -DSPEC\_CPU\_LP64  
435.gromacs: -DSPEC\_CPU\_LP64 -nofor\_main  
436.cactusADM: -DSPEC\_CPU\_LP64 -nofor\_main  
437.leslie3d: -DSPEC\_CPU\_LP64  
444.namd: -DSPEC\_CPU\_LP64  
447.dealII: -DSPEC\_CPU\_LP64  
450.soplex: -DSPEC\_CPU\_LP64  
453.povray: -DSPEC\_CPU\_LP64  
454.calculix: -DSPEC\_CPU\_LP64 -nofor\_main  
459.GemsFDTD: -DSPEC\_CPU\_LP64  
465.tonto: -DSPEC\_CPU\_LP64  
470.lbm: -DSPEC\_CPU\_LP64  
481.wrf: -DSPEC\_CPU\_LP64 -DSPEC\_CPU\_CASE\_FLAG -DSPEC\_CPU\_LINUX  
482.sphinx3: -DSPEC\_CPU\_LP64

## Base Optimization Flags

C benchmarks:  
-fast -parallel

C++ benchmarks:  
-fast -parallel

Fortran benchmarks:  
-fast -parallel

Benchmarks using both Fortran and C:  
-fast -parallel



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R410 E1  
(Intel Xeon X3320, 2.50 GHz)

**SPECfp2006 =** 20.1

**SPECfp\_base2006 =** 18.6

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Jul-2008

**Hardware Availability:** Jan-2008

**Software Availability:** Nov-2007

## Peak Compiler Invocation

C benchmarks (except as noted below):

```
/opt/intel/cc/10.1.008/bin/icc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

433.milc: icc

C++ benchmarks (except as noted below):

icpc

```
450.soplex: /opt/intel/cc/10.1.008/bin/icpc -L/opt/intel/cc/10.1.008/lib
-I/opt/intel/cc/10.1.008/include
```

Fortran benchmarks:

ifort

Benchmarks using both Fortran and C:

icc ifort

## Peak Portability Flags

```
410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
    433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
    444.namd: -DSPEC_CPU_LP64
    447.dealII: -DSPEC_CPU_LP64
    453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
    465.tonto: -DSPEC_CPU_LP64
    481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

## Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias
    -auto-ilp32
```

```
470.lbm: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12
    -scalar-rep -prefetch -opt-malloc-options=3
```

Continued on next page



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R410 E1  
(Intel Xeon X3320, 2.50 GHz)

**SPECfp2006 =**

**20.1**

**SPECfp\_base2006 =**

**18.6**

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Jul-2008

**Hardware Availability:** Jan-2008

**Software Availability:** Nov-2007

## Peak Optimization Flags (Continued)

482.sphinx3: -fast -unroll12

C++ benchmarks:

444.namd: -prof-gen(pass 1) -prof-use(pass 2) -fast -fno-alias  
-auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12  
-ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -fast  
-opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll14  
-ansi-alias

Fortran benchmarks:

410.bwaves: -fast -prefetch -parallel

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12 -O0  
-ansi-alias -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -fast

437.leslie3d: basepeak = yes

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12 -O0  
-prefetch -parallel

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll14 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch  
-auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll12  
-prefetch -parallel -auto-ilp32

454.calculix: -fast -unroll-aggressive -auto-ilp32

481.wrf: -fast -parallel -prefetch -auto-ilp32

The flags file that was used to format this result can be browsed at

[http://www.spec.org/cpu2006/flags/EM64T\\_Intel101\\_fp\\_flags.20090714.html](http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090714.html)

You can also download the XML flags source by saving the following link:

[http://www.spec.org/cpu2006/flags/EM64T\\_Intel101\\_fp\\_flags.20090714.xml](http://www.spec.org/cpu2006/flags/EM64T_Intel101_fp_flags.20090714.xml)



# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Bull SAS

NovaScale R410 E1  
(Intel Xeon X3320, 2.50 GHz)

**SPECfp2006 =** 20.1

**SPECfp\_base2006 =** 18.6

**CPU2006 license:** 20

**Test sponsor:** Bull SAS

**Tested by:** Bull SAS

**Test date:** Jul-2008

**Hardware Availability:** Jan-2008

**Software Availability:** Nov-2007

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.  
For other inquiries, please contact [webmaster@spec.org](mailto:webmaster@spec.org).

Tested with SPEC CPU2006 v1.0.

Report generated on Tue Jul 22 19:35:08 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 16 September 2008.