SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R900 (Intel Xeon X7350, 2.93 GHz)

SPECint®_rate2006 = 107

SPECint_rate_base2006 = 95.5

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Sep-2008
Hardware Availability: Nov-2007
Software Availability: May-2008



Hardware

CPU Name:	Intel Xeon X7350
CPU Characteristics:	
CPU MHz:	2933
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip
CPU(s) orderable:	2,4 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	8 MB I+D on chip per chip, 4 MB shared / 2 cores
L3 Cache:	None
Other Cache:	None
Memory:	16 GB (16 x 1 GB 667 MHz ECC CL5 FB-DIMM)
Disk Subsystem:	2 x 300 GB 10000 RPM SAS (RAID-0)
Other Hardware:	None

Software

Operating System:	SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16-60.0.21-smp
Compiler:	Intel C++ Compiler 10.1 for Linux Build 20080312 Package ID: l_cc_p_10.1.015
Auto Parallel:	Yes
File System:	ReiserFS
System State:	Run level 3 (multi-user)
Base Pointers:	32-bit
Peak Pointers:	32/64-bit
Other Software:	Microquill SmartHeap V8.1 Binutils 2.18.50.0.7.20080502

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Dell Inc.

PowerEdge R900 (Intel Xeon X7350, 2.93 GHz)

SPECint_rate2006 = 107

SPECint_rate_base2006 = 95.5

CPU2006 license: 55
Test sponsor: Dell Inc.
Tested by: Dell Inc.

Test date: Sep-2008
Hardware Availability: Nov-2007
Software Availability: May-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	8	574	136	**562**	**139**	561	139	8	485	161	**482**	**162**	482	162
401.bzip2	8	954	80.9	964	80.1	**957**	**80.7**	8	910	84.8	**913**	**84.6**	915	84.4
403.gcc	8	747	86.2	762	84.6	**753**	**85.5**	8	762	84.5	**755**	**85.4**	747	86.2
429.mcf	8	1197	60.9	1204	60.6	**1201**	**60.7**	8	1204	60.6	1187	61.4	**1189**	**61.3**
445.gobmk	8	615	137	**615**	**136**	616	136	8	**555**	**151**	561	150	548	153
456.hmmer	8	**633**	**118**	633	118	634	118	8	**404**	**185**	401	186	404	185
458.sjeng	8	738	131	744	130	**742**	**130**	8	**666**	**145**	663	146	666	145
462.libquantum	8	3823	43.4	**3830**	**43.3**	3834	43.2	1	340	61.0	**336**	**61.6**	336	61.6
464.h264ref	8	764	232	762	232	**763**	**232**	8	**727**	**244**	726	244	727	243
471.omnetpp	8	**858**	**58.3**	857	58.3	866	57.7	8	838	59.6	**835**	**59.9**	834	59.9
473.astar	8	789	71.2	**790**	**71.1**	790	71.1	8	745	75.4	741	75.8	**742**	**75.7**
483.xalancbmk	8	488	113	485	114	**486**	**114**	8	488	113	485	114	**486**	**114**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
```

Operating System Notes

```
'ulimit -s unlimited' was used to set the stack size to unlimited prior to run
```

Platform Notes

```
BIOS Settings:
Adjacent Cache Line Prefetch = Disabled (default Enabled)
Hardware Prefetcher = Disabled (default Enabled)
```

General Notes

```
All benchmarks compiled in 32-bit mode except 401.bzip2 and 456.hmmer,
for peak, are compiled in 64-bit mode
taskset was used to bind processes to cores except
for 462.libquantum peak
OMP_NUM_THREADS set to number of processors
KMP_AFFINITY set to "physical,0"
KMP_STACKSIZE set to 64M
```

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Base Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-fast -inline-calloc -opt-malloc-options=3

C++ benchmarks:
-xT -ipo -O3 -no-prec-div -Wl,-z,muldefs
-L/spec/cpu2006.1.1/lib -lsmartheap

Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

Peak Compiler Invocation

C benchmarks (except as noted below):
icc

401.bzip2: /opt/intel/cce/10.1.015/bin/icc
-L/opt/intel/cce/10.1.015/lib
-I/opt/intel/cce/10.1.015/include

456.hmmer: /opt/intel/cce/10.1.015/bin/icc
-L/opt/intel/cce/10.1.015/lib
-I/opt/intel/cce/10.1.015/include

C++ benchmarks:
icpc

Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LINUX
483.xalancbmk: -DSPEC_CPU_LINUX

Peak Optimization Flags

C benchmarks:

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -fast -ansi-alias -prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -fast -prefetch

403.gcc: -fast -inline-calloc -opt-malloc-options=3

429.mcf: -fast -prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xT -O2 -ipo -no-prec-div -ansi-alias

456.hmmer: -fast -unroll2 -ansi-alias -opt-multi-version-aggressive

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll4

462.libquantum: -fast -unroll4 -Ob0 -prefetch -opt-streaming-stores always -vec-guard-write -opt-malloc-options=3 -parallel -par-runtime-control

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -fast -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xT -O3 -ipo -no-prec-div -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revD.html`
`http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.07.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2006/flags/Intel-ic10.1-int-linux64-revD.xml`
`http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.07.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 22:12:43 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 14 October 2008.