# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

## IBM System x3550 (Intel Xeon X5260)

SPECint®2006 = 29.1

SPECint_base2006 = 25.6

**CPU2006 license:** 11
**Test sponsor:** IBM Corporation
**Tested by:** IBM Corporation

**Test date:** Sep-2008
**Hardware Availability:** Nov-2008
**Software Availability:** Nov-2008




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon X5260 |
| CPU Characteristics: | 1333MHz system bus |
| CPU MHz: | 3333 |
| FPU: | Integrated |
| CPU(s) enabled: | 4 cores, 2 chips, 2 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 6 MB I+D on chip per chip |
| L3 Cache: | None |
| Other Cache: | None |
| Memory: | 16 GB (8 x 2 GB DDR2-5300F ECC) |
| Disk Subsystem: | 1 x 36 GB SAS, 15000 RPM |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | SuSE Linux Enterprise Server 10 (x86_64) SP1, Kernel 2.6.16.46-0.12-smp |
| Compiler: | Intel C++ Compiler 11.0 for Linux Build 20080730 Package ID: l_cproc_b_11.0.042 |
| Auto Parallel: | Yes |
| File System: | ReiserFS |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 32-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | Microquill SmartHeap V8.1 Binutils 2.18.50.0.7.20080502 |

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

## IBM System x3550 (Intel Xeon X5260)

SPECint2006 = 29.1

SPECint_base2006 = 25.6

**CPU2006 license:** 11
**Test sponsor:** IBM Corporation
**Tested by:** IBM Corporation

**Test date:** Sep-2008
**Hardware Availability:** Nov-2008
**Software Availability:** Nov-2008

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | 431 | 22.6 | 432 | 22.6 | **432** | **22.6** | 347 | 28.2 | 347 | 28.2 | **347** | **28.2** |
| 401.bzip2 | **522** | **18.5** | 521 | 18.5 | 523 | 18.4 | 486 | 19.9 | 487 | 19.8 | **487** | **19.8** |
| 403.gcc | 485 | 16.6 | **486** | **16.6** | 488 | 16.5 | 376 | 21.4 | 374 | 21.5 | **375** | **21.5** |
| 429.mcf | 312 | 29.3 | 311 | 29.3 | **311** | **29.3** | 312 | 29.2 | **312** | **29.2** | 311 | 29.3 |
| 445.gobmk | 474 | 22.1 | **474** | **22.1** | 475 | 22.1 | **432** | **24.3** | 433 | 24.2 | 432 | 24.3 |
| 456.hmmer | **495** | **18.8** | 495 | 18.8 | 495 | 18.8 | 323 | 28.8 | **323** | **28.9** | 323 | 28.9 |
| 458.sjeng | 545 | 22.2 | **546** | **22.2** | 547 | 22.1 | 521 | 23.2 | 520 | 23.3 | **521** | **23.2** |
| 462.libquantum | 116 | 179 | 115 | 181 | **115** | **180** | 116 | 179 | 115 | 181 | **115** | **180** |
| 464.h264ref | **676** | **32.7** | 677 | 32.7 | 675 | 32.8 | **567** | **39.0** | 568 | 39.0 | 565 | 39.2 |
| 471.omnetpp | 393 | 15.9 | **393** | **15.9** | 395 | 15.8 | 357 | 17.5 | 356 | 17.5 | **356** | **17.5** |
| 473.astar | **430** | **16.3** | 430 | 16.3 | 431 | 16.3 | 370 | 19.0 | **368** | **19.1** | 367 | 19.1 |
| 483.xalancbmk | **252** | **27.4** | 252 | 27.4 | 252 | 27.4 | **252** | **27.4** | 252 | 27.4 | 252 | 27.4 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## General Notes

```
OMP_NUM_THREADS set to number of processors
KMP_AFFINITY set to "physical,0"
Hardware Prefetch Enabled, Adjacent Sector Prefetch Enabled
'ulimit -s unlimited' was used to set the stack size to unlimited prior to run
```

## Base Compiler Invocation

C benchmarks:
`icc`

C++ benchmarks:
`icpc`

## Base Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

## Base Optimization Flags

C benchmarks:
```
-xSSE4.1 -ipo -O3 -no-prec-div -static -parallel
-par-runtime-control -opt-prefetch
```

C++ benchmarks:
```
-xSSE4.1 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/spec/cpu2006.1.1/lib -lsmartheap
```

## Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

## Peak Compiler Invocation

C benchmarks (except as noted below):
```
icc
```

401.bzip2:
```
/opt/intel/Compiler/11.0/042/bin/intel64/icc
-L/opt/intel/Compiler/11.0/042/ipp/em64t/lib
-I/opt/intel/Compiler/11.0/042/ipp/em64t/include
```

456.hmmer:
```
/opt/intel/Compiler/11.0/042/bin/intel64/icc
-L/opt/intel/Compiler/11.0/042/ipp/em64t/lib
-I/opt/intel/Compiler/11.0/042/ipp/em64t/include
```

C++ benchmarks:
```
icpc
```

## Peak Portability Flags

400.perlbench: `-DSPEC_CPU_LINUX_IA32`
401.bzip2: `-DSPEC_CPU_LP64`
456.hmmer: `-DSPEC_CPU_LP64`
462.libquantum: `-DSPEC_CPU_LINUX`
483.xalancbmk: `-DSPEC_CPU_LINUX`

## Peak Optimization Flags

C benchmarks:

Continued on next page

## Peak Optimization Flags (Continued)

400.perlbench: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3 -no-prec-div -static -ansi-alias -opt-prefetch

401.bzip2: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3 -no-prec-div -static -auto-ilp32 -opt-prefetch -ansi-alias

403.gcc: -xSSE4.1 -ipo -O3 -no-prec-div -static -inline-calloc -opt-malloc-options=3

429.mcf: -xSSE4.1 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -O2 -ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2 -ansi-alias -auto-ilp32

458.sjeng: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll4

462.libquantum: basepeak = yes

464.h264ref: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3 -no-prec-div -static -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3 -no-prec-div -ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap

473.astar: -prof-gen(pass 1) -prof-use(pass 2) -xSSE4.1 -ipo -O3 -no-prec-div -ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs -L/spec/cpu2006.1.1/lib -lsmartheap

483.xalancbmk: basepeak = yes

## Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.03.html
http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090713.11.html

You can also download the XML flags sources by saving the following links:

http://www.spec.org/cpu2006/flags/Intel-Linux64-Platform.20090713.03.xml
http://www.spec.org/cpu2006/flags/Intel-ic11.0-int-linux64-revA.20090713.11.xml


SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Tue Jul 22 20:37:10 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 29 October 2008.