



SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7310)

SPECfp®_rate2006 = 47.4

SPECfp_rate_base2006 = 46.1

CPU2006 license: 9006


Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Dec-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008



Hardware

CPU Name: Intel Xeon E7310
CPU Characteristics: 1066 MHz system bus
CPU MHz: 1600
FPU: Integrated
CPU(s) enabled: 8 cores, 2 chips, 4 cores/chip
CPU(s) orderable: 1,2,3,4 chips
Primary Cache: 32 KB I + 32 KB D on chip per core
Secondary Cache: 4 MB I+D on chip per chip, 2 MB shared / 2 cores

Software

Operating System: SUSE Linux Enterprise Server 10 (x86_64) SP2, Kernel 2.6.16.60-0.21-smp
Compiler: Intel C++ and Fortran Compiler 11.0 for Linux Build 20081105 Package ID: l_cproc_p_11.0.074, l_cprof_p_11.0.074
Auto Parallel: Yes
File System: ext2
System State: Run level 3 (multi-user)
Base Pointers: 64-bit

Continued on next page

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7310)

SPECfp_rate2006 = 47.4

SPECfp_rate_base2006 = 46.1

CPU2006 license: 9006

Test date: Dec-2008

Test sponsor: NEC Corporation

Hardware Availability: Nov-2008

Tested by: NEC Corporation

Software Availability: Nov-2008

L3 Cache: None
Other Cache: None
Memory: 32 GB (16x2 GB PC2-5300F, 2 rank, CL5-5-5, ECC)
Disk Subsystem: 1x73.2 GB SAS, 15000 RPM
Other Hardware: None

Peak Pointers: 32/64-bit
Other Software: Binutils 2.18.50.0.7.20080502

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	8	3673	29.6	3647	29.8	3647	29.8	8	3646	29.8	3645	29.8	3642	29.8
416.gamess	8	1718	91.2	1713	91.4	1715	91.3	8	1684	93.0	1686	92.9	1686	92.9
433.milc	8	2323	31.6	2312	31.8	2314	31.7	8	2300	31.9	2299	31.9	2297	32.0
434.zeusmp	8	1407	51.7	1395	52.2	1397	52.1	8	1408	51.7	1403	51.9	1406	51.8
435.gromacs	8	739	77.3	741	77.1	745	76.6	8	740	77.2	738	77.4	739	77.3
436.cactusADM	8	1504	63.6	1534	62.3	1520	62.9	1	173	69.0	172	69.4	172	69.5
437.leslie3d	8	3305	22.8	3390	22.2	3370	22.3	8	3192	23.6	3194	23.5	3160	23.8
444.namd	8	921	69.7	922	69.6	921	69.6	8	927	69.2	927	69.2	927	69.2
447.dealII	8	1329	68.9	1302	70.3	1379	66.4	8	1304	70.2	1337	68.4	1315	69.6
450.soplex	8	2550	26.2	2555	26.1	2550	26.2	8	2317	28.8	2301	29.0	2300	29.0
453.povray	8	418	102	423	101	418	102	8	346	123	345	123	345	123
454.calculix	8	770	85.7	760	86.8	765	86.3	8	761	86.8	763	86.5	762	86.7
459.GemsFDTD	8	3843	22.1	3840	22.1	3843	22.1	8	3863	22.0	3864	22.0	3859	22.0
465.tonto	8	1481	53.2	1495	52.7	1493	52.7	8	1418	55.5	1423	55.3	1419	55.5
470.lbm	8	4946	22.2	5025	21.9	4944	22.2	4	2714	20.3	2715	20.2	2710	20.3
481.wrf	8	2247	39.8	2245	39.8	2247	39.8	8	2247	39.8	2245	39.8	2247	39.8
482.sphinx3	8	4522	34.5	4512	34.6	4506	34.6	8	4322	36.1	4299	36.3	4294	36.3

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.
taskset was used to bind processes to cores except
for 436.cactusADM peak

Operating System Notes

'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to "physical,0"
KMP_STACKSIZE set to 64M



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7310)

SPECfp_rate2006 = 47.4

SPECfp_rate_base2006 = 46.1

CPU2006 license: 9006

Test date: Dec-2008

Test sponsor: NEC Corporation

Hardware Availability: Nov-2008

Tested by: NEC Corporation

Software Availability: Nov-2008

Platform Notes

Bios settings:

Hardware Prefetcher: Disabled
Adjacent Cache Line Prefetch: Disabled
FSB High Bandwidth Optimization: Disabled

General Notes

The NEC Express5800/R140a-4 (Intel Xeon E7310) and
the Bull NovaScale R480 E1 (Intel Xeon E7310, 1.60 GHz) models are electronically equivalent.
The results have been measured on a NEC Express5800/R140a-4 (Intel Xeon E7310) model.

Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7310)

SPECfp_rate2006 = 47.4

SPECfp_rate_base2006 = 46.1

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Dec-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Base Optimization Flags

C benchmarks:

```
-xSSSE3 -ipo -O3 -no-prec-div -static -opt-prefetch
```

C++ benchmarks:

```
-xSSSE3 -ipo -O3 -no-prec-div -static -opt-prefetch
```

Fortran benchmarks:

```
-xSSSE3 -ipo -O3 -no-prec-div -static -opt-prefetch
```

Benchmarks using both Fortran and C:

```
-xSSSE3 -ipo -O3 -no-prec-div -static -opt-prefetch
```

Peak Compiler Invocation

C benchmarks (except as noted below):

```
icc
```

```
482.sphinx3: /opt/intel/Compiler/11.0/074/bin/ia32/icc  
          -L/opt/intel/Compiler/11.0/074/ipp/ia32/lib  
          -I/opt/intel/Compiler/11.0/074/ipp/ia32/include
```

C++ benchmarks (except as noted below):

```
icpc
```

```
450.soplex: /opt/intel/Compiler/11.0/074/bin/ia32/icpc  
          -L/opt/intel/Compiler/11.0/074/ipp/ia32/lib  
          -I/opt/intel/Compiler/11.0/074/ipp/ia32/include
```

Fortran benchmarks (except as noted below):

```
ifort
```

```
437.leslie3d: /opt/intel/Compiler/11.0/074/bin/ia32/ifort  
          -L/opt/intel/Compiler/11.0/074/ipp/ia32/lib  
          -I/opt/intel/Compiler/11.0/074/ipp/ia32/include
```

Benchmarks using both Fortran and C:

```
icc ifort
```

Peak Portability Flags

410.bwaves: -DSPEC_CPU_LP64

416.gamess: -DSPEC_CPU_LP64

433.milc: -DSPEC_CPU_LP64

434.zeusmp: -DSPEC_CPU_LP64

435.gromacs: -DSPEC_CPU_LP64 -nofor_main

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7310)

SPECfp_rate2006 = 47.4

SPECfp_rate_base2006 = 46.1

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Dec-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Peak Portability Flags (Continued)

```
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
 444.namd: -DSPEC_CPU_LP64
 447.dealII: -DSPEC_CPU_LP64
 453.povray: -DSPEC_CPU_LP64
 454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
 465.tonto: -DSPEC_CPU_LP64
 470.lbm: -DSPEC_CPU_LP64
 481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
```

Peak Optimization Flags

C benchmarks:

```
433.milc: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
           -no-prec-div -static -fno-alias

470.lbm: -xSSSE3 -ipo -O3 -no-prec-div -static -opt-prefetch
          -auto-ilp32

482.sphinx3: -xSSSE3 -ipo -O3 -no-prec-div -static -unroll12
```

C++ benchmarks:

```
444.namd: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
           -no-prec-div -static -fno-alias -auto-ilp32

447.dealII: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
            -no-prec-div -static -unroll12 -ansi-alias -scalar-rep-

450.soplex: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
            -no-prec-div -static -opt-malloc-options=3

453.povray: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
            -no-prec-div -static -unroll14 -ansi-alias
```

Fortran benchmarks:

```
410.bwaves: -xSSSE3 -ipo -O3 -no-prec-div -static -opt-prefetch

416.gamess: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
            -no-prec-div -static -unroll12 -Ob0 -ansi-alias
            -scalar-rep-

434.zeusmp: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
            -no-prec-div -static
```

Continued on next page



SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

NEC Corporation

Express5800/R140a-4
(Intel Xeon E7310)

SPECfp_rate2006 = 47.4

SPECfp_rate_base2006 = 46.1

CPU2006 license: 9006

Test sponsor: NEC Corporation

Tested by: NEC Corporation

Test date: Dec-2008

Hardware Availability: Nov-2008

Software Availability: Nov-2008

Peak Optimization Flags (Continued)

437.leslie3d: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
-no-prec-div -static -opt-malloc-options=3 -opt-prefetch

459.GemsFDTD: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
-no-prec-div -static -unroll2 -Ob0 -opt-prefetch

465.tonto: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
-no-prec-div -static -unroll4 -auto

Benchmarks using both Fortran and C:

435.gromacs: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
-no-prec-div -static -opt-prefetch -auto-ilp32

436.cactusADM: -prof-gen(pass 1) -prof-use(pass 2) -xSSSE3 -ipo -O3
-no-prec-div -static -unroll2 -opt-prefetch -parallel
-auto-ilp32

454.calculix: -xSSSE3 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: basepeak = yes

The flags files that were used to format this result can be browsed at

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revE.20090710.html>
<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.html>

You can also download the XML flags sources by saving the following links:

<http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revE.20090710.xml>
<http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revB.xml>

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.

Report generated on Tue Jul 22 22:27:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.

Originally published on 20 January 2009.