SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems

Sun Blade X6275 (Intel Xeon X5570 2.93GHz)

SPECint®2006 = 36.7

SPECint_base2006 = 29.7

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Apr-2009
Hardware Availability: Apr-2009
Software Availability: Jun-2009



Hardware

CPU Name:	Intel Xeon X5570
CPU Characteristics:	Intel Turbo Boost Technology up to 3.33 GHz
CPU MHz:	2933
FPU:	Integrated
CPU(s) enabled:	8 cores, 2 chips, 4 cores/chip, 2 threads/core
CPU(s) orderable:	1 or 2 chips
Primary Cache:	32 KB I + 32 KB D on chip per core
Secondary Cache:	256 KB I+D on chip per core
L3 Cache:	8 MB I+D on chip per chip
Other Cache:	None
Memory:	24 GB (6 x 4 GB DDR3-1333)
Disk Subsystem:	1 x 24 GB, SAS, Sun FlashDisk
Other Hardware:	None

Software

Operating System:	OpenSolaris 2008.11
Compiler:	Sun Studio 12 Update 1 (backend build 20090309)
Auto Parallel:	Yes
File System:	zfs with gzip compression
System State:	Default
Base Pointers:	64-bit
Peak Pointers:	32/64-bit
Other Software:	MicroQuill SmartHeap Library 9.01 for x64

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems

Sun Blade X6275 (Intel Xeon X5570 2.93GHz)

SPECint2006 = 36.7

SPECint_base2006 = 29.7

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Apr-2009
Hardware Availability: Apr-2009
Software Availability: Jun-2009

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	412	23.7	**411**	**23.8**	411	23.8	326	30.0	325	30.0	**325**	**30.0**
401.bzip2	520	18.6	**520**	**18.6**	519	18.6	474	20.4	474	20.4	**474**	**20.4**
403.gcc	339	23.8	339	23.7	**339**	**23.8**	294	27.4	**294**	**27.4**	294	27.4
429.mcf	**231**	**39.4**	231	39.5	231	39.4	167	54.6	**167**	**54.5**	167	54.5
445.gobmk	493	21.3	**493**	**21.3**	493	21.3	**426**	**24.6**	427	24.6	426	24.6
456.hmmer	357	26.2	357	26.2	**357**	**26.2**	**347**	**26.9**	347	26.9	347	26.9
458.sjeng	**521**	**23.2**	521	23.2	521	23.2	484	25.0	**484**	**25.0**	484	25.0
462.libquantum	129	161	128	161	**129**	**161**	**39.3**	**527**	38.7	536	39.3	527
464.h264ref	630	35.1	**630**	**35.1**	630	35.1	574	38.6	573	38.6	**573**	**38.6**
471.omnetpp	279	22.4	279	22.4	**279**	**22.4**	246	25.4	**246**	**25.4**	245	25.5
473.astar	372	18.9	**373**	**18.8**	373	18.8	**355**	**19.8**	355	19.8	355	19.8
483.xalancbmk	**189**	**36.5**	189	36.4	189	36.6	**177**	**38.9**	177	38.9	177	38.9

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Operating System Notes

```
ulimit -s 131072  (shell): increases stack
/etc/system parameters
   tune_t_fsflushr=10
   autoup=900
   set lpg_alloc_prefer=1
   set zfs:zfs_arc_max = 0x10000000
```

Platform Notes

```
  Default BIOS settings used except:
  Hyper-Threading Technology set to Enabled,
  Intel VT-d: Disabled.  VT-d, if enabled, supports
  remapping of I/O DMA transfers for virtualization.
```

General Notes

```
Environment variables set by runspec before the start of the run:
OMP_NUM_THREADS = "8"
SUNW_MP_PROCBIND = "true"
SUNW_MP_THR_IDLE = "SPIN"
```

Base Compiler Invocation

C benchmarks:

```
/data1/20090309_ceres_x86/bin/cc
```

Continued on next page

Base Compiler Invocation (Continued)

C++ benchmarks:
/data1/20090309_ceres_x86/bin/CC

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS

Base Optimization Flags

C benchmarks:
-fast -xipo=2 -m64 -xprefetch

C++ benchmarks:
-fast -xipo=2 -m64 -xpagesize=2M -xvector=simd -xprefetch=no%auto
-L/data1/SmartHeap_9/lib -R/data1/SmartHeap_9/lib -lsmartheap64
-library=stlport4

Base Other Flags

C benchmarks:
-V -# -xjobs=16

C++ benchmarks:
-verbose=diags,version -xjobs=16

Peak Compiler Invocation

C benchmarks:
/data1/20090309_ceres_x86/bin/cc

Continued on next page

Peak Compiler Invocation (Continued)

C++ benchmarks:
/data1/20090309_ceres_x86/bin/CC

Peak Portability Flags

400.perlbench: -DSPEC_CPU_SOLARIS_IA32
403.gcc: -DSPEC_CPU_LP64 -DSPEC_CPU_SOLARIS
462.libquantum: -DSPEC_CPU_SOLARIS
483.xalancbmk: -DSPEC_CPU_SOLARIS

Peak Optimization Flags

C benchmarks:

400.perlbench: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xpagesize=2M -xvector=simd -xalias_level=std
-xprefetch=no%auto -lbsdmalloc -lumem

401.bzip2: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xalias_level=strong -xprefetch=no%auto
-lumem

403.gcc: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xpagesize=2M -xalias_level=std -m64 -xprefetch=no%auto

429.mcf: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xalias_level=strict -xprefetch=no%auto -lbsdmalloc

445.gobmk: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -m64 -xpagesize=2M
-xrestrict -xalias_level=strong -xdepend -xautopar -lmvec

456.hmmer: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64

458.sjeng: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xvector=simd -xrestrict -xalias_level=std
-xprefetch=no%auto

462.libquantum: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xautopar -xreduction

Continued on next page

Peak Optimization Flags (Continued)

464.h264ref: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xalias_level=std -xautopar

C++ benchmarks:

471.omnetpp: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2
-xpagesize=2M
-L/data1/SmartHeap_9/lib -R/data1/SmartHeap_9/lib -lsmartheap
-library=stlport4

473.astar: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M
-L/data1/SmartHeap_9/lib -R/data1/SmartHeap_9/lib -lsmartheap_mt64
-xalias_level=compatible -library=stlport4 -xautopar

483.xalancbmk: -xprofile=collect:./feedback(pass 1)
-xprofile=use:./feedback(pass 2) -fast -xipo=2 -m64
-xpagesize=2M -xunroll=12
-L/data1/SmartHeap_9/lib -R/data1/SmartHeap_9/lib -lsmartheap64
-library=stlport4

Peak Other Flags

C benchmarks:
-V -# -xjobs=16

C++ benchmarks:
-verbose=diags,version -xjobs=16

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Sun-OpenSolaris-Studio-x86_64.20090710.00.html

You can also download the XML flags source by saving the following link:
http://www.spec.org/cpu2006/flags/Sun-OpenSolaris-Studio-x86_64.20090710.00.xml

Copyright 2006-2014 Standard Performance Evaluation Corporation

Sun Microsystems

Sun Blade X6275 (Intel Xeon X5570 2.93GHz)

SPECint2006 = 36.7

SPECint_base2006 = 29.7

CPU2006 license: 6
Test sponsor: Sun Microsystems
Tested by: Sun Microsystems

Test date: Apr-2009
Hardware Availability: Apr-2009
Software Availability: Jun-2009

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 02:05:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 28 April 2009.