SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom II X4 805)

SPECfp®2006 = 15.8

SPECfp_base2006 = 15.6

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2009
Hardware Availability: Feb-2009
Software Availability: Nov-2008



Hardware

CPU Name:	AMD Phenom II X4 805
CPU Characteristics:	
CPU MHz:	2500
FPU:	Integrated
CPU(s) enabled:	4 cores, 1 chip, 4 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core

Continued on next page

Software

Operating System:	Windows Vista Ultimate w/ SP1 (64-bit)
Compiler:	Intel C++ Compiler Professional 11.0 for IA32 Build 20080930 Package ID: w_cproc_p_11.0.054 Intel Visual Fortran Compiler Professional 11.0 for IA32 Build 20080930 Package ID: w_cprof_p_11.0.054 Microsoft Visual Studio 2008 (for libraries)
Auto Parallel:	Yes
File System:	NTFS

Continued on next page

SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom II X4 805)

SPECfp2006 = 15.8

SPECfp_base2006 = 15.6

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2009
Hardware Availability: Feb-2009
Software Availability: Nov-2008

L3 Cache: 4 MB I+D on chip per chip
Other Cache: None
Memory: 4 GB (4x1GB DDR2-800 CL5)
Disk Subsystem: Seagate 320 GB SATA, 7200RPM
Other Hardware: None

System State: Default
Base Pointers: 32-bit
Peak Pointers: 32-bit
Other Software: SmartHeap Library Version 8.1 from http://www.microquill.com/

Results Table

Benchmark	Base						Peak					
	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
410.bwaves	362	37.6	360	37.8	**361**	**37.7**	361	37.7	359	37.9	**359**	**37.8**
416.gamess	**1319**	**14.8**	1317	14.9	1319	14.8	**1280**	**15.3**	1281	15.3	1280	15.3
433.milc	854	10.7	855	10.7	**854**	**10.7**	848	10.8	855	10.7	**855**	**10.7**
434.zeusmp	**524**	**17.4**	527	17.3	524	17.4	**524**	**17.4**	527	17.3	524	17.4
435.gromacs	540	13.2	541	13.2	**540**	**13.2**	533	13.4	**532**	**13.4**	532	13.4
436.cactusADM	286	41.7	287	41.6	**287**	**41.7**	**283**	**42.3**	282	42.3	283	42.2
437.leslie3d	**747**	**12.6**	747	12.6	745	12.6	**747**	**12.6**	747	12.6	745	12.6
444.namd	646	12.4	**646**	**12.4**	646	12.4	**641**	**12.5**	641	12.5	641	12.5
447.dealII	841	13.6	824	13.9	**828**	**13.8**	**714**	**16.0**	709	16.1	715	16.0
450.soplex	**747**	**11.2**	747	11.2	746	11.2	**742**	**11.2**	743	11.2	741	11.3
453.povray	**275**	**19.3**	275	19.4	275	19.3	235	22.6	235	22.6	**235**	**22.6**
454.calculix	**1424**	**5.80**	1424	5.80	1424	5.80	1823	4.50	**1823**	**4.50**	1822	4.50
459.GemsFDTD	664	16.0	664	16.0	**664**	**16.0**	**652**	**16.3**	652	16.3	652	16.3
465.tonto	1090	9.00	1092	9.00	**1090**	**9.00**	**1011**	**9.70**	1011	9.70	1011	9.70
470.lbm	**602**	**22.8**	602	22.8	602	22.8	**602**	**22.8**	602	22.8	602	22.8
481.wrf	534	20.9	532	21.0	**533**	**21.0**	**533**	**21.0**	533	21.0	532	21.0
482.sphinx3	1081	18.0	**1091**	**17.9**	1107	17.6	1086	17.9	1078	18.1	**1086**	**18.0**

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

General Notes

```
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
Binaries were built on Windows Vista Ultimate (32-bit)
OMP_NUM_THREADS set to number of logical processors as seen by the OS
KMP_AFFINITY set to physical,0
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qc99
```

C++ benchmarks:

```
icl -Qvc9
```

Continued on next page

Base Compiler Invocation (Continued)

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icl -Qvc9 -Qc99 ifort

Base Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Base Optimization Flags

C benchmarks:
/arch:SSE2 -Qipo -O3 -Qprec-div- -Qparallel -Qopt-prefetch
/F1000000000

C++ benchmarks:
/arch:SSE2 -Qipo -O3 -Qprec-div- -Qparallel -Qopt-prefetch
-Qcxx-features /F1000000000 shlw32m.lib
-link /FORCE:MULTIPLE

Fortran benchmarks:
/arch:SSE2 -Qipo -O3 -Qprec-div- -Qparallel -Qopt-prefetch
/F1000000000

Benchmarks using both Fortran and C:
/arch:SSE2 -Qipo -O3 -Qprec-div- -Qparallel -Qopt-prefetch
/F1000000000

Peak Compiler Invocation

C benchmarks:
icl -Qvc9 -Qc99

C++ benchmarks:
icl -Qvc9

Fortran benchmarks:
ifort

Continued on next page

Peak Compiler Invocation (Continued)

Benchmarks using both Fortran and C:
icl -Qvc9 -Qc99 ifort

Peak Portability Flags

436.cactusADM: -Qlowercase /assume:underscore
444.namd: -TP
447.dealII: -DDEAL_II_MEMBER_VAR_SPECIALIZATION_BUG
453.povray: -DSPEC_CPU_WINDOWS_ICL
454.calculix: -DSPEC_CPU_NOZMODIFIER -Qlowercase
481.wrf: -DSPEC_CPU_WINDOWS_ICL

Peak Optimization Flags

C benchmarks:

433.milc: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa /F1000000000

470.lbm: basepeak = yes

482.sphinx3: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qunroll2 /F1000000000

C++ benchmarks:

444.namd: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Oa /F1000000000 shlw32m.lib
-link /FORCE:MULTIPLE

447.dealII: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll2 -Qopt-prefetch
-Qansi-alias -Qscalar-rep- /F1000000000 shlw32m.lib
-link /FORCE:MULTIPLE

450.soplex: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- /F1000000000 shlw32m.lib
-link /FORCE:MULTIPLE

453.povray: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2)
-Qipo -O3 -Qprec-div- -Qunroll4 -Qansi-alias /F1000000000
shlw32m.lib -link /FORCE:MULTIPLE

Fortran benchmarks:

410.bwaves: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch
-Qparallel /F1000000000

Continued on next page

Peak Optimization Flags (Continued)

416.gamess: `/arch:SSE2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qansi-alias -Qscalar-rep- /F1000000000`

434.zeusmp: `basepeak = yes`

437.leslie3d: `basepeak = yes`

459.GemsFDTD: `/arch:SSE2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qunroll2 -Ob0 -Qopt-prefetch -Qparallel /F1000000000`

465.tonto: `/arch:SSE2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qunroll4 -Qauto /F1000000000`

Benchmarks using both Fortran and C:

435.gromacs: `/arch:SSE2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qopt-prefetch /F1000000000`

436.cactusADM: `/arch:SSE2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qunroll2 -Qopt-prefetch -Qparallel /F1000000000`

454.calculix: `/arch:SSE2 -Qipo -O3 -Qprec-div- /F1000000000`

481.wrf: `/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel /F1000000000`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.xml`

SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 01:10:18 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 June 2009.