SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.

(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom II X3 720)

SPECint®_rate2006 = 41.2

SPECint_rate_base2006 = 39.7

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2009
Hardware Availability: Feb-2009
Software Availability: Nov-2008



Hardware

CPU Name:	AMD Phenom II X3 720
CPU Characteristics:	
CPU MHz:	2800
FPU:	Integrated
CPU(s) enabled:	3 cores, 1 chip, 3 cores/chip
CPU(s) orderable:	1 chip
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	6 MB I+D on chip per chip
Other Cache:	None
Memory:	4 GB (4x1GB DDR2-800 CL5)
Disk Subsystem:	Seagate 320 GB SATA, 7200RPM
Other Hardware:	None

Software

Operating System:	Windows Vista Ultimate w/ SP1 (64-bit)
Compiler:	Intel C++ Compiler Professional 11.0 for IA32 Build 20080930 Package ID: w_cproc_p_11.0.054 Microsoft Visual Studio 2008 (for libraries)
Auto Parallel:	Yes
File System:	NTFS
System State:	Default
Base Pointers:	32-bit
Peak Pointers:	32-bit
Other Software:	SmartHeap Library Version 8.1 from http://www.microquill.com/

SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

GIGA-BYTE Technology Co. Ltd.
(Test Sponsor: Intel Corporation)

Gigabyte MA78GM-S2H Motherboard (AMD Phenom II X3 720)

SPECint_rate2006 = 41.2

SPECint_rate_base2006 = 39.7

CPU2006 license: 13
Test sponsor: Intel Corporation
Tested by: Intel Corporation

Test date: May-2009
Hardware Availability: Feb-2009
Software Availability: Nov-2008

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	3	615	47.7	**614**	**47.7**	612	48.0	3	**485**	**60.6**	484	60.6	486	60.3
401.bzip2	3	837	34.5	836	34.5	**837**	**34.5**	3	832	34.8	833	34.8	**832**	**34.8**
403.gcc	3	620	39.0	627	38.4	**627**	**38.4**	3	**601**	**40.2**	599	40.2	604	39.9
429.mcf	3	**928**	**29.4**	930	29.4	924	29.7	3	**927**	**29.4**	925	29.7	930	29.4
445.gobmk	3	574	54.9	575	54.9	**574**	**54.9**	3	536	58.8	**536**	**58.8**	536	58.8
456.hmmer	3	1688	16.5	**1686**	**16.5**	1686	16.5	3	**1683**	**16.5**	1689	16.5	1677	16.8
458.sjeng	3	824	44.1	**823**	**44.1**	823	44.1	3	**760**	**47.7**	760	47.7	759	47.7
462.libquantum	3	914	68.1	913	68.1	**914**	**68.1**	1	386	53.7	**386**	**53.7**	386	53.7
464.h264ref	3	902	73.5	**903**	**73.5**	903	73.5	3	831	79.8	**831**	**79.8**	830	80.1
471.omnetpp	3	625	30.0	**624**	**30.0**	623	30.0	3	**571**	**33.0**	571	33.0	571	33.0
473.astar	3	**663**	**31.8**	661	31.8	664	31.8	3	633	33.3	631	33.3	**632**	**33.3**
483.xalancbmk	3	481	42.9	**477**	**43.5**	476	43.5	3	481	42.9	**477**	**43.5**	476	43.5

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
Tested systems can be used with Shin-G ATX case, Antec NeoPower 480W power supply
Binaries were built on Windows Vista Ultimate (32-bit)
OMP_NUM_THREADS set to number of logical processors as seen by the OS
KMP_AFFINITY set to physical,0
submit disabled for 462.libquantum peak
```

Base Compiler Invocation

C benchmarks:

```
icl -Qvc9 -Qc99
```

C++ benchmarks:

```
icl -Qvc9
```

Base Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`

Continued on next page

Base Portability Flags (Continued)

483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Base Optimization Flags

C benchmarks:
`/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000`

C++ benchmarks:
`/arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qcxx-features /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

Base Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

Peak Compiler Invocation

C benchmarks:
`icl -Qvc9 -Qc99`

C++ benchmarks:
`icl -Qvc9`

Peak Portability Flags

403.gcc: `-DSPEC_CPU_WIN32`
464.h264ref: `-DSPEC_CPU_NO_INTTYPES -DWIN32`
483.xalancbmk: `-Qoption,cpp,--no_wchar_t_keyword`

Peak Optimization Flags

C benchmarks:

400.perlbench: `/arch:SSE2`(pass 2) `-Qprof_gen`(pass 1) `-Qprof_use`(pass 2) `-Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-prefetch /F512000000 shlw32m.lib -link /FORCE:MULTIPLE`

Continued on next page

Peak Optimization Flags (Continued)

401.bzip2: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qansi-alias /F512000000

403.gcc: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

429.mcf: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch /F512000000

445.gobmk: /arch:SSE2 -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O2 -Qprec-div- -Qansi-alias /F512000000

456.hmmer: /arch:SSE2 -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll2 -Qansi-alias /F512000000

458.sjeng: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qunroll4 /F512000000

462.libquantum: /arch:SSE2 -Qipo -O3 -Qprec-div- -Qopt-prefetch -Qparallel -Qpar-runtime-control -Qvec-guard-write /F512000000

464.h264ref: Same as 456.hmmer

C++ benchmarks:

471.omnetpp: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=block /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

473.astar: /arch:SSE2(pass 2) -Qprof_gen(pass 1) -Qprof_use(pass 2) -Qipo -O3 -Qprec-div- -Qansi-alias -Qopt-ra-region-strategy=routine /F512000000 shlw32m.lib -link /FORCE:MULTIPLE

483.xalancbmk: basepeak = yes

Peak Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic11.0-win32-revA.xml`

SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 01:21:36 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 23 June 2009.