# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440 E2
(Intel Xeon E5504, 2.00 GHz)

**SPECfp®_rate2006 = 59.5**

**SPECfp_rate_base2006 = 57.5**

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** NEC Corporation

**Test date:** Apr-2009
**Hardware Availability:** Apr-2009
**Software Availability:** Feb-2009




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E5504 |
| CPU Characteristics: | |
| CPU MHz: | 2000 |
| FPU: | Integrated |
| CPU(s) enabled: | 4 cores, 1 chip, 4 cores/chip |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |

Continued on next page

### Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 10 (x86_64) SP2 with patch Linux kernel 20090119, Kernel 2.6.16.60-0.34-smp |
| Compiler: | Intel C++ and Fortran Compiler Professional 11.0 for Linux<br>Build 20090131 Package ID: l_cproc_p_11.0.081, l_cprof_p_11.0.081 |
| Auto Parallel: | No |
| File System: | ReiserFS |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Bull SAS

NovaScale R440 E2
(Intel Xeon E5504, 2.00 GHz)

SPECfp_rate2006 = 59.5

SPECfp_rate_base2006 = 57.5

**CPU2006 license:** 20
**Test sponsor:** Bull SAS
**Tested by:** NEC Corporation

**Test date:** Apr-2009
**Hardware Availability:** Apr-2009
**Software Availability:** Feb-2009

L3 Cache: 4 MB I+D on chip per chip
Other Cache: None
Memory: 24 GB (6 X 4 GB PC3-8500R running at 800 MHz)
Disk Subsystem: 1x146.5 GB SAS, 15000 RPM
Other Hardware: None

System State: Run level 3 (multi-user)
Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: Binutils 2.18.50.0.7.20080502

## Results Table

| Benchmark | Base | | | | | | | Peak | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Copies | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 4 | 812 | 66.9 | **812** | **67.0** | 811 | 67.0 | 4 | 812 | 66.9 | **812** | **67.0** | 811 | 67.0 |
| 416.gamess | 4 | 1204 | 65.0 | 1205 | 65.0 | **1204** | **65.0** | 4 | **1191** | **65.7** | 1191 | 65.8 | 1192 | 65.7 |
| 433.milc | 4 | 675 | 54.4 | 676 | 54.3 | **675** | **54.4** | 4 | 675 | 54.4 | 676 | 54.3 | **675** | **54.4** |
| 434.zeusmp | 4 | **596** | **61.0** | 597 | 61.0 | 595 | 61.1 | 4 | **586** | **62.1** | 585 | 62.2 | 587 | 62.0 |
| 435.gromacs | 4 | 504 | 56.7 | 506 | 56.5 | **504** | **56.6** | 4 | **499** | **57.2** | 497 | 57.5 | 502 | 56.9 |
| 436.cactusADM | 4 | 705 | 67.8 | **707** | **67.6** | 709 | 67.4 | 4 | 705 | 67.8 | **707** | **67.6** | 709 | 67.4 |
| 437.leslie3d | 4 | 843 | 44.6 | **845** | **44.5** | 845 | 44.5 | 4 | 843 | 44.6 | **845** | **44.5** | 845 | 44.5 |
| 444.namd | 4 | 686 | 46.7 | 685 | 46.9 | **685** | **46.8** | 4 | 678 | 47.3 | **678** | **47.3** | 683 | 47.0 |
| 447.dealII | 4 | 618 | 74.0 | 607 | 75.3 | **610** | **75.0** | 4 | **559** | **81.8** | 563 | 81.2 | 553 | 82.8 |
| 450.soplex | 4 | 730 | 45.7 | **730** | **45.7** | 730 | 45.7 | 4 | 689 | 48.4 | 689 | 48.4 | **689** | **48.4** |
| 453.povray | 4 | 297 | 71.6 | **298** | **71.5** | 300 | 71.0 | 4 | 235 | 90.7 | 236 | 90.2 | **235** | **90.6** |
| 454.calculix | 4 | **474** | **69.6** | 474 | 69.6 | 473 | 69.7 | 4 | **473** | **69.8** | 474 | 69.6 | 472 | 69.9 |
| 459.GemsFDTD | 4 | **1077** | **39.4** | 1078 | 39.4 | 1077 | 39.4 | 4 | **1038** | **40.9** | 1038 | 40.9 | 1039 | 40.9 |
| 465.tonto | 4 | 676 | 58.2 | **677** | **58.1** | 678 | 58.1 | 4 | 636 | 61.9 | **637** | **61.7** | 643 | 61.2 |
| 470.lbm | 4 | 1340 | 41.0 | **1339** | **41.1** | 1339 | 41.1 | 4 | 1299 | 42.3 | 1298 | 42.3 | **1298** | **42.3** |
| 481.wrf | 4 | 603 | 74.1 | 602 | 74.2 | **603** | **74.1** | 4 | 603 | 74.1 | 602 | 74.2 | **603** | **74.1** |
| 482.sphinx3 | 4 | 1305 | 59.7 | **1305** | **59.7** | 1304 | 59.8 | 4 | **1269** | **61.4** | 1268 | 61.5 | 1270 | 61.4 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Submit Notes

```
The config file option 'submit' was used.
 numactl was used to bind copies to the cores
```

## Operating System Notes

```
'ulimit -s unlimited' was used to set the stacksize to unlimited prior to run
```

## Platform Notes

```
Default BIOS settings were used.
```

## General Notes

```
The NEC Express5800/R120a-1(Intel Xeon E5504),
the NEC Express5800/R120a-2(Intel Xeon E5504),
the Bull NovaScale R440 E2 (Intel Xeon E5504, 2.00 GHz) and
the Bull NovaScale R460 E2 (Intel Xeon E5504, 2.00 GHz) models are electronically equivalent.
The results have been measured on a NEC Express5800/R120a-2(Intel Xeon E5504) model.
```

## Base Compiler Invocation

C benchmarks:
icc

C++ benchmarks:
icpc

Fortran benchmarks:
ifort

Benchmarks using both Fortran and C:
icc ifort

## Base Portability Flags

410.bwaves: -DSPEC_CPU_LP64
416.gamess: -DSPEC_CPU_LP64
433.milc: -DSPEC_CPU_LP64
434.zeusmp: -DSPEC_CPU_LP64
435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
437.leslie3d: -DSPEC_CPU_LP64
444.namd: -DSPEC_CPU_LP64
447.dealII: -DSPEC_CPU_LP64
450.soplex: -DSPEC_CPU_LP64
453.povray: -DSPEC_CPU_LP64
454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
465.tonto: -DSPEC_CPU_LP64
470.lbm: -DSPEC_CPU_LP64
481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
482.sphinx3: -DSPEC_CPU_LP64

## Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static

Continued on next page

## Base Optimization Flags (Continued)

C++ benchmarks:
`-xSSE4.2 -ipo -O3 -no-prec-div -static`

Fortran benchmarks:
`-xSSE4.2 -ipo -O3 -no-prec-div -static`

Benchmarks using both Fortran and C:
`-xSSE4.2 -ipo -O3 -no-prec-div -static`

## Peak Compiler Invocation

C benchmarks (except as noted below):
`icc`

482.sphinx3: `icc -m32`

C++ benchmarks (except as noted below):
`icpc`

450.soplex: `icpc -m32`

Fortran benchmarks:
`ifort`

Benchmarks using both Fortran and C:
`icc ifort`

## Peak Portability Flags

410.bwaves: `-DSPEC_CPU_LP64`
416.gamess: `-DSPEC_CPU_LP64`
433.milc: `-DSPEC_CPU_LP64`
434.zeusmp: `-DSPEC_CPU_LP64`
435.gromacs: `-DSPEC_CPU_LP64 -nofor_main`
436.cactusADM: `-DSPEC_CPU_LP64 -nofor_main`
437.leslie3d: `-DSPEC_CPU_LP64`
444.namd: `-DSPEC_CPU_LP64`
447.dealII: `-DSPEC_CPU_LP64`
453.povray: `-DSPEC_CPU_LP64`
454.calculix: `-DSPEC_CPU_LP64 -nofor_main`
459.GemsFDTD: `-DSPEC_CPU_LP64`
465.tonto: `-DSPEC_CPU_LP64`
470.lbm: `-DSPEC_CPU_LP64`
481.wrf: `-DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX`

# Peak Optimization Flags

C benchmarks:

433.milc: basepeak = yes

470.lbm: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -auto-ilp32

482.sphinx3: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2

C++ benchmarks:

444.namd: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -fno-alias -auto-ilp32

447.dealII: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -ansi-alias -scalar-rep-

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -opt-malloc-options=3

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: basepeak = yes

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2)

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -Ob0 -opt-prefetch

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll4 -auto

Benchmarks using both Fortran and C:

Continued on next page

# Peak Optimization Flags (Continued)

435.gromacs: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-static`(pass 2) `-prof-use`(pass 2) `-opt-prefetch -auto-ilp32`

436.cactusADM: `basepeak = yes`

454.calculix: `-xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32`

481.wrf: `basepeak = yes`

The flags files that were used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revG.html`
`http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revE.html`

You can also download the XML flags sources by saving the following links:
`http://www.spec.org/cpu2006/flags/Intel-ic11.0-fp-linux64-revG.xml`
`http://www.spec.org/cpu2006/flags/NEC-Intel-Linux-Settings-flags-revE.xml`


SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 02:28:50 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 7 July 2009.