# SPEC® CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Motherboard X8DTL-6 (Intel Xeon X5650, 2.66GHz)

SPECfp®2006 = 42.5

SPECfp_base2006 = 39.8

**CPU2006 license:** 001176
**Test sponsor:** Supermicro
**Tested by:** Supermicro

**Test date:** Apr-2010
**Hardware Availability:** Mar-2010
**Software Availability:** Jan-2010




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon X5650 |
| CPU Characteristics: | Intel Turbo Boost Technology up to 3.06 GHz |
| CPU MHz: | 2666 |
| FPU: | Integrated |
| CPU(s) enabled: | 12 cores, 2 chips, 6 cores/chip, 2 threads/core |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |

Continued on next page

### Software

| | |
|---|---|
| Operating System: | SUSE Linux Enterprise Server 11 (x86_64) Kernel 2.6.27.19-5-default |
| Compiler: | Intel C++ and Fortran Professional Compiler for IA32 and Intel 64, Version 11.1 Build 20091130 Package ID: l_cproc_p_11.1.064, l_cprof_p_11.1.064 |
| Auto Parallel: | Yes |
| File System: | ReiserFS |
| System State: | Run level 3 (multi-user) |

Continued on next page

# SPEC CFP2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## Supermicro

Motherboard X8DTL-6 (Intel Xeon X5650, 2.66GHz)

SPECfp2006 = 42.5

SPECfp_base2006 = 39.8

**CPU2006 license:** 001176
**Test sponsor:** Supermicro
**Tested by:** Supermicro

**Test date:** Apr-2010
**Hardware Availability:** Mar-2010
**Software Availability:** Jan-2010

L3 Cache: 12 MB I+D on chip per chip
Other Cache: None
Memory: 24 GB (6 x 4 GB DDR3-1333 RDIMM, ECC, CL9)
Disk Subsystem: 1 x 320 GB SATA II, 7200 RPM
Other Hardware: None

Base Pointers: 64-bit
Peak Pointers: 32/64-bit
Other Software: None

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 410.bwaves | 79.3 | 171 | 82.1 | 166 | **81.5** | **167** | 77.9 | 175 | 79.7 | 171 | **78.9** | **172** |
| 416.gamess | 896 | 21.9 | 892 | 22.0 | **892** | **22.0** | 796 | 24.6 | **797** | **24.6** | 798 | 24.5 |
| 433.milc | **196** | **46.8** | 196 | 46.7 | 196 | 46.8 | 193 | 47.6 | 194 | 47.3 | **194** | **47.3** |
| 434.zeusmp | **261** | **34.9** | 262 | 34.8 | 260 | 35.0 | **261** | **34.9** | 262 | 34.8 | 260 | 35.0 |
| 435.gromacs | **332** | **21.5** | 332 | 21.5 | 333 | 21.4 | **328** | **21.8** | 330 | 21.7 | 328 | 21.8 |
| 436.cactusADM | **49.8** | **240** | 49.6 | 241 | 49.8 | 240 | 48.6 | 246 | **48.6** | **246** | 48.4 | 247 |
| 437.leslie3d | **301** | **31.3** | 301 | 31.3 | 302 | 31.2 | **301** | **31.3** | 301 | 31.3 | 302 | 31.2 |
| 444.namd | **443** | **18.1** | 444 | 18.1 | 442 | 18.1 | **445** | **18.0** | 444 | 18.0 | 445 | 18.0 |
| 447.dealII | **323** | **35.4** | 323 | 35.4 | 323 | 35.4 | 316 | 36.2 | **316** | **36.2** | 317 | 36.0 |
| 450.soplex | 280 | 29.8 | 275 | 30.3 | **276** | **30.2** | 272 | 30.7 | 273 | 30.6 | **273** | **30.6** |
| 453.povray | 196 | 27.1 | 197 | 27.0 | **196** | **27.1** | 152 | 35.0 | 153 | 34.7 | **153** | **34.7** |
| 454.calculix | 310 | 26.6 | 313 | 26.4 | **311** | **26.5** | **297** | **27.8** | 299 | 27.6 | 297 | 27.8 |
| 459.GemsFDTD | **222** | **47.8** | 222 | 47.7 | 208 | 51.1 | 156 | 67.9 | 156 | 67.8 | **156** | **67.9** |
| 465.tonto | 429 | 23.0 | **429** | **22.9** | 429 | 22.9 | 323 | 30.5 | **323** | **30.5** | 323 | 30.4 |
| 470.lbm | 219 | 62.7 | **218** | **62.9** | 218 | 63.1 | 217 | 63.4 | 216 | 63.5 | **217** | **63.4** |
| 481.wrf | 275 | 40.7 | **275** | **40.6** | 276 | 40.5 | 248 | 45.1 | **248** | **45.0** | 249 | 44.9 |
| 482.sphinx3 | **471** | **41.3** | 469 | 41.5 | 477 | 40.8 | **541** | **36.0** | 541 | 36.0 | 542 | 36.0 |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Operating System Notes

```
'ulimit -s unlimited' was set for stacksize unlimited
KMP_AFFINITY set to granularity=fine,scatter
KMP_STACKSIZE set to 200M
```

## Platform Notes

```
Fan speed set to Full Speed in BIOS Setup.
As tested, the system used a Supermicro
PWS-665-PQ power supply, 2 SNK-P0017 heatsinks,
and 1 SAN Ave92 9G0912G101
2 Nidec UltraFlo T92T12MMA7-57 cooling fans.
```

## General Notes

```
Binaries were compiled on SLES 10 with Binutils 2.18.50.0.7.20080502
```

## Base Compiler Invocation

C benchmarks:
```
icc   -m64
```

C++ benchmarks:
```
icpc  -m64
```

Fortran benchmarks:
```
ifort -m64
```

Benchmarks using both Fortran and C:
```
icc   -m64 ifort -m64
```

## Base Portability Flags

```
    410.bwaves: -DSPEC_CPU_LP64
    416.gamess: -DSPEC_CPU_LP64
      433.milc: -DSPEC_CPU_LP64
    434.zeusmp: -DSPEC_CPU_LP64
    435.gromacs: -DSPEC_CPU_LP64 -nofor_main
436.cactusADM: -DSPEC_CPU_LP64 -nofor_main
    437.leslie3d: -DSPEC_CPU_LP64
      444.namd: -DSPEC_CPU_LP64
     447.dealII: -DSPEC_CPU_LP64
     450.soplex: -DSPEC_CPU_LP64
     453.povray: -DSPEC_CPU_LP64
    454.calculix: -DSPEC_CPU_LP64 -nofor_main
459.GemsFDTD: -DSPEC_CPU_LP64
      465.tonto: -DSPEC_CPU_LP64
        470.lbm: -DSPEC_CPU_LP64
        481.wrf: -DSPEC_CPU_LP64 -DSPEC_CPU_CASE_FLAG -DSPEC_CPU_LINUX
    482.sphinx3: -DSPEC_CPU_LP64
```

## Base Optimization Flags

C benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
```

C++ benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
```

Fortran benchmarks:
```
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch
```

Continued on next page

## Base Optimization Flags (Continued)

Benchmarks using both Fortran and C:
`-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch`

## Peak Compiler Invocation

C benchmarks:
`icc -m64`

C++ benchmarks:
`icpc -m64`

Fortran benchmarks:
`ifort -m64`

Benchmarks using both Fortran and C:
`icc -m64 ifort -m64`

## Peak Portability Flags

`Same as Base Portability Flags`

## Peak Optimization Flags

C benchmarks:

433.milc: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-static`(pass 2) `-prof-use`(pass 2) `-ansi-alias`

470.lbm: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-static`(pass 2) `-prof-use`(pass 2) `-parallel -ansi-alias -auto-ilp32`

482.sphinx3: `-xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32 -unroll2`

C++ benchmarks:

444.namd: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-static`(pass 2) `-prof-use`(pass 2) `-fno-alias -auto-ilp32`

447.dealII: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-static`(pass 2) `-prof-use`(pass 2) `-unroll2 -ansi-alias -scalar-rep- -auto-ilp32`

Continued on next page

## Peak Optimization Flags (Continued)

450.soplex: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -opt-malloc-options=3 -auto-ilp32

453.povray: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll4 -ansi-alias

Fortran benchmarks:

410.bwaves: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch -parallel

416.gamess: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -Ob0 -ansi-alias -scalar-rep-

434.zeusmp: basepeak = yes

437.leslie3d: basepeak = yes

459.GemsFDTD: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -Ob0 -opt-prefetch -parallel

465.tonto: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -inline-calloc -opt-malloc-options=3 -auto -unroll4

Benchmarks using both Fortran and C:

435.gromacs: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -opt-prefetch -auto-ilp32

436.cactusADM: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2) -O3(pass 2) -no-prec-div(pass 2) -static(pass 2) -prof-use(pass 2) -unroll2 -opt-prefetch -parallel -auto-ilp32

454.calculix: -xSSE4.2 -ipo -O3 -no-prec-div -static -auto-ilp32

481.wrf: Same as 454.calculix

The flags file that was used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100316.html

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100316.xml`


SPEC and SPECfp are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 06:52:37 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 11 May 2010.