# SPEC® CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

## IBM BladeCenter HX5 (Intel Xeon E7520)

SPECint®2006 = 22.4

SPECint_base2006 = 20.5

**CPU2006 license:** 11
**Test sponsor:** IBM Corporation
**Tested by:** IBM Corporation

**Test date:** May-2010
**Hardware Availability:** Jun-2010
**Software Availability:** Jan-2010




### Hardware

| | |
|---|---|
| CPU Name: | Intel Xeon E7520 |
| CPU Characteristics: | |
| CPU MHz: | 1867 |
| FPU: | Integrated |
| CPU(s) enabled: | 8 cores, 2 chips, 4 cores/chip, 2 threads/core |
| CPU(s) orderable: | 1,2 chips |
| Primary Cache: | 32 KB I + 32 KB D on chip per core |
| Secondary Cache: | 256 KB I+D on chip per core |
| L3 Cache: | 18 MB I+D on chip per chip |
| Other Cache: | None |
| Memory: | 128 GB (16 x 8 GB PC3-8500R CL7, Quad Rank, running at 800 MHz) |
| Disk Subsystem: | 2 x 50 GB SATA, SSD |
| Other Hardware: | None |

### Software

| | |
|---|---|
| Operating System: | SuSE Linux Enterprise Server 11 (x86_64), Kernel 2.6.27.19-5-default |
| Compiler: | Intel C++ Professional Compiler for IA32 and Intel 64, Version 11.1<br>Build 20091130 Package ID: l_cproc_p_11.1.064 |
| Auto Parallel: | Yes |
| File System: | ext3 |
| System State: | Run level 3 (multi-user) |
| Base Pointers: | 32-bit |
| Peak Pointers: | 32/64-bit |
| Other Software: | Microquill SmartHeap V8.1 |

# SPEC CINT2006 Result

Copyright 2006-2014 Standard Performance Evaluation Corporation

## IBM Corporation

## IBM BladeCenter HX5 (Intel Xeon E7520)

SPECint2006 = 22.4

SPECint_base2006 = 20.5

**CPU2006 license:** 11
**Test sponsor:** IBM Corporation
**Tested by:** IBM Corporation

**Test date:** May-2010
**Hardware Availability:** Jun-2010
**Software Availability:** Jan-2010

## Results Table

| Benchmark | Base | | | | | | Peak | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio | Seconds | Ratio |
| 400.perlbench | **671** | **14.6** | 674 | 14.5 | 667 | 14.6 | 578 | 16.9 | **578** | **16.9** | 578 | 16.9 |
| 401.bzip2 | **871** | **11.1** | 870 | 11.1 | 874 | 11.0 | 867 | 11.1 | **868** | **11.1** | 869 | 11.1 |
| 403.gcc | 628 | 12.8 | 630 | 12.8 | **629** | **12.8** | 534 | 15.1 | 533 | 15.1 | **533** | **15.1** |
| 429.mcf | 394 | 23.1 | **381** | **23.9** | 381 | 24.0 | **332** | **27.4** | 331 | 27.5 | 333 | 27.4 |
| 445.gobmk | 754 | 13.9 | **753** | **13.9** | 751 | 14.0 | **705** | **14.9** | 706 | 14.9 | 705 | 14.9 |
| 456.hmmer | 353 | 26.4 | **353** | **26.4** | 353 | 26.4 | 343 | 27.2 | 343 | 27.2 | **343** | **27.2** |
| 458.sjeng | **855** | **14.2** | 851 | 14.2 | 855 | 14.2 | **815** | **14.9** | 814 | 14.9 | 816 | 14.8 |
| 462.libquantum | 61.9 | 335 | 63.3 | 328 | **62.7** | **331** | 61.9 | 335 | 63.3 | 328 | **62.7** | **331** |
| 464.h264ref | 1027 | 21.6 | 1030 | 21.5 | **1027** | **21.5** | 972 | 22.8 | 971 | 22.8 | **971** | **22.8** |
| 471.omnetpp | **497** | **12.6** | 497 | 12.6 | 496 | 12.6 | **348** | **18.0** | 349 | 17.9 | 348 | 18.0 |
| 473.astar | 603 | 11.6 | **602** | **11.7** | 601 | 11.7 | 577 | 12.2 | **577** | **12.2** | 577 | 12.2 |
| 483.xalancbmk | 328 | 21.0 | 331 | 20.8 | **329** | **21.0** | 339 | 20.3 | 342 | 20.2 | **341** | **20.3** |

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

## Platform Notes

```
Demand Scrub disabled
```

## General Notes

```
'ulimit -s unlimited' was used to set the stack size to unlimited prior to run
OMP_NUM_THREADS set to number of cores
KMP_AFFINITY set to granularity=fine,scatter
Binaries were compiled on SLES 10 with Binutils 2.18.50.0.7.20080502
```

## Base Compiler Invocation

C benchmarks:

```
icc  -m64
```

C++ benchmarks:

```
icpc -m64
```

## Base Portability Flags

400.perlbench: `-DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64`
401.bzip2: `-DSPEC_CPU_LP64`
403.gcc: `-DSPEC_CPU_LP64`

Continued on next page

## Base Portability Flags (Continued)

429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
471.omnetpp: -DSPEC_CPU_LP64
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX

## Base Optimization Flags

C benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -static -parallel -opt-prefetch

C++ benchmarks:
-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-64bit -lsmartheap64

## Base Other Flags

C benchmarks:

403.gcc: -Dalloca=_alloca

## Peak Compiler Invocation

C benchmarks (except as noted below):
icc -m64

400.perlbench: icc -m32

429.mcf: icc -m32

445.gobmk: icc -m32

464.h264ref: icc -m32

C++ benchmarks (except as noted below):
icpc -m32

473.astar: icpc -m64

## Peak Portability Flags

400.perlbench: -DSPEC_CPU_LINUX_IA32
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
473.astar: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

## Peak Optimization Flags

C benchmarks:

400.perlbench: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -ansi-alias -opt-prefetch

401.bzip2: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div -static(pass 2) -prof-use(pass 2)
-auto-ilp32 -opt-prefetch -ansi-alias

403.gcc: -xSSE4.2 -ipo -O3 -no-prec-div -static -inline-calloc
-opt-malloc-options=3 -auto-ilp32

429.mcf: -xSSE4.2 -ipo -O3 -no-prec-div -static -opt-prefetch

445.gobmk: -xSSE4.2(pass 2) -prof-gen(pass 1) -prof-use(pass 2) -O2
-ipo -no-prec-div -ansi-alias

456.hmmer: -xSSE4.2 -ipo -O3 -no-prec-div -static -unroll2
-ansi-alias -auto-ilp32

458.sjeng: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -unroll4

462.libquantum: basepeak = yes

464.h264ref: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -static(pass 2)
-prof-use(pass 2) -unroll2 -ansi-alias

C++ benchmarks:

471.omnetpp: -xSSE4.2(pass 2) -prof-gen(pass 1) -ipo(pass 2)
-O3(pass 2) -no-prec-div(pass 2) -prof-use(pass 2)
-ansi-alias -opt-ra-region-strategy=block -Wl,-z,muldefs
-L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-32bit -lsmartheap

Continued on next page

## Peak Optimization Flags (Continued)

473.astar: `-xSSE4.2`(pass 2) `-prof-gen`(pass 1) `-ipo`(pass 2) `-O3`(pass 2) `-no-prec-div`(pass 2) `-prof-use`(pass 2) `-ansi-alias -opt-ra-region-strategy=routine -Wl,-z,muldefs -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-64bit -lsmartheap64`

483.xalancbmk: `-xSSE4.2 -ipo -O3 -no-prec-div -opt-prefetch -Wl,-z,muldefs -L/home/cmplr/usr3/alrahate/cpu2006.1.1.ic11.1/libic11.1-32bit -lsmartheap`

## Peak Other Flags

C benchmarks:

403.gcc: `-Dalloca=_alloca`

The flags file that was used to format this result can be browsed at
`http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100603.html`

You can also download the XML flags source by saving the following link:
`http://www.spec.org/cpu2006/flags/Intel-ic11.1-linux64-revE.20100603.xml`


SPEC and SPECint are registered trademarks of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.


For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 08:36:48 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 18 June 2010.