SPEC® CINT2006 Result

Hewlett-Packard Company

ProLiant BL465c G7
(2.3 GHz AMD Opteron 6134)

SPECint®_rate2006 = Not Run

SPECint_rate_base2006 = 246

CPU2006 license:	3	**Test date:**	Sep-2010
Test sponsor:	Hewlett-Packard Company	**Hardware Availability:**	Jun-2010
Tested by:	Hewlett-Packard Company	**Software Availability:**	Mar-2010



Hardware

CPU Name:	AMD Opteron 6134
CPU Characteristics:	
CPU MHz:	2300
FPU:	Integrated
CPU(s) enabled:	16 cores, 2 chips, 8 cores/chip
CPU(s) orderable:	1,2 chips
Primary Cache:	64 KB I + 64 KB D on chip per core
Secondary Cache:	512 KB I+D on chip per core
L3 Cache:	12 MB I+D on chip per chip, 6 MB shared / 4 cores
Other Cache:	None
Memory:	64 GB (16 x 4 GB 2Rx4 PC3-10600R-9, ECC)
Disk Subsystem:	1x146 GB 10 K SAS
Other Hardware:	None

Software

Operating System:	Red Hat Enterprise Linux Server release 5.5, Advanced Platform, Kernel 2.6.18-194.el5
Compiler:	x86 Open64 4.2.4 Compiler Suite
Auto Parallel:	No
File System:	ext3
System State:	Run level 3 (multi-user)
Base Pointers:	32/64-bit
Peak Pointers:	Not Applicable
Other Software:	binutils 2.18 SmartHeap 8.1 32-bit Library for Linux

SPEC CINT2006 Result

Hewlett-Packard Company

ProLiant BL465c G7
(2.3 GHz AMD Opteron 6134)

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 246

CPU2006 license: 3
Test sponsor: Hewlett-Packard Company
Tested by: Hewlett-Packard Company
Test date: Sep-2010
Hardware Availability: Jun-2010
Software Availability: Mar-2010

Results Table

	Base							Peak						
Benchmark	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
400.perlbench	16	662	236	665	235	**664**	**236**							
401.bzip2	16	**906**	**170**	907	170	904	171							
403.gcc	16	**659**	**196**	658	196	660	195							
429.mcf	16	777	188	**773**	**189**	773	189							
445.gobmk	16	739	227	740	227	**740**	**227**							
456.hmmer	16	**422**	**354**	423	353	421	355							
458.sjeng	16	887	218	885	219	**886**	**218**							
462.libquantum	16	382	869	383	866	**382**	**867**							
464.h264ref	16	1143	310	1139	311	**1142**	**310**							
471.omnetpp	16	**609**	**164**	609	164	609	164							
473.astar	16	731	154	728	154	**730**	**154**							
483.xalancbmk	16	394	280	396	279	**396**	**279**							

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
'numactl' was used to bind copies to the cores.
See the configuration file for details.
```

Operating System Notes

```
'ulimit -s unlimited' was used to set environment stack size
'ulimit -l 2097152'  was used to set environment locked pages in memory limit

Set vm/nr_hugepages=14336 in /etc/sysctl.conf
mount -t hugetlbfs nodev /mnt/hugepages
```

Platform Notes

```
BIOS Configuration:
  HP Power Profile set to Maximum Performance
  Thermal Configuration set to Increased Cooling
```

General Notes

```
Environment variables set by runspec before the start of the run:
HUGETLB_LIMIT = "450"
LD_LIBRARY_PATH = "/cpu2006/amd1002mc-rate-libs-revC/64:/cpu2006/amd1002mc-rate-libs-revC/32"

The x86 Open64 Compiler Suite is only available from (and supported by) AMD at
http://developer.amd.com/cpu/open64
```

Hewlett-Packard Company

ProLiant BL465c G7
(2.3 GHz AMD Opteron 6134)

SPECint_rate2006 = Not Run

SPECint_rate_base2006 = 246

CPU2006 license: 3		**Test date:**	Sep-2010
Test sponsor:	Hewlett-Packard Company	**Hardware Availability:**	Jun-2010
Tested by:	Hewlett-Packard Company	**Software Availability:**	Mar-2010

Base Compiler Invocation

C benchmarks:
`opencc`

C++ benchmarks:
`openCC`

Base Portability Flags

400.perlbench: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX_X64
401.bzip2: -DSPEC_CPU_LP64
403.gcc: -DSPEC_CPU_LP64
429.mcf: -DSPEC_CPU_LP64
445.gobmk: -DSPEC_CPU_LP64
456.hmmer: -DSPEC_CPU_LP64
458.sjeng: -DSPEC_CPU_LP64
462.libquantum: -DSPEC_CPU_LP64 -DSPEC_CPU_LINUX
464.h264ref: -DSPEC_CPU_LP64
483.xalancbmk: -DSPEC_CPU_LINUX

Base Optimization Flags

C benchmarks:
-march=barcelona -mso -Ofast -CG:local_sched_alg=1
-INLINE:aggressive=on -IPA:plimit=8000 -IPA:small_pu=100
-HP:bdt=2m:heap=2m

C++ benchmarks:
-march=barcelona -mso -Ofast -m32 -INLINE:aggressive=on
-CG:cmp_peep=on -L/root/work/libraries/SmartHeap-8.1/lib -lsmartheap

The flags files that were used to format this result can be browsed at
http://www.spec.org/cpu2006/flags/x86-open64-424-flags-rate-revC.20100901.html
http://www.spec.org/cpu2006/flags/amd-platform-rate-revC.html

You can also download the XML flags sources by saving the following links:
http://www.spec.org/cpu2006/flags/x86-open64-424-flags-rate-revC.20100901.xml
http://www.spec.org/cpu2006/flags/amd-platform-rate-revC.xml

For questions about this result, please contact the tester.
For other inquiries, please contact webmaster@spec.org.

Tested with SPEC CPU2006 v1.1.
Report generated on Wed Jul 23 14:57:41 2014 by SPEC CPU2006 PS/PDF formatter v6932.
Originally published on 17 November 2010.